ST-7L

12VDC Box Mount



ST-7L is shown in Bronze Powder Coat Finish (BZ)

Dimensions: 3" x 5 " x 3/8" thick (faceplate) 2 7/8" H x 4 5/8" W x 3 1/8" D (back box)

- 6061 Marine Grade Aluminum, available in eight standard TGIC powder coat finishes
- Remote transformer required.
- Stainless steel hardware.
- Clear lens.
- Single gang junction box design.
- High-temperature silicone O-ring seal used to seal the cap against the body.
- Molded silicone wire pass-thru attached to socket wire prevents wicking and water leaking into the lamp compartment.
- Input Voltage: 12VDC (remote magnetic transformer required)
- Socket: GU5.3 Bi Pin Porcelain
- Wet Listed
- Specification-grade landscape lighting, wet-location luminaire for step lighting or path lighting applications.

1 PRODUCT	2 MATERIAL	3 WATTAGE	4 CCT	5 FINISH
ST-7L				

Sample Part Number: **ST-7L-A-2-27-BK**

1 PRODUCT

ST-7L

See chart for detailed visual explanation

2 MATERIAL

A Aluminum

B Brass

3 WATTAGE

2 2 Watts
4 4 Watts

test note here

4 CCT

27 2700K
30 4000K

test note here

5 FINISH

BG Beige
BB Black Bronze
BK Black
BKT Black Texture
BZ Bronze
BZT Bronze Texture
SL Silver
WH White


5 year warranty | Warranty only valid with QTL power supplies | Field modifications void warranty | Data subject to change, all data has +/- 5% tolerance

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

ST-7L

12VDC Box Mount

1 PRODUCT - DIMENSIONS



2 MATERIAL



Aluminum

Brass

5 FINISH

Eight Standard TGIC powder coat finishes



Beige

Black

Black Texture

Bronze



Bronze Texture

Black Bronze

Silver

White

ACCESSORIES - LENS

Cap holds up to 3 accessories

SP



Spread Lens

To order separately use AY-1-MR16-1

LI



Linear Lens

To order separately use AY-1-MR16-2

LV



Louver Lens

To order separately use AY-1-MR16-4

WI



Wire Holder

To order separately use AY-1-MR16-5

FR



Frosted Lens

To order separately use AY-1-MR16-6

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

Specification subject to change. Rev-11-11-26

ST-7L

12VDC Box Mount

ACCESSORIES - MOUNTING

MR16 Halogen or LED; GY-6.35 Bi Pin Porcelain Maximum wattage: 50 Watt, 8 Watt LED

MT-1



Ground Stake

Test Note Here

MT-2



Adjustable Ground Stake

Test Note Here

Q-MT-6



Ground Mount

Test Note Here

Q-MT-11



Surface Mount

Test Note Here

Q-MT-14



Tree Mount

Test Note Here

LAMPS

MR16



SORAA

MR16



DAUER

MR16



BRILLIANCE

COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

DIMMING PROTOCOL	OUTDOOR
	LANDSCAPE LIGHTING
Phase	Q-HEX Q-SET-1 Q-SET-2 Q-SET-3 QOMD QOMS

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting