EXCELSIOR IN-4L

12VAC/DC MR16 9W LED In-Ground Well Light



IN-4L Shown in Bronze Texure Powder Coat Finish (BZT)

Dimensions: 7 1/2 " square x 11 1/4"

- Bronze frame and grate.
- Not compatible with electronic transformers.
- 10 degrees of aiming adjustment.
- Aluminum lamp holder.
- Tempered glass lens.
- 6 feet of 16/2 low voltage cable supplied.
- Input Voltage: 12VAC/DC (remote magnetic transformer required)
- Socket: GU5.3 Bi Pin Porcelain
- Wet Listed
- Specification-grade, wet-location direct burial landscape luminaire for uplighting applications.

1 PRODUCT	2 MATERIAL	3 FIXTURE REGRESS	4 FINISH	5 WATTAGE	6 CCT	7 LENS
IN-4L	B			9.0		

Sample Part Number: **IN-4L-B-1-NT-9.0-30-30**

1 PRODUCT

IN-4L	

2 MATERIAL

B	Bronze

3 FIXTURE REGRESS

1	1 3/4" Regress
2	3" Regress (standard)

4 FINISH

BG	Beige
BB	Black Bronze
BK	Black
BKT	Black Texture
BZ	Bronze
BZT	Bronze Texture
SL	Silver
WH	White
DB	Dark Bronze
NT	Natural

DB finish has longer lead time - finish

5 WATTAGE

9.0	9.0W

6 CCT

27	2700K
30	3000K
40	4000K

7 LENS

15	15 Degree Lens
30	30 Degree Lens
45	45 Degree Lens
60	60 Degree Lens


5 year warranty | Warranty only valid with QTL power supplies | Field modifications void warranty | Data subject to change, all data has +/- 5% tolerance

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

EXCELSIOR IN-4L

12VAC/DC MR16 9W LED In-Ground Well Light

1 PRODUCT - DIMENSIONS



2 MATERIAL

Bronze


4 FINISH

Eight Standard TGIC Free powder coat finish.

- Beige
- Black
- Black Texture
- Bronze
- Bronze Texture
- Black Bronze
- Dark Bronze
- Natural
- Silver
- White

ACCESSORIES - LENS

Holds up to two accessories

SP	LI	SO	LV	WI	FR
					
Spread Lens	Linear Lens	Softening Lens	Louver Lens	Wire Holder	Frosted Lens
To order separately	To order separately	To order separately	To order separately	To order separately	To order separately

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

Specification subject to change. Rev-11-11-26

EXCELSIOR IN-4L

12VAC/DC MR16 9W LED In-Ground Well Light

use AY-1-MR16-1 | use AY-1-MR16-2 | use AY-1-MR16-3 | use AY-1-MR16-4 | use AY-1-MR16-5 | use AY-1-MR16-6

COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

DIMMING PROTOCOL	OUTDOOR
	LANDSCAPE LIGHTING
Phase	Q-HEX Q-SET-1 Q-SET-2 Q-SET-3 QOMD QOMS

EXCELSIOR 9W LED MODULE

MR16 LED MODULE



9W LED Module

- Equivalent to MR16 75W Halogen (equivalent CBCP)
- 2700K, 3000K, or 4000K
- 10.8-13.2V AC/DC
- 12W startup draw
- Interchangable lens: 15°, 30°, 45°, 60°
- Compatible with low-voltage magnetic transformers
- Field replaceable

LED MODULE SPECIFICATIONS

WATTAGE	LENS	2700K	3000K	4000K
9W	15°, 30°, 45°, 60°	810 Lumens	835 Lumens	855 Lumens

LED LENS



15° Lens



30° Lens



45° Lens



60° Lens

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting