




EMBD-MITERED

Field Assembled Extrusion- Recessed

SEE THIS EXTRUSION AS A FACTORY BUILT FIXTURE ►



- Flanged LED profile for recessing in walls and millwork
- Mitered edges allow for different configuration options
- Can be mounted with a recessed spring clip for new or remodel applications, or available with a magnetic mounting clip for easy installation

1	2	3	4	5	6	7	8
PRODUCT	FINISH	MOUNTING	LENS	WIRE INPUT/OUTPUT	LEFT END ANGLE	RIGHT END ANGLE	EXTRUSION LENGTH (IN)
EMBDM				NI			

Sample Part Number: **EMBDM-ST-MG-DF-NI-LI45-RI45-48"**

1	PRODUCT	2	FINISH	3	MOUNTING	4	LENS
	EMBDM		ST Satin CU Custom Color		MG Magnet SP Spring Clip Refer to following pages for mounting clip option details and provided quantities.		DF Diffused PR Polar FR Frosted For representation of LED visibility, see Diode Visibility section on following pages.
5	WIRE INPUT/OUTPUT	6	LEFT END ANGLE	7	RIGHT END ANGLE	8	EXTRUSION LENGTH (IN)
	NI Not Installed		LI45 Inner 45° LO45 Outer 45° LFT Flat (no angle) See following pages for mitered angle configuration options		LI45 Inner 45° LO45 Outer 45° LFT Flat (no angle) See following pages for mitered angle configuration options		1" increments from 1" - 98.43" Tolerance +0.0"/-0.5"

COMPATIBLE LED STRIPS

	STATIC WHITE (SW)	STATIC WHITE INDIVIDUALLY ADDRESSABLE (SW-IA)	STATIC WHITE STANDARD (SD-SW)	STATIC WHITE HIGH EFFICACY (SW-HE)	STATIC WHITE HIGH EFFICACY PLUS (SW-HE+)	STATIC WHITE EXTREME TEMP (SW-XT)	DYNAMIC WHITE HIGH EFFICACY (DW-HE)	WARM DIM (WD)	STATIC COLOR (SC)	RGB	RGBW	RGBW HIGH EFFICACY (RGBW-HE)
DRY	✓ W/FT: 1.5, 3.0, 4.0, 5.0		✓ W/FT: 1.0, 2.0, 4.0, 6.0	✓ W/FT: 1.5, 3.0, 6.0	✓ W/FT: 3.0, 6.0		✓ W/FT: 1.5, 2.5	✓ W/FT: 6.0	✓ W/FT: 5.0	✓ W/FT: 6.0	✓ W/FT: 6.0	✓ W/FT: 4.0
DMP	✓ W/FT: 1.5, 3.0, 4.0, 5.0			✓ W/FT: 1.5, 3.0, 6.0			✓ W/FT: 1.5, 2.5		✓ W/FT: 5.0	✓ W/FT: 6.0	✓ W/FT: 6.0	✓ W/FT: 4.0
ENC	✓ W/FT: 1.5, 3.0, 4.0, 5.0			✓ W/FT: 1.5, 3.0, 6.0			✓ W/FT: 1.5, 2.5		✓ W/FT: 5.0	✓ W/FT: 6.0	✓ W/FT: 6.0	✓ W/FT: 4.0
WET	✓ W/FT: 1.5, 3.0, 4.0, 5.0		✓ W/FT: 1.0, 2.0, 4.0		✓ W/FT: 3.0	✓ W/FT: 3.0	✓ W/FT: 1.5, 2.5	✓ W/FT: 6.0	✓ W/FT: 5.0	✓ W/FT: 6.0		✓ W/FT: 4.0

Field modifications must comply with QTL's installation methods otherwise warranty is null & void | Spring clip technology | Suitable for installation in drywall | Painted end caps match the extrusion finish and have a white painted interior. Satin end caps utilize a metallic paint.




EMBD-MITERED


Field Assembled Extrusion- Recessed

SEE THIS EXTRUSION AS A FACTORY BUILT FIXTURE ▶


1 PRODUCT - DIMENSIONS



Profile with flat lens



Profile with flat lens and magnet mounting clip




Profile with flat lens and spring mounting clip

END CAPS


One pair of end caps is provided with each length of extrusion ordered.

Flat end caps



Feed

To order separately, use
EMBD-EC



No feed

To order separately, use
EMBD-EC

2 FINISH



Satin

Custom color available

3 MOUNTING

MG



Magnet Clip

One MG provided per foot.

To order separately use MG-02

SP




Spring Clip

2 clips provided for 4' or less. 4 clips provided
for greater than 4'.

To order separately use SP-01

MMA-02



Magnet Mount
Accessory for MG-02

Sold separately, to order use MMA-02

Each bracket comes with 2 #6 x 5/8 Flat Head
SS

Required when mounting to a non-magnetic
surface

4 DIODE VISIBILITY



Diffused

Polar

Frosted

COMPATIBLE ACCESSORIES

SHIELD B - Small



For use within
extrusions

SHIELD B - Medium



For use within
extrusions



EMBD-MITERED

Field Assembled Extrusion- Recessed

[SEE THIS EXTRUSION AS A FACTORY BUILT FIXTURE ►](#)

6 / 7 LEFT/RIGHT END ANGLE CONFIGURATION OPTIONS

