
EXCELSIOR IN-4L

12VAC/DC MR16 9W LED In-Ground Well Light



Dimensions: 7 1/2 " square x 11 1/4"

- Bronze frame and grate.
- Not compatible with electronic transformers.
- 10 degrees of aiming adjustment.
- Aluminum lamp holder.
- Tempered glass lens.
- 6 feet of 16/2 low voltage cable supplied.
- Input Voltage: 12VAC/DC (remote magnetic transformer required)
- Socket: GU5.3 Bi Pin Porcelain
- Wet Listed
- Specification-grade, wet-location direct burial landscape luminaire for uplighting applications.

IN-4L Shown in Bronze Texure Powder Coat Finish (BZT)

1 PRODUCT	2 MATERIAL	3 FINISH
IN-4L		

Sample Part Number: **IN-4L-B-1-NT-9.0-30-30**

1 PRODUCT	2 MATERIAL	3 FINISH
IN-4L		


5 year warranty | Warranty only valid with QTL power supplies | Field modifications void warranty | Data subject to change, all data has +/- 5% tolerance

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

EXCELSIOR IN-4L

12VAC/DC MR16 9W LED In-Ground Well Light

1 PRODUCT - DIMENSIONS




3 FINISH

ALUMINUM POWDER COAT FINISHES



13/14/15 ACCESSORIES

Holds up to two accessories

SP	LI	SO	LV	WI	FR
					
Spread Lens	Linear Lens	Softening Lens	Louver Lens	Wire Holder	Frosted Lens
To order separately use AY-1-MR16-1	To order separately use AY-1-MR16-2	To order separately use AY-1-MR16-3	To order separately use AY-1-MR16-4	To order separately use AY-1-MR16-5	To order separately use AY-1-MR16-6

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

EXCELSIOR IN-4L

12VAC/DC MR16 9W LED In-Ground Well Light

COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

DIMMING PROTOCOL	OUTDOOR
	LANDSCAPE LIGHTING
Phase	Q-HEX Q-SET-1 Q-SET-2 Q-SET-3 QOMD QOMS

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting