
EXCELSIOR IN-4L

12VAC/DC MR16 9W LED In-Ground Well Light



IN-4L Shown in Bronze Texure Powder Coat Finish (BZT)

Dimensions: 7 1/2 " square x 11 1/4"

- Bronze frame and grate.
- Not compatible with electronic transformers.
- 10 degrees of aiming adjustment.
- Aluminum lamp holder.
- Tempered glass lens.
- 6 feet of 16/2 low voltage cable supplied.
- Input Voltage: 12VAC/DC (remote magnetic transformer required)
- Socket: GU5.3 Bi Pin Porcelain
- Wet Listed
- Specification-grade, wet-location direct burial landscape luminaire for uplighting applications.

VOYA WA 2D ORDERING PROCESS

A Specify Shared Options
Options shared between Up and Down Lights

B Specify Up Light Options
Options only affecting Up Lighting Part of the fixture

C Specify Down Light Options
Options only affecting Down Lighting Part of the fixture

A. SHARED OPTIONS

1 PRODUCT	2 KNUCKLE	3 CRI	4 CCT	5 SNOOT	6 COB	7 BEAM ANGLE	8 MATERIAL	9 FINISH	10 WATTAGE	11 OUTPUT SETTING	12 WEEP HOLE	13 ACCESSORY 1	14 ACCESSORY 2	15 ACCESSORY 3
IN-4L														

Sample Part Number: **IN-4L-B-1-NT-9.0-30-30**

1 PRODUCT	2 KNUCKLE	3 CRI	4 CCT	5 SNOOT	6 COB	7 BEAM ANGLE
IN-4L						

8 MATERIAL	9 FINISH	10 WATTAGE	11 OUTPUT SETTING

12 WEEP HOLE	13 ACCESSORY 1	14 ACCESSORY 2	15 ACCESSORY 3


5 year warranty | Warranty only valid with QTL power supplies | Field modifications void warranty | Data subject to change, all data has +/- 5% tolerance

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

EXCELSIOR IN-4L

12VAC/DC MR16 9W LED In-Ground Well Light

1 PRODUCT - DIMENSIONS




9 FINISH

ALUMINUM POWDER COAT FINISHES



13 / 14 / 15 ACCESSORIES

Holds up to two accessories

SP	LI	SO	LV	WI	FR
					
Spread Lens	Linear Lens	Softening Lens	Louver Lens	Wire Holder	Frosted Lens
To order separately use AY-1-MR16-1	To order separately use AY-1-MR16-2	To order separately use AY-1-MR16-3	To order separately use AY-1-MR16-4	To order separately use AY-1-MR16-5	To order separately use AY-1-MR16-6

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

Specification subject to change. Rev-11-11-26

EXCELSIOR IN-4L

12VAC/DC MR16 9W LED In-Ground Well Light

COMPATIBLE POWER SUPPLIES

DIMMING PROTOCOL	OUTDOOR
	LANDSCAPE LIGHTING
Phase	Q-HEX Q-SET-1 Q-SET-2 Q-SET-3 QOMD QOMS

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting