




FD-3
12V MR11 20W, 3W LED Accent Light



- Machined 6061-T6 copper-free aluminum. Aluminum components are black anodized, then a polyester powder coat finish is applied.
- Stainless steel hardware.
- 2ft. 18/2 LV wire leads.
- Clear tempered glass lens, glued in.
- High-temperature silicone O-ring seal used to seal the cap against the body.
- Molded silicone wire pass-thru attached to socket wire prevents wicking and water leaking into the lamp compartment.
- Wattage: 20 watt, 3 watt LED
- Input Voltage: 12V (remote transformer required)
- Socket: GY 6.35 Bi-Pin Porcelain
- IP Rating: 66
- Specification-grade landscape lighting, wet-location luminaire for uplighting or downlighting applications. Can be utilized for ground mounted, tree mounted or surface mounted installations.

FD-3 Shown in Bronze Powder Coat Finish (BZ)
Knuckle: Tapered & Positive Locking

Dimensions: 1 3/4" dia. x 6" overall

1	2	3
PRODUCT	MATERIAL	FINISH
FD-3	A	

Sample Part Number: **FD-3-A-BK**

1	2	3
PRODUCT	MATERIAL	FINISH
FD-3	A 6061 - T6 Aluminum	<div><div>BG</div>Beige<div>BK</div>Black<div>BKT</div>Black Texture<div>BZ</div>Bronze<div>BZT</div>Bronze Texture<div>SL</div>Silver<div>WH</div>White</div>

10 year warranty for Aluminum | Warranty only valid with QTL power supplies | Field modifications void warranty | Data subject to change, all data has +/- 5% tolerance




FD-3

12V MR11 20W, 3W LED Accent Light


1

PRODUCT - DIMENSIONS



2

MATERIAL



3

FINISH

Standard TGIC powder coat finishes and Clear Anodized finish available



ACCESSORIES - COLOR FILTERS

Holds up to three accessories. Wire Filter Holder is included for each color filter to hold filter in place.

BL	LB	PK	AM	MV	RD	GR	DA
Blue Glass Filter	Light Blue Glass Filter	Pink Glass Filter	Amber Glass Filter	Mercury Vapor Glass Filter	Red Glass Filter	Green Glass Filter	Dichroic Amber Glass Filter
To order separately use AY-2-MR11-BL	To order separately use AY-2-MR11-LB	To order separately use AY-2-MR11-PK	To order separately use AY-2-MR11-AM	To order separately use AY-2-MR11-MV	To order separately use AY-2-MR11-RD	To order separately use AY-2-MR-11GR	To order separately use AY-2-MR11-DA









FD-3

12V MR11 20W, 3W LED Accent Light

ACCESSORIES - LENS

Holds up to three accessories

<div>SP</div> <div></div> <div>Spread Lens</div> <div>To order separately use AY-1-MR11-1</div>	<div>LI</div> <div></div> <div>Linear Lens</div> <div>To order separately use AY-1-MR11-2</div>	<div>SO</div> <div></div> <div>Softening Lens</div> <div>To order separately use AY-1-MR11-3</div>	<div>LV</div> <div></div> <div>Louver Lens</div> <div>To order separately use AY-1-MR11-4</div>	<div>WI</div> <div></div> <div>Wire Holder</div> <div>To order separately use AY-1-MR11-5</div>	<div>FR</div> <div></div> <div>Frosted Lens</div> <div>To order separately use AY-1-MR11-6</div>
--	--	---	--	--	---

ACCESSORIES - MOUNTING

1/2" NPS; Mount options must be order separately

<div>MT-1</div> <div></div> <div>Ground Stake</div>	<div>MT-2</div> <div></div> <div>Adjustable Ground Stake</div>	<div>MT-6</div> <div></div> <div>Stainless Steel Ground Spike</div>	<div>MT-7</div> <div></div> <div>Stainless Steel Ground Spike</div>	<div>MT-8</div> <div></div> <div>Stainless Steel Ground Spike</div>
--	---	--	--	--

LAMPS

MR11 Halogen or LED; GY-6.35 Bi-Pin Porcelain
Maximum wattage: 20 Watt, 3 Watt LED

<div>MR8</div> <div></div> <div>ELI</div>	<div>MR8</div> <div></div> <div>EMERY ALLEN</div>	<div>MR11</div> <div></div> <div>ELI</div>	<div>MR11</div> <div></div> <div>BRILLIANCE</div>	<div>MR11</div> <div></div> <div>EMERY ALLEN</div>
--	--	---	--	---

COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

DIMMING PROTOCOL	OUTDOOR
	LANDSCAPE LIGHTING
Phase	Q-HEX Q-SET-1 Q-SET-2 Q-SET-3 QOMD QOMS