


**RL-5**

12V MR16 35W Halogen/8W LED Pendant Light



RL-5 Shown in Bronze Texture Powder Coat Finish (BZT)



Dimensions: 2 3/8" dia. x 11"

- 1" brass loop for mounting. Hanging hook included.
- 6061 Marine Grade Aluminum components are anodized, then a polyester powder coat finish is applied.
- Stainless steel hardware.
- 12" of 18 ga. wire leads.
- High-temperature silicone O-ring seal used to seal the cap against the body.
- Molded silicone wire pass-thru attached to socket wire prevents wicking and water leaking into the lamp compartment.
- Maximum Wattage: 35W Halogen/8W LED
- Input Voltage: 12V (remote transformer required)
- Socket: GU5.3 Bi-Pin Porcelain
- Wet Listed
- Specification-grade, wet-location landscape luminaire for pendant mounted downlighting applications. Can be utilized for pergola, tree-mounted, and other exterior installations.

1 PRODUCT	2 MATERIAL	3 SS CABLE	4 18/2 WIRE	5 FINISH
RL-5	A			

Sample Part Number: **RL-5-A-0-0-BK**


1 PRODUCT	2 MATERIAL	3 SS CABLE	4 18/2 WIRE	5 FINISH
RL-5	A Aluminum	<p>0 No SS Cable</p> <p>5 5' SS Cable</p> <p>10 10' SS Cable</p> <p>15 15' SS Cable</p> <p>20 20' SS Cable</p> <p>25 25' SS Cable</p> <p>30 30' SS Cable</p>	<p>0 Standard 12" Wire</p> <p>5 Extra 5' Wire</p> <p>10 Extra 10' Wire</p> <p>15 Extra 15' Wire</p> <p>20 Extra 20' Wire</p> <p>25 Extra 25' Wire</p> <p>30 Extra 30' Wire</p> <p>12" wire is standard. Length selected will be added to the standard 12" wire length.</p>	<p>BG Beige</p> <p>BB Black Bronze</p> <p>BK Black</p> <p>BKT Black Texture</p> <p>BZ Bronze</p> <p>BZT Bronze Texture</p> <p>SL Silver</p> <p>WH White</p>

5 year warranty | Warranty only valid with QTL power supplies | Field modifications void warranty | Data subject to change, all data has +/- 5% tolerance

**RL-5**

12V MR16 35W Halogen/8W LED Pendant Light

1 PRODUCT - DIMENSIONS




2 MATERIAL



Aluminum

5 FINISH

Eight Standard TGIC Free powder coat finishes



LAMPS

MR16 Halogen or LED; GU5.3 Bi Pin Porcelain
Maximum wattage: 35W Halogen/8W LED



RL-5

12V MR16 35W Halogen/8W LED Pendant Light

COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

DIMMING PROTOCOL	OUTDOOR
	LANDSCAPE LIGHTING
Phase	Q-HEX Q-SET-1 Q-SET-2 Q-SET-3 QOMD QOMS