




WA-20L

12VAC/DC 9W LED MR16 Wall Mount

10 YEAR
WARRANTY
ALUMINUM
MADE IN AMERICA
FROM DOMESTIC &
FOREIGN PARTS



WA-20L Shown in Bronze Texture Powder Coat Finish (BZT)

Weight: 2.1 lbs
Overall Dimensions: 3" dia. x 6 1/4" overall

- Machined 6061-T6 copper-free aluminum. Aluminum components are anodized, then a polyester powder coat finish is applied.
- Remote magnetic transformer required.
- Not compatible with electronic transformers.
- Stainless steel hardware.
- Junction box mount design.
- 10" 18ga. Teflon coated wire leads.
- Three mounting plate options.
- Clear tempered glass lens, glued in.
- High-temperature silicone O-ring seal used to seal the cap against the body.
- Molded silicone wire pass-thru attached to socket wire prevents wicking and water leaking into the lamp compartment.
- Input Voltage: 12VAC/DC (remote magnetic transformer required)
- Socket: GY 6.35 Bi-Pin Porcelain
- Specification-grade wet-location luminaire for wall mount applications.

| 1 PRODUCT | 2 MATERIAL | 3 MOUNTING PLATE | 4 FINISH | 5 LED LAMP |
|--------------|---------------|---------------------|-------------|---------------|
| WA-20L | A | | | |

Sample Part Number: WA-20L-A-1-BK-52

| 1 PRODUCT | 2 MATERIAL | 3 MOUNTING PLATE | 4 FINISH | 5 LED LAMP |
|--------------|----------------------|---|---|--|
| WA-20L | A 6061 - T6 Aluminum | 1 4/0 Round Mounting Plate 2 4/0 Square Mounting Plate 3 3/0 Round Mounting Plate | AC Aged Copper BG Beige BK Black BKT Black Texture BZ Bronze BZT Bronze Texture SL Silver WH White | 50 2W-9W, 15° Lens 2700K 165-720 51 2W-9W, 30° Lens 2700K 165-720 52 2W-9W, 45° Lens 2700K 165-720 60 2W-9W, 60° Lens 2700K 165-720 53 2W-9W, 15° Lens 3000K 190-800 54 2W-9W, 30° Lens 3000K 190-800 55 2W-9W, 45° Lens 3000K 190-800 61 2W-9W, 60° Lens 3000K 190-800 |

CRI = 85
Adjustable LED Module


10 year warranty for aluminum | Warranty only valid with QTL power supplies | Field modifications void warranty | Data subject to change, all data has +/- 5% tolerance



WA-20L

12VAC/DC 9W LED MR16 Wall Mount

1 PRODUCT - DIMENSIONS



2 MATERIAL



6061 - T6 Aluminum

3 MOUNTING PLATE

Three plate options



4/0 Round
Mounting Plate
5" diameter



4/0 Square
Mounting Plate
5" Square



3/0 Round
Mounting Plate
4" diameter

4 FINISH

Standard TGIC powder coat finishes and Clear Anodized finish available



Aged Copper

Beige

Black

Black Texture



Bronze

Bronze Texture

Silver

White



WA-20L

12VAC/DC 9W LED MR16 Wall Mount

ACCESSORIES - COLOR FILTERS

Holds up to two accessories Wire Filter Holder is included for each color filter to hold filter in place.

| | | | | | | | |
|--|--|--|---|---|---|---|--|
| | | | | | | | |
| BL Blue Glass Filter To order separately use AY-2-MR-16-BL | LB Light Blue Glass Filter To order separately use AY-2-MR-16-LB | PK Pink Glass Filter To order separately use AY-2-MR-16-PK | AM Amber Glass Filter To order separately use AY-2-MR-16-AM | MV Mercury Vapor Glass Filter To order separately use AY-2-MR-16-MV | RD Red Glass Filter To order separately use AY-2-MR-16-RD | GR Green Glass Filter To order separately use AY-2-MR-16-GR | DA Dichroic Amber Glass Filter To order separately use AY-2-MR-16-DA |

ACCESSORIES - LENS

Holds up to two accessories

| | | | | | |
|--|--|---|--|--|---|
| | | | | | |
| SP Spread Lens To order separately use AY-1-MR16-1 | LI Linear Lens To order separately use AY-1-MR16-2 | SO Softening Lens To order separately use AY-1-MR16-3 | LV Louver Lens To order separately use AY-1-MR16-4 | WI Wire Holder To order separately use AY-1-MR16-5 | FR Frosted Lens To order separately use AY-1-MR16-6 |

COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

| DIMMING PROTOCOL | OUTDOOR |
|------------------|--|
| | LANDSCAPE LIGHTING |
| Phase | Q-HEX Q-SET-1 Q-SET-2 Q-SET-3 QOMD QOMS |



9W MULT LEVEL LED

MR16 LED MODULE



- Equivalent to MR16 20W/35W/50W/75W Halogen (equivalent CBCP)
- Four lights levels, 2700K, 3000K, or 4000K
- 10.8-13.2V AC/DC
- 12W startup draw
- Interchangeable lens: 15°, 30°, 45°, 60°
- Superior Light Output and thermal performance compared to LED Replacement Lamps
- Compatible with low-voltage magnetic transformers
- Field replaceable
- Pb Free

9W Mult-Level - 2W, 4W, 6W, 9W
(165 - 860 Lumens)

LED MODULE SPECIFICATIONS

[Calculated L70 = 60000 hour]

| LED MODULE | WATTAGE | CCT | LENS | 2W | 4W | 6W | 9W |
|------------|---------|-------|------|------------|------------|------------|------------|
| 50 | 2W-9W | 2700K | 15 | 165 Lumens | 345 Lumens | 515 Lumens | 720 Lumens |
| 51 | 2W-9W | 2700K | 30 | 165 Lumens | 345 Lumens | 515 Lumens | 720 Lumens |
| 52 | 2W-9W | 2700K | 45 | 165 Lumens | 345 Lumens | 515 Lumens | 720 Lumens |
| 60 | 2W-9W | 2700K | 60 | 165 Lumens | 345 Lumens | 515 Lumens | 720 Lumens |
| 53 | 2W-9W | 3000K | 15 | 190 Lumens | 360 Lumens | 530 Lumens | 800 Lumens |
| 54 | 2W-9W | 3000K | 30 | 190 Lumens | 360 Lumens | 530 Lumens | 800 Lumens |
| 55 | 2W-9W | 3000K | 45 | 190 Lumens | 360 Lumens | 530 Lumens | 800 Lumens |
| 61 | 2W-9W | 3000K | 60 | 190 Lumens | 360 Lumens | 530 Lumens | 800 Lumens |
| 62 | 2W-9W | 4000K | 15 | 210 Lumens | 385 Lumens | 590 Lumens | 860 Lumens |
| 63 | 2W-9W | 4000K | 60 | 210 Lumens | 385 Lumens | 590 Lumens | 860 Lumens |
| 64 | 2W-9W | 4000K | 45 | 210 Lumens | 385 Lumens | 590 Lumens | 860 Lumens |
| 65 | 2W-9W | 4000K | 60 | 210 Lumens | 385 Lumens | 590 Lumens | 860 Lumens |

LED LENS

MR16 Halogen or LED; GY-6.35 Bi Pin Porcelain
Maximum wattage: 50watt, 8 watt LED



15° Lens



45° Lens



30° Lens



60° Lens