




IN-1L

12VAC/DC MR16 9W LED In Ground Light



IN-1L Shown in Bronze Texture Powder Coat Finish
(BZT)



Dimensions: 3 1/16" dia. x 5" long

- 6061 Marine Grade Aluminum components are black anodized, then a polyester powder coat finish is applied.
- Not compatible with electronic transformers.
- Tempered glass lens.
- 6 feet of 16/2 low voltage cable supplied.
- Input Voltage: 12VAC/DC (remote magnetic transformer required)
- Socket: GY 6.35 Bi-pin porcelain
- Wet Listed
- Specification-grade, wet-location direct burial landscape luminaire for uplighting applications.

1 PRODUCT	2 MATERIAL	3 TOP STYLE	4 POUR COLLAR	5 FINISH	6 WATTAGE	7 CCT	8 LENS
IN-1L	A				9.0		

Sample Part Number: IN-1L-A-R-0-BK-9.0-27-30

1 PRODUCT	2 MATERIAL	3 TOP STYLE	4 POUR COLLAR	5 FINISH
IN-1L	A Aluminum	R Round Top S Square Top T Tapered	O None PC Pour Collar No pour collar comes standard unless specified otherwise.	BG Beige BB Black Bronze BK Black BKT Black Texture BZ Bronze BZT Bronze Texture SL Silver WH White
6 WATTAGE	7 CCT	8 LENS		
9.0 9.0W	27 2700K 30 3000K 40 4000K	15 15 Degree Lens 30 30 Degree Lens 45 45 Degree Lens 60 60 Degree Lens		


5 year warranty | Warranty only valid with QTL power supplies | Field modifications void warranty | Data subject to change, all data has +/- 5% tolerance



IN-1L

12VAC/DC MR16 9W LED In Ground Light

1 PRODUCT - DIMENSIONS




2 MATERIAL



Aluminum


5 FINISH

Eight Standard TGIC Free powder coat finishes



ACCESSORIES - COLOR FILTERS

Lens cap holds 2 lens accessory. Wire Filter Holder is included for each color filter to hold filter in place.





IN-1L

12VAC/DC MR16 9W LED In Ground Light

ACCESSORIES - LENS

Holds up to two accessories

SP	LI	SO	LV	WI	FR
Spread Lens To order separately use AY-1-MR16-1	Linear Lens To order separately use AY-1-MR16-2	Softening Lens To order separately use AY-1-MR16-3	Louver Lens To order separately use AY-1-MR16-4	Wire Holder To order separately use AY-1-MR16-5	Frosted Lens To order separately use AY-1-MR16-6

COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

DIMMING PROTOCOL	OUTDOOR
	LANDSCAPE LIGHTING
Phase	Q-HEX Q-SET-1 Q-SET-2 Q-SET-3 QOMD QOMS



9W LED MODULE

MR16 LED MODULE

3 YEAR
WARRANTY



9W LED Module

- Equivalent to MR16 75W Halogen (equivalent CBCP)
- 2700K, 3000K, or 4000K
- 10.8-13.2V AC/DC
- 12W startup draw
- Interchangeable lens: 15°, 30°, 45°, 60°
- Compatible with low-voltage magnetic transformers
- Field replaceable

LED MODULE SPECIFICATIONS

WATTAGE	LENS	2700K	3000K	4000K
9W	15°, 30°, 45°, 60°	810 Lumens	835 Lumens	855 Lumens

LED LENS



15° Lens



30° Lens



45° Lens



60° Lens