MAJOR

Field Assembled Extrusion - Surface

SEE THIS EXTRUSION AS A FACTORY BUILT FIXTURE ▶

- FPO

FPO

1 PRODUCT	2 FINISH	3 MOUNTING	4 LENS	5 WIRE INPUT/OUTPUT	6 EXTRUSION LENGTH (IN)
MAJOR		SST		NI	

Sample Part Number: **MAJOR-ST-SST-DF-NI-48"**

1 PRODUCT

MAJOR

2 FINISH

ST	Satin
BK	Black
WH	White
CU	Custom Color

Custom finishes require a longer lead time, consult factory

3 MOUNTING

SST Stainless Steel

Refer to following pages for mounting clip option details and provided quantities.

4 LENS

DF	Diffused
PM	Prismatic

Lens come in continuous 50' rolls
For representation of LED visibility, see Diode Visibility section on following pages.
For beam angles, see Photometric Performance section on following pages.
For optional snap-on louver ordering, see External Louver Accessory section on following pages.

5 WIRE INPUT/OUTPUT

NI Not Installed

6 EXTRUSION LENGTH (IN)

1" increments from 1" - 98.43" Extrusion Tolerance +0 -1/8".

PRELIMINARY SUBJECT TO CHANGE

COMPATIBLE LED STRIPS

	STATIC WHITE (SW)	STATIC WHITE HIGH EFFICACY (SW-HE)	STATIC WHITE HIGH EFFICACY PLUS (SW-HE+)	DYNAMIC WHITE HIGH EFFICACY (DW-HE)	WARM DIM (WD)	STATIC COLOR (SC)	RGB	RGBW HIGH EFFICACY (RGBW-HE)
DRY	✓ W/FT: 1.5, 3.0, 4.0, 5.0	✓ W/FT: 1.5, 3.0, 6.0, 9.0	✓ W/FT: 3.0, 6.0	✓ W/FT: 1.5, 2.5, 4.0	✓ W/FT: 6.0	✓ W/FT: 5.0	✓ W/FT: 6.0	✓ W/FT: 4.0, 8.0
DMP	✓ W/FT: 1.5, 3.0, 4.0, 5.0	✓ W/FT: 1.5, 3.0, 6.0		✓ W/FT: 1.5, 2.5		✓ W/FT: 5.0	✓ W/FT: 6.0	✓ W/FT: 4.0
ENC								
WET	✓ W/FT: 1.5, 3.0, 4.0, 5.0					✓ W/FT: 5.0	✓ W/FT: 6.0	✓ W/FT: 4.0

Field modifications must comply with QTL's installation methods otherwise warranty is null & void | Surface mount | Painted end caps match the extrusion finish and have a white painted interior. Satin end caps utilize a metallic paint.

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting


Specification subject to change. Rev-11-11-26

MAJOR


Field Assembled Extrusion - Surface

SEE THIS EXTRUSION AS A FACTORY BUILT FIXTURE ▶

1 PRODUCT - DIMENSIONS



Profile




Profile with flat lens and stainless steel mounting clip

END CAPS

One pair of end caps is provided with each length of extrusion ordered.


Flat end caps



No feed

To order separately, use MAJOR-EC

2 FINISH



Satin


Black

White

Custom finishes require a longer lead time, consult factory

3 MOUNTING

SST



Stainless Steel Clip

2 clips provided for 4' or less; 4 clips provided for greater than 4'

To order separately use SST-01

Each clip comes with a #4 x 3/4" Long Flat Head SS

4 DIODE VISIBILITY



DF - Diffused lens

PM - Prismatic lens

PHOTOMETRIC PERFORMANCE

Nominal beam spread shown, beam spread varies based on light engine. For more detailed information, see factory built fixture photometric data.



60°


COMPATIBLE ACCESSORIES

HINGE - HMB-M



Adjustable mounting bracket - Medium

HINGE - HMB-L



Adjustable mounting bracket - Large

HINGE - HMB-XL



Adjustable mounting bracket - XLarge

Q-PIVOT



Small mounting accessory

Q-ANGLE



Adjustable mounting accessory

PRELIMINARY
SUBJECT TO CHANGE

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting