





NL-MICRO

MICRO 5 L BRACKET - ALUMINUM EXTRUSION




- L bracket with no reveal, creating the least amount of cutoff
- Surface mounts from the side, best for wall applications
- Mounts the MICRO 5 family of fixtures
- Paintable finish
- Intended for indoor use only
- Screw mounting track for field installation of fixtures
- Inline bracket slot for seamless run connections
- Durable anodized aluminum

1 PRODUCT	2 FINISH	3 LENGTH (IN)
NL-MICRO		


Sample Part Number: NL-MICRO-ST-48"

1 PRODUCT	2 FINISH	3 LENGTH (IN)
NL-MICRO	ST BK Satin Black	1" increments from 2" - 98.43" Tolerance +0.0"/-0.5" Light engine ordered separately


1 PRODUCT - DIMENSIONS WITH RECOMMENDED PROFILES




Profile



Profile with: ALTA-01



Profile with: ATOM-01



Profile with: TILT-01

Field modifications must comply with QTL's installation methods otherwise warranty is null & void | surface mount



NL-MICRO

MICRO 5 L BRACKET - ALUMINUM EXTRUSION

2 FINISH



Satin




Black

COMPATIBILITY CHART

	ATOM	TILT	WALA	WAVE	NEXUS	ALTA	ANYBEND
Lens Notes	Works with: ATOM-01, ATOM-03	Works with: TILT-01				Works with: ALTA-01, ALTA-03	
SST-08 Stainless Steel Clip	✓	✓				✓	
WSC-02 White Snug Clip			✓	✓	✓		✓
VHB	✓	✓	✓	✓	✓		✓

PHOTOMETRIC PERFORMANCE

Order separately | Tested with SW24/5.0 at 3000K






NL-MICRO

MICRO 5 L BRACKET - ALUMINUM EXTRUSION

JOINER/CONNECTORS



Inline Bracket

1 per length included

6/32" stainless steel, flat tip set
screws, 1/8" long