



PERI - SW-CV CHART

LED Strips - Static White High Efficacy



1 V/WATTS	2 RATED	3 CCT - LUMENS/CRI	4 CONNECTOR/WIRE IN	5 CONNECTOR/WIRE OUT	6 WIRE COLOR	7 WIRE TYPE	8 ILLUMINATED LENGTH
SW-HE24/3.0							

1 V/WATTS SW-HE24/3.0	2 RATED DRY IP20	3 CCT - LUMENS/CRI 20 2000K 362/93 22 2200K 377/96 24 2400K 391/97 27 2700K 398/97 30 3000K 407/98 35 3500K 468/97 40 4000K 462/97	4 CONNECTOR/WIRE IN BW Bare Wire (Standard 24") BRL Barrel CLS Closed End (No feed) CON6 Connector 6" CON24 Connector 24"	5 CONNECTOR/WIRE OUT BW Bare Wire (Standard 24") BRL Barrel CLS Closed End (No feed) CON6 Connector 6" CON24 Connector 24"
	DMP IP54	24 2400K 353/93 27 2700K 323/94 30 3000K 349/97 35 3500K 382/98 40 4000K 405/97	BW Bare Wire (Standard 24") BRL Barrel CON6 Connector 6" CON24 Connector 24"	Connector/Wire In not needed to specify product. Typical selection is BW. BW: Standard length is 24", Max length is 120". Request custom length by writing in part number next to BW (example: BW48)
	WET IP67	20 2000K 309/93 22 2200K 341/96 24 2400K 357/96 27 2700K 369/97 30 3000K 381/98 35 3500K 427/98 40 4000K 411/97	BW Bare Wire (Standard 24") BRL Barrel CON6 Connector 6" CON24 Connector 24"	Connector/Wire In not needed to specify product. Typical selection is BW. BW: Standard length is 24", Max length is 120". Request custom length by writing in part number next to BW (example: BW48)

6 WIRE COLOR WH White BK Black N/A Specify for Barrel Barrel is white	7 WIRE TYPE CL2 Class 2 CL2P Class 2 Plenum Rated N/A Specify for Barrel CL2P only available with bare wire leads (BW)	8 ILLUMINATED LENGTH 2"-384" 2" increments
DRY ► WH White BK Black N/A Specify for Barrel Barrel is black	CL2 Class 2 CL2P Class 2 Plenum Rated N/A Specify for Barrel CL2P only available with bare wire leads (BW)	2"-180" 2" increments
DMP ► WH White BK Black N/A Specify for Barrel Barrel is black	CL2 Class 2 CL2P Class 2 Plenum Rated N/A Specify for Barrel CL2P only available with bare wire leads (BW)	2"-360" 2" increments



PERI - SW-CV CHART

LED Strips - Static White High Efficacy

3 CCT - LUMENS/CRI - DELIVERED LUMENS

[Calculated L70 = 66000 hrs]

Tested with SW-HE24/3.0-DRY


CCT	Lumen/ft	Luminous Efficacy	CRI Ra	CRI R9	TM30 Rf	TM30 Rg
2000K	362	121 Lm/W	93	61	91	101
2200K	377	126 Lm/W	96	90	93	98
2400K	391	130 Lm/W	97	94	92	98
2700K	398	137 Lm/W	97	96	93	100
3000K	407	140 Lm/W	98	96	93	100
3500K	468	156 Lm/W	97	93	91	98
4000K	462	154 Lm/W	97	97	91	98

TEMPERATURE RATINGS


		Min	Max
DRY	Ambient Operating Temp - Surface	-4°F	145°F
	Storage Temp	-4°F	140°F
	Installation Temp	50°F	100°F

4 / 5 CONNECTOR/WIRE - IN/OUT

Connector/Wire In or Out not needed to specify product. Standard configuration is BW for Wire In and CLS for Wire out




6 WIRE COLOR



White

Black

8 ILLUMINATED LENGTH - DIMENSIONS



Section (in)	A	B	C	D
DRY (IP20)	0.47"	0.24"	2.00"	0.07"
DMP (IP54)	0.47"	0.24"	2.00"	0.15"
WET (IP67)	0.55"	0.24"	2.00"	0.16"

COMPATIBLE EXTRUSIONS

	WIDE	ROND	TORQ	TRE3	LALO	TALO	ARKA	TEL A	VEVE	FLUR	EMBD	LATO	MDIN	OPTI	THIN
DRY	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
DMP	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓
WET	✓														



PERI - SW-CV CHART

LED Strips - Static White High Efficacy

COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

DIM TO LEVEL	INDOOR
	SW24/5.0, SW-HE, SW-HE+
Dim to Black	Q6M-DC+CAP QTM-DC+CAP iQ-PH iQ-PH+QD1
0.1%	QT-CAB-QZ-PH/0-10V QT-CAB-eLED+0-10V QT-CAB-eLED+0-10V-AWN QTM-eLED+0-10V QTM-eLED+0-10V-AWN QZ-BOWTIE+DIMMER QZ-DMX QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP
1%	QT-CAB-eLED+DALI-DT6 QT-CAB-eLED+DALI-DT6-AWN QTM-eLED(E) QTM-eLED+DALI-DT6 QTM-eLED+DALI-DT6-AWN QZ-DALI-DT6
10%	Non-Dim Power Supply with SW App Dongle



PERI - SW-CV CHART

LED Strips - Static White High Efficacy

DIMMING PROTOCOL	INDOOR
	SW24/5.0, SW-HE, SW-HE+
Non-Dim	QT-CAB-eLED-ND QTM-eLED-ND QZ-ND
Phase	Q6M-DC+CAP QT-CAB-QZ-PH/0-10V QTM-DC+CAP QTM-eLED(E) QZ-BOWTIE+DIMMER QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP iQ-PH iQ-PH+QD1
0-10V	QT-CAB-QZ-PH/0-10V QT-CAB-eLED+0-10V QT-CAB-eLED+0-10V-AWN QTM-eLED+0-10V QTM-eLED+0-10V-AWN QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP
Lutron Athena	QT-CAB-eLED+0-10V-AWN QT-CAB-eLED+DALI-DT6-AWN QTM-eLED+0-10V-AWN QTM-eLED+DALI-DT6-AWN
ECO System	QTM-eLED(E)
DMX	QZ-DMX
DALI-2: DT6	QT-CAB-eLED+DALI-DT6 QT-CAB-eLED+DALI-DT6-AWN QTM-eLED+DALI-DT6 QTM-eLED+DALI-DT6-AWN QZ-DALI-DT6
SCENE App Dimmed	Non-Dim Power Supply with SW App Dongle

COMPATIBLE MOUNTING ACCESSORIES



COMPATIBLE WIRING ACCESSORIES





PERI - SW-CV CHART

LED Strips - Static White High Efficacy

COMPATIBLE CONTROL ACCESSORIES

SCENE APP DONGLE



Wi-Fi or Bluetooth
Connectivity

COMPATIBLE APPS

SCENE APP



Create and control
scenes and
automations