



# SW-HE+24/3.0

LED Strips - Static White High Efficacy Plus



Declare.

UK  
CA



- Dry and wet rated with 2" cut points
- Field-cuttable up to 196"
- Ambient operating temp: -13-145°F
- Installation temp: 50-100°F | Storage temp: -13-176°F
- Calculated L70 = 55000 hrs

1 V/WATTS	2 RATED	3 CCT - LUMENS/CRI	4 CONNECTOR/WIRE IN	5 CONNECTOR/WIRE OUT	6 WIRE COLOR	7 WIRE TYPE	8 ILLUMINATED LENGTH
SW-HE+24/3.0							

Sample Part Number: **SW-HE+24/3.0-DRY-27-BW-CLS-WH-CL2-48"**

<b>1</b> V/WATTS  <b>SW-HE+24/3.0</b> Voltage: 24VDC Wattage: 3.0W/ft See following pages for compatible power supplies.	<b>2</b> RATED  DRY IP20	<b>3</b> CCT - LUMENS/CRI  27 2700K 613/93 30 3000K 587/92 35 3500K 637/93 40 4000K 716/92	<b>4</b> CONNECTOR/WIRE IN  BW Bare Wire (Standard 24") BRL Barrel CLS Closed End (No feed) CON6 Connector 6" CON24 Connector 24"  Connector/Wire In not needed to specify product. Typical selection is BW. BW: Standard length is 24". Max length is 120". Request custom length by writing in part number next to BW (example: BW48)	<b>5</b> CONNECTOR/WIRE OUT  BW Bare Wire (Standard 24") BRL Barrel CLS Closed End (No feed) CON6 Connector 6" CON24 Connector 24"  Connector/Wire Out not needed to specify product. Typical selection is CLS or BW. BW: Standard length is 24". Max length is 120". Request custom length by writing in part number next to BW (example: BW48)
	<b>WET</b> IP67	<b>27</b> 2700K 451/94 <b>30</b> 3000K 460/92 <b>35</b> 3500K 498/93 <b>40</b> 4000K 637/93	  BW Bare Wire (Standard 24") BRL Barrel CON6 Connector 6" CON24 Connector 24"  Connector/Wire In not needed to specify product. Typical selection is BW. BW: Standard length is 24". Max length is 120". Request custom length by writing in part number next to BW (example: BW48)	  BW Bare Wire (Standard 24") BRL Barrel CLS Closed End (No feed) CON6 Connector 6" CON24 Connector 24"  Connector/Wire Out not needed to specify product. Typical selection is CLS or BW. BW: Standard length is 24". Max length is 120". Request custom length by writing in part number next to BW (example: BW48)
<b>6</b> WIRE COLOR  DRY ► WH White BK Black N/A Specify for Barrel  Barrel is white	<b>7</b> WIRE TYPE  CL2 Class 2 CL2P Class 2 Plenum Rated N/A Specify for Barrel  CL2P only available with bare wire leads (BW)	<b>8</b> ILLUMINATED LENGTH  2"-196" 2" increments  Available in reel lengths of 32' (Class 2) and 100'. Each reel will have a 2' soldered lead wire attached. Contact factory for larger reels.		
<b>WET</b> ► WH White BK Black N/A Specify for Barrel  Barrel is black	  CL2 Class 2 CL2P Class 2 Plenum Rated N/A Specify for Barrel  CL2P only available with bare wire leads (BW)	  2"-196" 2" increments		

5 year warranty | Warranty only valid with QTL power supplies | Field modifications must comply with QTL's installation methods otherwise warranty is null & void | All data has +/- 5% tolerance | UL Listed



# SW-HE+24/3.0

LED Strips - Static White High Efficacy Plus

## 3 CCT - LUMENS/CRI - DELIVERED LUMENS

[Calculated L70 = 55000 hrs]  
Tested with SW-HE+24/3.0-DRY


CCT	Lumen/ft	Luminous Efficacy	CRI Ra	CRI R9	TM30 Rf	TM30 Rg
2700K	613	187 Lm/W	93	65	92	100
3000K	587	179 Lm/W	92	63	91	100
3500K	637	194 Lm/W	93	78	91	100
4000K	716	210 Lm/W	92	59	89	97

## TEMPERATURE RATINGS


		Min	Max
DRY	Ambient Operating Temp - Surface	-13°F	145°F
	Storage Temp	-13°F	176°F
	Installation Temp	50°F	100°F

## 4 / 5 CONNECTOR/WIRE - IN/OUT


Connector/Wire In or Out not needed to specify product. Standard configuration is BW for Wire In and CLS for Wire out



## 6 WIRE COLOR



## 8 ILLUMINATED LENGTH - DIMENSIONS



## COMPATIBLE EXTRUSIONS

	WIDE	ROND	TORQ	TRE3	LALO	TALO	ARKA	TELA	VEVE	FLUR	EMBD	LATO	MDIN	OPTI-FLAT	OPTI-OPTICS	THIN
DRY	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
DMP																
WET	✓				✓	✓	✓	✓					✓			✓

EXCLUDES 30°, 45°, 60° LENS



# SW-HE+24/3.0

LED Strips - Static White High Efficacy Plus

## COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

DIM TO LEVEL	INDOOR	OUTDOOR
	SW24/5.0, SW-HE, SW-HE+	SW24/5.0, SW-HE, SW-HE+
Dim to Black	Q6M-DC+CAP QTM-DC+CAP iQ-PH+QD1	QOM-DC+CAP QOM-PH
0.1%	QT-CAB-QZ-PH/0-10V QT-CAB-eLED+0-10V QT-CAB-eLED+0-10V-AWN QT-CAB-eLED+DALI-DT6 QT-CAB-eLED+DALI-DT6-AWN QTM-eLED+0-10V QTM-eLED+0-10V-AWN QTM-eLED+DALI-DT6 QTM-eLED+DALI-DT6-AWN QZ-BOWTIE+DIMMER QZ-DMX QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP	Q-SET-QZ-DMX Q-SET-QZ-PH/0-10V Q-SET-eLED+0-10V QOM-eLED+0-10V QOM-eLED+DALI-DT6 QOM-eLED+PS-DALI-DT6 QZ-DMX QZ-PH/0-10V
1%	QTM-eLED(E) QZ-DALI-DT6	Q-SET+QZ-DALI-DT6 QZ-DALI-DT6
10%	Non-Dim Power Supply with SW App Dongle	




# SW-HE+24/3.0

LED Strips - Static White High Efficacy Plus

DIMMING PROTOCOL	INDOOR	OUTDOOR
	SW24/5.0, SW-HE, SW-HE+	SW24/5.0, SW-HE, SW-HE+
Non-Dim	QT-CAB-eLED-ND QTM-eLED-ND QZ-ND	Q-SET-QZ-ND Q-SET-eLED-ND QOM-eLED-ND QZ-ND
Phase	Q6M-DC+CAP QT-CAB-QZ-PH/0-10V QTM-DC+CAP QTM-eLED(E) QZ-BOWTIE+DIMMER QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP iQ-PH+QD1	Q-SET-QZ-PH/0-10V QOM-DC+CAP QOM-PH QZ-PH/0-10V
0-10V	QT-CAB-QZ-PH/0-10V QT-CAB-eLED+0-10V QT-CAB-eLED+0-10V-AWN QTM-eLED+0-10V QTM-eLED+0-10V-AWN QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP	Q-SET-QZ-PH/0-10V Q-SET-eLED+0-10V QOM-eLED+0-10V QZ-PH/0-10V
Lutron Athena	QT-CAB-eLED+0-10V-AWN QT-CAB-eLED+DALI-DT6-AWN QTM-eLED+0-10V-AWN QTM-eLED+DALI-DT6-AWN	
ECO System	QTM-eLED(E)	
DMX	QZ-DMX	Q-SET-QZ-DMX QZ-DMX
DALI-2: DT6	QT-CAB-eLED+DALI-DT6 QT-CAB-eLED+DALI-DT6-AWN QTM-eLED+DALI-DT6 QTM-eLED+DALI-DT6-AWN QZ-DALI-DT6	Q-SET+QZ-DALI-DT6 QOM-eLED+DALI-DT6 QZ-DALI-DT6
SCENE App Dimmed	Non-Dim Power Supply with SW App Dongle	

## COMPATIBLE MOUNTING ACCESSORIES

 QUOVA-MICRO	 SHIELD A - Medium	 SHIELD B - Medium	 BL-GRAZER	 BL-MICRO	 BL-LARGE	 SD-L-LARGE	 SD-L-MEDIUM	 SD-L-MICRO	 SD-J-LARGE
QUOVA Knife Edge	For standalone use	For use within extrusions	Backwards L Mounting Bracket	Backwards L Mounting Bracket	Backwards L Mounting Bracket	L Mounting Bracket	L Mounting Bracket	L Mounting Bracket	J Mounting Bracket
 iQ-STRAP	 iQ-CLIP-SS10	 iQ-CLIP-PL							
Plastic strap, Fits all LED strips	Metal clip, Fits WET strip	Plastic clip, Fits WET strip							



# SW-HE+24/3.0

LED Strips - Static White High Efficacy Plus

## COMPATIBLE WIRING ACCESSORIES

<b>Q-NECT-02-LEAD-24</b>  Connects LED board to 24" lead wire DRY ONLY	<b>Q-NECT-02-JUMP-3</b>  Connects two LED boards together with 3" jumper, DRY ONLY	<b>Q-NECT-02-INLINE</b>  Connects two LED boards together DRY ONLY	<b>Q-NECT-SCREW-LEAD-12</b>  Connects LED board to 12" lead wire DRY ONLY	<b>Q-NECT-SCREW-JUMP-12</b>  Connects two LED boards together with 12" jumper, DRY ONLY	<b>Q-mini-J</b>  UL Listed, miniature junction box, DRY/DMP (WET rated with silicone)	<b>Q-mini-J5</b>  UL Listed, miniature junction box, DRY/DMP (WET rated with silicone)	<b>BARREL-EXT</b>  8ft barrel cable extender DRY ONLY	<b>BARREL FOUR-FER</b>  Splits lead from one to four LED Barrel connector fixtures, DRY/DMP	<b>CON120-EXT</b>  10ft Con cable extender DRY/DMP/WET
<b>CON FOUR-FER</b>  Splits lead from one to four LED Con connectors DRY/DMP/WET					<b>CON M - BARREL F</b>  Male con to barrel cable adaptor DRY/DMP				

## COMPATIBLE CONTROL ACCESSORIES

### SCENE APP DONGLE



Wi-Fi or Bluetooth  
Connectivity

## COMPATIBLE APPS

### NFC APP



Read and write  
DMX addresses and  
adjust voltage