



VERS-FLUSH (02) STATIC COLOR

24VDC Linear Fixtures - Surface & Recessed

white optics

UL LISTED

RoHS COMPLIANT

EPD ENVIRONMENTAL PRODUCT DECLARATION 5 YEAR WARRANTY

Certified with Red & Amber

Declare

Red List Approved



- Features a co-extruded lens with an internal reflector, maximizing light delivery for improved brightness.
- The fixture's flat lens sits flush, showcasing the versatile fixture's exceptional light performance in any indoor environment.
- Features integrated metal endcaps
- Mounting options include a concealed or magnetic clip
- With an internal White Optics coating, the fixture achieves greater lumen output
- Durable anodized aluminum housings
- QTL Red & Amber LED products are FWC certified, making them safe for turtles and other wildlife
- Consult factory for field assembly options
- Optional external louver accessory available in white or black for added glare control

INFORMATION REQUIRED FOR LIGHTING SCHEDULE

| 1 PRODUCT | 2 WATTS/ FT | 3 CCT | 4 RATED | 5 LENS | 6 EXTERNAL LOUVER |
|--------------|----------------|----------|------------|-----------|----------------------|
| VERS-02-SC | 5.0 | | DRY | | |

Sample Part Number: VERS-02-SC-5.0-G-DRY-DF-L1-BK-P1-BW-BW-BK-CL2-CC-BK-48"-E

| ADDITIONAL INFORMATION REQUIRED TO ORDER | | | | | | | | | | | | | | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|--|--|
| 7 WIRE INPUT/OUTPUT | 8 CONNECTOR/WIRE IN | 9 CONNECTOR/WIRE OUT | 10 WIRE COLOR | 11 WIRE TYPE | 12 MOUNTING | 13 FINISH | 14 LENGTH (IN) | 15 EXACT/ OPTIMAL | | | | | | |
| 1 VERS-02-SC See following pages for compatible power supplies. | 2 5.0 5.0W/ft | 3 A Amber B Blue G Green R Red | 4 DRY IP20 | 5 DF Diffused PR Polar | 6 L1-WH White Plastic L1-BK Black Plastic L2-ST Satin Anodized Aluminum L2-BK Black Anodized Aluminum L2-WH White Powder Coated Aluminum N/A No Louver | For representation of LED visibility, see Diode Visibility section on following pages. For beam angles, see Photometric Performance section on following pages | | Plastic Louvers come in 12" lengths, multiple pieces will be used to match fixture length. Aluminum louvers come in maximum 98" lengths and will be cut to match fixture length. White and custom painted finishes are not compatible with L2 external louvers. | | | | | | |
| 7 WIRE INPUT/OUTPUT | 8 CONNECTOR/WIRE IN | 9 CONNECTOR/WIRE OUT | 10 WIRE COLOR | 11 WIRE TYPE | 12 MOUNTING | 13 FINISH | 14 LENGTH (IN) | 15 EXACT/ OPTIMAL | | | | | | |
| SINGLE (Input only) S1 End Feed S2 Bottom Feed When using TBC Mounting, a bare wire S2 wire feed is recommended. See install instructions for details. | BW Bare Wire (Standard 36") CON6 Connector 6" CON24 Connector 24" BW: Standard length is 36", Max length is 120". Request custom length by writing in part number next to BW (example: BW48) | CLS Closed End (No feed) | WH White BK Black | CC Concealed Clip MG Magnet TBC-03 9/16" Flat TB-Grid TBC-04 15/16" Flat or Tegular TB-Grid TBC-05 9/16" Tegular TB-Grid or 9/16" Flat TB-Grid, with External Louver TBC-06 9/16" Tegular TB-Grid, with External Louver TBC-07 15/16" Flat TB-Grid, with External Louver TBC-08 15/16" Tegular TB-Grid, with External Louver | ST Satin BK Black BZ Bronze WH White CU Custom White and custom painted finishes are not compatible with external louvers. Custom finishes require a longer lead time, consult factory. | DRY Minimum length is 12", maximum length is 98" not including end caps. Contact us for lengths under 12". | O Optimal Illumination E Exact Specified Length | | | | | | | |
| PASS THROUGH (Input/output) P1 End Feed P2 Bottom Feed When using TBC Mounting, a bare wire P2 wire feed is recommended. See install instructions for details. | BW Bare Wire (Standard 36") CON6 Connector 6" CON24 Connector 24" BW: Standard length is 36", Max length is 120". Request custom length by writing in part number next to BW (example: BW48) | BW Bare Wire (Standard 36") CON6 Connector 6" CON24 Connector 24" BW: Standard length is 36", Max length is 120". Request custom length by writing in part number next to BW (example: BW48) | | | | | | | | | | | | |


5 year warranty | Warranty only valid with QTL power supplies | Field modifications void warranty | Data subject to change, all data has +/- 5% tolerance



VERS-FLUSH (02) STATIC COLOR

24VDC Linear Fixtures - Surface & Recessed

1 PRODUCT - DIMENSIONS



2 DELIVERED LUMENS

[Calculated L70 = 50000 hrs]
Tested with VERS-02-SC-5.0-**-DRY

| | Red | | Green | | Blue | | Amber | |
|----|-------|------------|-------|------------|-------|------------|-------|------------|
| | LM/FT | Wavelength | LM/FT | Wavelength | LM/FT | Wavelength | LM/FT | Wavelength |
| PR | 120 | 634 | 561 | 519 | 127 | 467 | 88 | 595 |
| DF | 114 | 634 | 530 | 519 | 119 | 467 | 83 | 595 |

5 DIODE VISIBILITY



DF - Diffused lens


PR - Polar lens

PHOTOMETRIC PERFORMANCE

Nominal beam spread shown, beam spread varies based on light engine. For more detailed information, see photometric data.

5W/ft | Green

Polar lens





VERS-FLUSH (02) STATIC COLOR


24VDC Linear Fixtures - Surface & Recessed

TEMPERATURE RATINGS


| | | 5.0 W/FT | |
|-----|----------------------------------|----------|-------|
| | | Min | Max |
| DRY | Ambient Operating Temp - Surface | -4°F | 125°F |

6 EXTERNAL LOUVER

PLASTIC




METAL




7 WIRE INPUT/OUTPUT

SINGLE (Input only)



PASS THROUGH (Input/Output)






VERS-FLUSH (02) STATIC COLOR


24VDC Linear Fixtures - Surface & Recessed

CONFIGURATION OPTIONS



8 / 9 CONNECTOR/WIRE – IN/OUT

Connector/Wire In or Out not needed to specify product.



Bare Wire 36"
22 AWG



10 WIRE COLOR



12 MOUNTING

| | | | | |
|-------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|-----------------------------------------------------------|------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| CC (CC-01) | CC (CC-02) | MG | MMA-02 | TBC-03 |
| | | | | |
| Concealed Clip | Louver Concealed Clip Required if L1 or L2 Louver is selected | Magnet Clip | Magnet Mount Accessory for MG-02 | Plastic T-Bar Clip |
| 2 pieces of hardware provided for 4' or less; 4 pieces of hardware provided for greater than 4' | 2 pieces of hardware provided for 4' or less; 4 pieces of hardware provided for greater than 4' | One MG provided per foot To order separately use MG-02 | Sold separately, to order use MMA-02 Each clip comes with a #6 Flat Screw | Use on 9/16" Flat Drop Ceiling 2 clips provided for first 12"; 1 clip provided for each additional 12" or less length |
| To order separately use CC-01 | To order separately use CC-02 | | Required when mounting to a non-magnetic surface | To order separately use TBC-03 Each pair of clips comes with M2.5 x 4mm set screw and Allen key |
| Each clips comes with a #4 x 5/8" Flat Head screw. | Each clips comes with a #4 x 5/8" Flat Head screw. | | | |




VERS-FLUSH (02) STATIC COLOR

24VDC Linear Fixtures - Surface & Recessed

MOUNTING CONTINUED

| TBC-04 | TBC-05 | TBC-06 | TBC-07 | TBC-08 |
|----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|
| | | | | |
| Plastic T-Bar Clip |
| Use on 15/16" Flat or Tegular Drop Ceiling | Use on 9/16" Tegular Drop Ceiling or with Louver on 9/16" Flat Drop Ceiling | Use with Louver on 9/16" Tegular Drop Ceiling | Use with Louver on 15/16" Flat Drop Ceiling | Use with Louver on 15/16" Tegular Drop Ceiling |
| 2 clips provided for first 12"; 1 clip provided for each additional 12" or less length | 2 clips provided for first 12"; 1 clip provided for each additional 12" or less length | 2 clips provided for first 12"; 1 clip provided for each additional 12" or less length | 2 clips provided for first 12"; 1 clip provided for each additional 12" or less length | 2 clips provided for first 12"; 1 clip provided for each additional 12" or less length |
| To order separately use TBC-04 | To order separately use TBC-05 | To order separately use TBC-06 | To order separately use TBC-07 | To order separately use TBC-08 |
| Each pair of clips comes with M2.5 x 4mm set screw and Allen key | Each pair of clips comes with M2.5 x 4mm set screw and Allen Key | Each pair of clips comes with M2.5 x 4mm set screw and Allen key | Each pair of clips comes with M2.5 x 4mm set screw and Allen key | Each pair of clips comes with M2.5 x 4mm set screw and Allen key |

13 FINISH




Satin
Black
Bronze
White

Custom color available

15 EXACT/OPTIMAL FIXTURE LENGTH

Exact fixtures are the exact length specified. Optimal fixtures' length is rounded down based on LED cut points to allow the fixture to be illuminated end to end. For runs with multiple fixtures that need to fill a specific length, it's recommended to order all optimal fixtures with an exact fixture at the end of the run.





VERS-FLUSH (02) STATIC COLOR

24VDC Linear Fixtures - Surface & Recessed

SC DRY LENGTHS BY INCH

Available in any length in between 12" and 98" not including end caps, chart below shows example lengths. Exact fixtures are the length specified. Optimal fixtures' length is rounded down with illumination end to end. All fixtures' tolerance is $+0 - 1/8"$. Consult factory for lengths under 12".

EXACT LENGTH

| Requested Length | Potential dim spot on either end of fixture |
|------------------|---------------------------------------------|
| 12" | 1" |
| 13" | 0.5" |
| 14" | 1" |
| 15" | 0.5" |
| 16" | 1" |
| 17" | 0.5" |
| 18" | 1" |
| 19" | 0.5" |
| 20" | 1" |
| 21" | 0.5" |
| 22" | 1" |
| 23" | 0.5" |
| 24" | 1" |
| 36" | 1" |
| 48" | 1" |
| 60" | 1" |
| 72" | 1" |
| 84" | 1" |
| 96" | 1" |

OPTIMAL LENGTH: highlighted rows are closest to requested nominal length

| Requested Nominal Length | S1 & S2 | | P1 & P2 | |
|--------------------------|----------------|-------------------|----------------|-------------------|
| | S1 End Feed | S2 Bottom Feed | P1 End Feed | P2 Bottom Feed |
| 12" | 10.49" | | 10.74" | |
| 13" | 12.49" | | 12.74" | |
| 14" | 12.49" | | 12.74" | |
| 15" | 14.49" | | 14.74" | |
| 16" | 14.49" | | 14.74" | |
| 17" | 16.49" | | 16.74" | |
| 18" | 16.49" | | 16.74" | |
| 19" | 18.49" | | 18.74" | |
| 20" | 18.49" | | 18.74" | |
| 21" | 20.49" | | 20.74" | |
| 22" | 20.49" | | 20.74" | |
| 23" | 22.49" | | 22.74" | |
| 24" | 22.49" | | 22.74" | |
| 36" | 34.49" | | 34.74" | |
| 48" | 46.49" | | 46.74" | |
| 60" | 58.49" | | 58.74" | |
| 72" | 70.49" | | 70.74" | |
| 84" | 82.49" | | 82.74" | |
| 96" | 94.49" | | 94.74" | |

COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has $+/- 5\%$ tolerance.

| DIM TO LEVEL | INDOOR | |
|--------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | SC | |
| Dim to Black | | Q6M-DC+CAP QTM-DC+CAP iQ-PH iQ-PH+QD1 |
| 0.1% | | QT-CAB-QZ-PH/0-10V QT-CAB-eLED+0-10V QT-CAB-eLED+0-10V-AWN QT-CAB-eLED+DALI-DT6 QT-CAB-eLED+DALI-DT6-AVN QTM-eLED+0-10V QTM-eLED+0-10V-AWN QTM-eLED+DALI-DT6 QTM-eLED+DALI-DT6-AWN QZ-BOWTIE+DIMMER QZ-DMX QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP |
| 1% | | QTM-eLED(E) QZ-DALI-DT6 |
| 10% | | Non-Dim Power Supply with SW App Dongle |



VERS-FLUSH (02) STATIC COLOR

24VDC Linear Fixtures - Surface & Recessed

| DIMMING PROTOCOL | INDOOR |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| | SC |
| Non-Dim | QT-CAB-eLED-ND QTM-eLED-ND QZ-ND |
| Phase | Q6M-DC+CAP QT-CAB-QZ-PH/0-10V QTM-DC+CAP QTM-eLED(E) QZ-BOWTIE+DIMMER QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP iQ-PH iQ-PH+QD1 |
| 0-10V | QT-CAB-QZ-PH/0-10V QT-CAB-eLED+0-10V QT-CAB-eLED+0-10V-AWN QTM-eLED+0-10V QTM-eLED+0-10V-AWN QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP |
| Lutron Athena | QT-CAB-eLED+0-10V-AWN QT-CAB-eLED+DALI-DT6-AWN QTM-eLED+0-10V-AWN QTM-eLED+DALI-DT6-AWN |
| ECO System | QTM-eLED(E) |
| DMX | QZ-DMX |
| DALI-2: DT6 | QT-CAB-eLED+DALI-DT6 QT-CAB-eLED+DALI-DT6-AWN QTM-eLED+DALI-DT6 QTM-eLED+DALI-DT6-AWN QZ-DALI-DT6 |
| SCENE App Dimmed | Non-Dim Power Supply with SW App Dongle |

COMPATIBLE MOUNTING ACCESSORIES

| | | | | | | | | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
| HINGE - HMB-M  1.41" Adjustable mounting bracket - Medium | HINGE - HMB-L  1.46" Adjustable mounting bracket - Large | HINGE - HMB-XL  1.29" Adjustable mounting bracket - XLarge | Q-PIVOT  4" 1.46" Small mounting accessory | Q-ANGLE  .75" 1.38" 1.03" Adjustable mounting accessory | NU-LARGE  | NU-LARGE  | SD-J-LARGE  | BL-LARGE  | NL-LARGE  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|

SD-L-LARGE



L Mounting Bracket



VERS-FLUSH (02) STATIC COLOR

24VDC Linear Fixtures - Surface & Recessed

COMPATIBLE WIRING ACCESSORIES



COMPATIBLE APPS

NFC APP



Read and write
DMX addresses and
adjust voltage