



VERS-GRAZER (04) RGBW

24VDC Linear Fixtures - Surface & Recessed

white optics



RoHS
COMPLIANT

EPD
ENVIRONMENTAL
PRODUCT DECLARATION

5 YEAR
WARRANTY

Declare

Red List
Approved



- Optically enhanced VERSatile fixture with narrow grazing properties ranging from 12° to 36°
- The high-quality lens features a proprietary diffusing agent for superior beam control and clean edges
- Features integrated metal endcaps
- Mounting options include a concealed clip
- With an internal White Optics coating, the fixture achieves greater lumen output
- Durable anodized aluminum housings
- Consult factory for field assembly options
- Optional external louver accessory available in white or black for added glare control

INFORMATION REQUIRED FOR LIGHTING SCHEDULE

| 1 PRODUCT | 2 WATTS/ FT | 3 CCT | 4 RATED | 5 LENS | 6 EXTERNAL LOUVER |
|--------------|----------------|----------|------------|-----------|----------------------|
| VERS-04-RGBW | 6.0 | | | | |

Sample Part Number: VERS-04-RGBW-6.0-RGBW-30-DRY-GZR-L1-BK-P1-BW-BK-CL2-CC-BK-48"-E

| 7 WIRE INPUT/OUTPUT | 8 CONNECTOR/WIRE IN | 9 CONNECTOR/WIRE OUT | 10 WIRE COLOR | 11 MOUNTING | 12 FINISH | 13 LENGTH (IN) | 14 EXACT/OPTIMAL |
|------------------------|------------------------|-------------------------|------------------|----------------|--------------|-------------------|---------------------|
| | | | | | | | |

| 1 PRODUCT | 2 WATTS/FT | 3 CCT | 4 RATED | 5 LENS | 6 EXTERNAL LOUVER |
|---|--------------------|------------------------------------|--|---|--|
| VERS-04-RGBW See following pages for compatible power supplies. | 6.0 6.0W/ft | 27 2700K 30 3000K | DRY DRY DMP DMP PENC PENC | 25D Optical 25° Grazer For representation of LED visibility, see Diode Visibility section on following pages. For beam angles, see Photometric Performance section on following pages | L1-WH White Plastic L1-BK Black Plastic L2-ST Satin Anodized Aluminum L2-BK Black Anodized Aluminum L2-WH White Powder Coated Aluminum N/A No Louver Plastic Louvers come in 12" lengths, multiple pieces will be used to match fixture length. Aluminum louvers come in maximum 98" lengths and will be cut to match fixture length. White and custom painted finishes are not compatible with L2 external louvers. |

| 7 WIRE INPUT/OUTPUT | 8 CONNECTOR/WIRE IN | 9 CONNECTOR/WIRE OUT | 10 WIRE COLOR |
|---|---|--|--|
| SINGLE (Input only) S1 End Feed S2 Bottom Feed S3 Left Side Feed S4 Right Side Feed When using TBC Mounting, a bare wire S2 wire feed is recommended. See install instructions for details. | BW Bare Wire (Standard 36") CON6 Connector 6" CON24 Connector 24" BW: Standard length is 36", Max length is 120". Request custom length by writing in part number next to BW (example: BW48) | CLS Closed End (No feed) | WH White BK Black |
| PASS THROUGH (Input/output) P1 End Feed P2 Bottom Feed P3 Left Side Feed P4 Right Side Feed Pass Through options are not available for PENC rating. When using TBC Mounting, a bare wire P2 wire feed is recommended. See install instructions for details. | BW Bare Wire (Standard 36") CON6 Connector 6" CON24 Connector 24" BW: Standard length is 36", Max length is 120". Request custom length by writing in part number next to BW (example: BW48) | BW Bare Wire (Standard 36") CON6 Connector 6" CON24 Connector 24" BW: Standard length is 36", Max length is 120". Request custom length by writing in part number next to BW (example: BW48) | |
| 11 WIRE TYPE CL2 Class 2 CL2P Plenum Rated CL2P only available with bare wire leads (BW) | 12 MOUNTING CC Concealed Clip TBC-03 9/16" Flat TB-Grid TBC-04 15/16" Flat or Tegular TB-Grid TBC-05 9/16" Tegular TB-Grid or 9/16" Flat TB-Grid, with External Louver TBC-06 9/16" Tegular TB-Grid, with External Louver TBC-07 15/16" Flat TB-Grid, with External Louver TBC-08 15/16" Tegular TB-Grid, with External Louver | 13 FINISH ST Satin BK Black BZ Bronze WH White CU Custom White and custom painted finishes are not compatible with external louvers. Custom finishes require a longer lead time, consult factory. | 14 LENGTH (IN) Minimum length is 12", maximum length is 98" not including end caps. Contact us for lengths under 12". |
| | | | 15 EXACT/OPTIMAL <input checked="" type="radio"/> Optimal Illumination <input type="radio"/> Exact Specified Length Exact fixtures match the exact length you specify, but they may have dim spots at the ends. Optimal fixtures are slightly shorter than the length specified, but provide full illumination from end to end. See Exact/Optimal Fixture Length charts. |


5 year warranty | Warranty only valid with QTL power supplies | Field modifications void warranty | Data subject to change, all data has +/- 5% tolerance



VERS-GRAZER (04) RGBW

24VDC Linear Fixtures - Surface & Recessed

1 PRODUCT - DIMENSIONS



2 DELIVERED LUMENS

[Calculated L70 = 51000 hrs]
Tested with VERS-04-RGBW-**-**-DRY

| | 3000K | | Red | | Green | | Blue | |
|-----|-------|-----|-------|------------|-------|------------|-------|------------|
| | LM/FT | CRI | LM/FT | Wavelength | LM/FT | Wavelength | LM/FT | Wavelength |
| GZR | 155 | 92 | 41 | 632 | 122 | 514 | 36 | 463 |
| 25D | 146 | 93 | 39 | 631 | 108 | 514 | 33 | 464 |



VERS-GRAZER (04) RGBW

24VDC Linear Fixtures - Surface & Recessed

5 DIODE VISIBILITY



Optical lens


GZR - Grazer lens

PHOTOMETRIC PERFORMANCE

Nominal beam spread shown, beam spread varies based on light engine. For more detailed information, see photometric data.


6W/ft

Grazer lens



6W/ft

25D lens




TEMPERATURE RATINGS


| | | 6.0 W/FT | |
|------|----------------------------------|----------|-------|
| | | Min | Max |
| DRY | Ambient Operating Temp - Surface | -4°F | 115°F |
| DMP | Ambient Operating Temp - Surface | -4°F | 110°F |
| PENC | Ambient Operating Temp - Surface | -4°F | 95°F |

6 EXTERNAL LOUVER


PLASTIC



L1-XX




Lumen Multiplier
WH BK




Profile with plastic louver

0.71 0.48


METAL



L2-XX



Lumen Multiplier
WH BK ST



Profile with metal louver




VERS-GRAZER (04) RGBW


24VDC Linear Fixtures - Surface & Recessed

7 WIRE INPUT/OUTPUT


SINGLE (Input only)




PASS THROUGH (Input/Output)




CONFIGURATION OPTIONS




Single End Feed




Connection by others
Non-Continuous End Feed




Connection by others
Non-Continuous Corner Feed




Continuous Bottom Feed



Continuous Side Feed - Left




Continuous Side Feed - Right



Continuous End to End Feed

8 / 9 CONNECTOR/WIRE – IN/OUT

Connector/Wire In or Out not needed to specify product.



Bare Wire 36"
22 AWG



6" or 24" Overall
Wire Connector | 24 AWG
IP67 Rated, UL Listed

10 WIRE COLOR



White









Black



VERS-GRAZER (04) RGBW

24VDC Linear Fixtures - Surface & Recessed

12 MOUNTING

| | | | | |
|--|---|--|---|---|
|  <p>CC (CC-01)</p> <p>.18" .7" 1.25"</p> <p>Concealed Clip</p> <p>2 pieces of hardware provided for 4' or less; 4 pieces of hardware provided for greater than 4'</p> <p>To order separately use CC-01</p> <p>Each clips comes with a #4 x 5/8" Flat Head screw.</p> |  <p>CC (CC-02)</p> <p>.21" .7" 1.25"</p> <p>Louver Concealed Clip Required if L1 or L2 Louver is selected</p> <p>2 pieces of hardware provided for 4' or less; 4 pieces of hardware provided for greater than 4'</p> <p>To order separately use CC-02</p> <p>Each clips comes with a #4 x 5/8" Flat Head screw.</p> |  <p>TBC-03</p> <p>.64" .50" .27"</p> <p>Plastic T-Bar Clip</p> <p>Use on 9/16" Flat Drop Ceiling; not compatible with PENC</p> <p>2 clips provided for first 12"; 1 clip provided for each additional 12" or less length</p> <p>To order separately use TBC-03</p> <p>Each pair of clips comes with M2.5 x 4mm set screw and Allen key</p> |  <p>TBC-04</p> <p>1.02" .50" .27"</p> <p>Plastic T-Bar Clip</p> <p>Use on 15/16" Flat or Tegular Drop Ceiling; not compatible with PENC</p> <p>2 clips provided for first 12"; 1 clip provided for each additional 12" or less length</p> <p>To order separately use TBC-04</p> <p>Each pair of clips comes with M2.5 x 4mm set screw and Allen key</p> |  <p>TBC-05</p> <p>.64" .50" .41"</p> <p>Plastic T-Bar Clip</p> <p>Use on 9/16" Tegular Drop Ceiling or with Louver on 9/16" Flat Drop Ceiling; not compatible with PENC</p> <p>2 clips provided for first 12"; 1 clip provided for each additional 12" or less length</p> <p>To order separately use TBC-05</p> <p>Each pair of clips comes with M2.5 x 4mm set screw and Allen key</p> |
|  <p>TBC-06</p> <p>.64" .50" .48"</p> <p>Plastic T-Bar Clip</p> <p>Use with Louver on 9/16" Tegular Drop Ceiling; not compatible with PENC</p> <p>2 clips provided for first 12"; 1 clip provided for each additional 12" or less length</p> <p>To order separately use TBC-06</p> <p>Each pair of clips comes with M2.5 x 4mm set screw and Allen key</p> |  <p>TBC-07</p> <p>1.02" .50" .47"</p> <p>Plastic T-Bar Clip</p> <p>Use with Louver on 15/16" Flat Drop Ceiling; not compatible with PENC</p> <p>2 clips provided for first 12"; 1 clip provided for each additional 12" or less length</p> <p>To order separately use TBC-07</p> <p>Each pair of clips comes with M2.5 x 4mm set screw and Allen key</p> |  <p>TBC-08</p> <p>1.02" .50" .48"</p> <p>Plastic T-Bar Clip</p> <p>Use with Louver on 15/16" Tegular Drop Ceiling; not compatible with PENC</p> <p>2 clips provided for first 12"; 1 clip provided for each additional 12" or less length</p> <p>To order separately use TBC-08</p> <p>Each pair of clips comes with M2.5 x 4mm set screw and Allen key</p> | | |

13 FINISH



Satin

Black

Bronze

White

Custom color available




VERS-GRAZER (04) RGBW

24VDC Linear Fixtures - Surface & Recessed

15 EXACT/OPTIMAL FIXTURE LENGTH

Exact fixtures are the exact length specified. Optimal fixtures' length is rounded down based on LED cut points to allow the fixture to be illuminated end to end. For runs with multiple fixtures that need to fill a specific length, it's recommended to order all optimal fixtures with an exact fixture at the end of the run.

Optimal Fixtures



Exact Fixtures

RGBW DRY, DMP, PENC LENGTHS BY INCH

Available in any length in between 12" and 98" not including end caps, chart below shows example lengths. Exact fixtures are the length specified. Optimal fixtures' length is rounded down with illumination end to end. All fixtures' tolerance is $+0 - 1/8"$. Consult factory for lengths under 12".

EXACT LENGTH

| Requested Length | Potential dim spot on either end of fixture |
|------------------|---|
| 12" | 2" |
| 13" | 0.5" |
| 14" | 1" |
| 15" | 1.5" |
| 16" | 2" |
| 17" | 0.5" |
| 18" | 1" |
| 19" | 1.5" |
| 20" | 2" |
| 21" | 0.5" |
| 22" | 1" |
| 23" | 1.5" |
| 24" | 2" |
| 36" | 2" |
| 48" | 2" |
| 60" | 2" |
| 72" | 2" |
| 84" | 2" |
| 96" | 2" |

OPTIMAL LENGTH: highlighted rows are closest to requested nominal length

| Requested Nominal Length | S1 & S2 | P1 & P2 | S3 & S4 | P3 & P4 |
|--------------------------|---------|---------|---------|---------|
| 12" | 8.59" | 8.94" | 8.49" | 8.59" |
| 13" | 12.59" | 12.94" | 12.49" | 12.59" |
| 14" | 12.59" | 12.94" | 12.49" | 12.59" |
| 15" | 12.59" | 12.94" | 12.49" | 12.59" |
| 16" | 12.59" | 12.94" | 12.49" | 12.59" |
| 17" | 16.59" | 16.94" | 16.49" | 16.59" |
| 18" | 16.59" | 16.94" | 16.49" | 16.59" |
| 19" | 16.59" | 16.94" | 16.49" | 16.59" |
| 20" | 16.59" | 16.94" | 16.49" | 16.59" |
| 21" | 20.59" | 20.94" | 20.49" | 20.59" |
| 22" | 20.59" | 20.94" | 20.49" | 20.59" |
| 23" | 20.59" | 20.94" | 20.49" | 20.59" |
| 24" | 20.59" | 20.94" | 20.49" | 20.59" |
| 36" | 32.59" | 32.94" | 32.49" | 32.59" |
| 48" | 44.59" | 44.94" | 44.49" | 44.59" |
| 60" | 56.59" | 56.94" | 56.49" | 56.59" |
| 72" | 68.59" | 68.94" | 68.49" | 68.59" |
| 84" | 80.59" | 80.94" | 80.49" | 80.59" |
| 96" | 92.59" | 92.94" | 92.49" | 92.59" |

COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has $+/- 5\%$ tolerance.

| DIM TO LEVEL | INDOOR | | OUTDOOR | |
|--------------|--|--|---------------|---|
| | RGBW, RGBW-HE | | RGBW, RGBW-HE | |
| 0.1% | QT-CAB-eLED+DALI-DT8 QT-CAB-eLED+DMX QTM-eLED+DALI-DT8 QTM-eLED+DMX QZ-DMX | | | Q-SET-QZ-DMX QOM-eLED+DALI-DT8 QOM-eLED+DMX QOM-eLED+PS-DALI-DT8 QZ-DMX |
| 1% | QZ-DALI-DT8 | | | Q-SET+QZ-DALI-DT8 |
| 10% | Non-Dim Power Supply with RGBW App Dongle | | | |




VERS-GRAZER (04) RGBW


24VDC Linear Fixtures - Surface & Recessed

| DIMMING PROTOCOL | INDOOR | OUTDOOR |
|------------------|--|--|
| | RGBW, RGBW-HE | RGBW, RGBW-HE |
| DMX | QTM-eLED+DMX QZ-DMX | Q-SET-QZ-DMX QOM-eLED+DMX QZ-DMX |
| DALI-2: DT8 | QT-CAB-eLED+DALI-DT8 QTM-eLED+DALI-DT8 QZ-DALI-DT8 | Q-SET+QZ-DALI-DT8 QOM-eLED+DALI-DT8 |
| SCENE App Dimmed | Non-Dim Power Supply with RGBW App Dongle | |

COMPATIBLE MOUNTING ACCESSORIES



COMPATIBLE WIRING ACCESSORIES



UL Listed, miniature junction box, DRY/DMP (WET rated with silicone)

COMPATIBLE CONTROL ACCESSORIES



Wi-Fi or Bluetooth Connectivity

COMPATIBLE APPS

NFC APP



Read and write DMX addresses and adjust voltage