




Q-CAP KURV™ STATIC WHITE

24VDC Flexible Fixtures



- Flexible encapsulated fixture
- Side bend
- 6" bend radius
- Interior and exterior rated (not including FC)
- Seven different mounting options
- Available in a seamless configuration for a continuous line of light
- Utilize clear endcaps for continuous runs
- Do not cut Non-Field Cuttable Q-CAP flexible fixtures
- IK10 impact rated

ORDERING PROCESS

A Specify Non-Field Cuttable Q-CAP

B (Optional) Specify field cuttable 4' piece - used to adjust total run length in the field (dry applications only)

A. NON-FIELD CUTTABLE Q-CAP

INFORMATION REQUIRED FOR LIGHTING SCHEDULE

A1	A2	A3	A4	A5	A6
PRODUCT	MOUNTING	RATED	CCT	WATTAGE	LENS

ADDITIONAL INFORMATION REQUIRED TO ORDER

A7	A8	A9	A10	A11	A12
WIRE INPUT/OUTPUT	CONNECTOR/WIRE IN	CONNECTOR/WIRE OUT	END CAPS	LENGTH (IN)	EXACT/OPTIMAL

Sample Part Number: KURV-SW-PPS-2-DRY-30-5.0-ENC/TL-P1-BW-BW-N/A-48"-E

A1 PRODUCT	A2 MOUNTING	A3 RATED	A4 CCT
KURV-SW KURV-SW-USA Select USA option for BA, BAA and BABA projects. See last page for compatible power supplies.	RLC MC SGC PPS-2 PPS-96 PPS-LP-2 PPS-LP-96 WSC BN-SB-SST-16' BN-SB-SST-32' BN-SB-WH-16' BN-SB-WH-32' White snug clip only for indirect cove use, not intended for hanging fixtures upside down. PPS mounting clip recommended for seamless applications	DRY WET SBM SB not recommended to be used in chlorinated water. Available only in S1, S5, or S6 wire exits.	24 27 30 35 40 2400K 2700K 3000K 3500K 4000K
A5 WATTAGE	A6 LENS	A7 WIRE INPUT/OUTPUT	A8 CONNECTOR/WIRE IN
1.5 1.5W-SO 3.0 3.0W-HO 5.0 5.0W-VHO 1.5HE 1.5WHE-SO 3.0HE 3.0WHE-HO 6.0HE 6.0WHE-VHO SO: Standard Output HO: High Output VHO: Very High Output SBM: Available only in 1.5, 3.0, & 5.0 (no HE)	ENC/CL Encapsulated in Clear ENC/TL Encapsulated in Translucent For representation of LED visibility, see Diode Visibility section on following pages	SINGLE (Input only) S1 End Feed S2 Bottom Feed S3 Left Side Feed S4 Right Side Feed S5 Seamless Feed S6 Seamless Feed PASS THROUGH (Input/Output) P1 End Feed P2 Bottom Feed P3 Left Side Feed P4 Right Side Feed P5 Seamless Feed P6 Seamless Feed	BW Bare Wire (Standard 24") BRL Barrel CON6 Connector 6" CON24 Connector 24" BW: Standard length is 24". Max length is 120". Request custom length by writing in part number next to BW (example: BW48)
A9 CONNECTOR/WIRE OUT	A10 END CAPS	A11 LENGTH (IN)	A12 EXACT/OPTIMAL
N/A Closed End (No feed)	CL Clear WH White N/A Not Applicable	Minimum length is 12", maximum length is 191" not including end caps. Contact us for lengths under 12". SW: Available in 1" increments. SW-HE: Available in 2" increments.	O Optimal Illumination E Exact Specified Length Exact fixtures are the exact length specified +0 - 1/8". Optimal fixtures' length is rounded down with illumination end to end. See Exact/Optimal Fixture Length charts.

5 year warranty | Side Bend | Data subject to change, all data has +/- 5% tolerance | Ambient or mounting surface must not be lower than -4°F or higher than: 1.5 - 125°F; 3.0 - 115°F; 5.0 - 108°F | Patent # D863646 S, 10,619,828 B2 | Only FC fixtures are Field-Cuttable per installation instructions | Field Cuttable is not returnable or refundable after it has been cut



Q-CAP KURV™ STATIC WHITE

24VDC Flexible Fixtures

B. FIELD CUTTABLE Q-CAP

INFORMATION REQUIRED FOR LIGHTING SCHEDULE

B1	B2	B3	B4	B5	B6
PRODUCT	MOUNTING	RATED	CCT	WATTAGE	LENS
KURV-FC-SW		DRY			

ADDITIONAL INFORMATION REQUIRED TO ORDER

B7	B8	B9	B10	B11	B12
WIRE INPUT/OUTPUT	CONNECTOR/WIRE IN	CONNECTOR/WIRE OUT	END CAPS	LENGTH (IN)	EXACT / OPTIMAL
		N/A	CL	48"	N/A

Sample Part Number: KURV-SW-PPS-2-DRY-30-5.0-ENC/TL-P1-BW-BW-N/A-48"-E

B1 PRODUCT KURV-FC-SW See last page for compatible power supplies.	B2 MOUNTING RLC Rigid Lock Channel MC Magnetic Clip SGC Side Gaze Channel PPS-2 PVC Clip PPS-96 PVC Channel PPS-LP-2 PVC Low Profile Clip PPS-LP-96 PVC Low Profile Channel WSC White Snug Clip BN-SB-SST-16' 16' BENDIT Side Stainless Steel Channel BN-SB-SST-32' 32' BENDIT Side Stainless Steel Channel BN-SB-WH-16' 16' BENDIT Side White Stainless Channel BN-SB-WH-32' 32' BENDIT Side White Stainless Channel White snug clip only for indirect cove use, not intended for hanging fixtures upside down. PPS mounting clip recommended for seamless applications	B3 RATED DRY IP20	B4 CCT 24 2400K 27 2700K 30 3000K 35 3500K 40 4000K
B5 WATTAGE 1.5 1.5W-SO 3.0 3.0W-HO 5.0 5.0W-VHO 1.5HE 1.5WHE-SO 3.0HE 3.0WHE-HO 6.0HE 6.0WHE-VHO SO: Standard Output HO: High Output VHO: Very High Output SBM available only in 1.5, 3.0, & 5.0 (no HE)	B6 LENS ENC/CL Encapsulated in Clear ENC/TL Encapsulated in Translucent For representation of LED visibility, see Diode Visibility section on following pages	B7 WIRE INPUT/OUTPUT SINGLE (Input only) S1 End Feed S2 Bottom Feed S3 Left Side Feed S4 Right Side Feed S5 Seamless Feed S6 Seamless Feed	B8 CONNECTOR/WIRE IN BW Bare Wire (Standard 24") BRL Barrel CON6 Connector 6" CON24 Connector 24" BW: Standard length is 24", Max length is 120'. Request custom length by writing in part number next to BW (example: BW48)
B10 END CAPS CL Clear Due to cutting, white endcaps are not available.	B11 LENGTH (IN) 48" Nominal Starting Run length is 48.55" for S1, S5, S6 and 48.75" for S2, S3, S4 Each cut point subtracts from the Starting Run Length 15, 3.0, & 5.0 have a 1" cut point 15HE, 3.0HE, & 6.0HE have a 2" cut point S2, S3, & S4 can be cut down to as little as 1.75" for SW & 2.75" for SW-HE S1 can be cut down to as little as 1.55" for SW & 2.55" SW-HE S5 & S6 can be cut down to as little as 6.55"	B12 EXACT/OPTIMAL N/A	


Single ►




Q-CAP KURV™ STATIC WHITE

24VDC Flexible Fixtures


1 PRODUCT - DIMENSIONS







BEND RADIUS



FLEXIBILITY



2 MOUNTING






Q-CAP KURV™ STATIC WHITE


24VDC Flexible Fixtures

MOUNTING CONTINUED




To order separately use KURV-PPS-96

Each clip comes with a #8" flat screw




To order separately use KURV-PPS-LP-2



To order separately use KURV-PPS-LP-96

Each clip comes with a #8" flat screw



BENDIT Channel
Horizontal Stainless Steel
Flexible Channel

Continuous mounting solution for flexible fixtures, 16' or 32' field cuttable lengths

To order separately use either
STND-QCAP-BN-SB-SST-16',
STND-QCAP-BN-SB-SST-32',
STND-QCAP-BN-SB-WH-16', or
STND-QCAP-BN-SB-WH-32'

64 #4-40 1/2" screws provided per
16'

4 / 5 DELIVERED LUMENS

[Calculated L70 = 40000 hrs]
Tested with KURV-SW-WSC-DRY

CCT	1.5W/FT		15HE W/FT		3.0W/FT		3.0HE W/FT		5.0W/FT		6.0HE W/FT	
	ENC/CL	ENC/TL	ENC/CL	ENC/TL	ENC/CL	ENC/TL	ENC/CL	ENC/TL	ENC/CL	ENC/TL	ENC/CL	ENC/TL
	LM	CRI	LM	CRI	LM	CRI	LM	CRI	LM	CRI	LM	CRI
2400K	110	94	103	95	133	93	133	92	197	93	182	93
2700K	110	98	103	97	153	95	146	95	208	98	195	98
3000K	118	98	109	98	150	96	163	96	213	98	198	98
3500K	121	96	115	95	159	98	144	98	213	96	203	97
4000K	128	96	121	96	147	97	127	97	229	97	213	97
	298	97	325	98	298	97	325	98	295	98	305	97
	295	97	295	97	294	97	295	97	295	97	295	97
	445	97	518	97	284	97	518	97	556	98	486	98

6 DIODE VISIBILITY



ENC/CL - Clear encapsulation



ENC/TL - Translucent encapsulation

TEMPERATURE RATINGS

	1.5 W/FT		1.5 HE W/FT		3.0 W/FT		3.0 HE W/FT		5.0 W/FT		6.0 HE W/FT	
	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
Ambient Operating Temp - Surface	-4°F	135°F	-4°F	140°F	-4°F	125°F	-4°F	125°F	-4°F	110°F	-4°F	100°F
Storage Temp	-4°F	140°F	-4°F	140°F	-4°F	140°F	-4°F	140°F	-4°F	140°F	-4°F	140°F
Installation Temp	50°F	100°F	50°F	100°F	50°F	100°F	50°F	100°F	50°F	100°F	50°F	100°F

BUG RATING

WATTAGE	B	U	G
1.5 (ALL CCTs), 3.0 (ALL CCTs), 5.0 (ALL CCTs)	B0	U1	G0
1.5HE (ALL CCTs), 3.0HE (ALL CCTs), 6.0HE ENC/TL (4000K, 2700K)	B0	U1	G0
6.0HE ENC/CL (2400K), 6.0HE ENC/TL (2400K, 2700K)	B0	U1	G1
6.0HE ENC/CL (2700K, 3000K, 3500K, 4000K), 6.0HE ENC/TL (3000K, 3500K)	B0	U2	G1




Q-CAP KURV™ STATIC WHITE


24VDC Flexible Fixtures

7 WIRE INPUT/OUTPUT


SINGLE (Input only)




PASS THROUGH (Input/Output) - Only applicable for Non-Field Cuttable Q-CAP




SEAMLESS SINGLE (Input only)




SEAMLESS PASS THROUGH (Input/Output) - Only applicable for Non-Field Cuttable Q-CAP




CONFIGURATION OPTIONS




Single End Feed




Non-Continuous End Feed




Non-Continuous Corner Feed




Continuous Bottom Feed




Continuous Side Feed - Left




Continuous Side Feed - Right




Seamless Side Feed



Continuous End to End Feed




Field Cuttable - Continuous End to End Feed



Field Cuttable - Seamless Side Feed

FIELD CUTTABLE MARKING



Field cuttable fixtures are sold in 4' increments and go at the end of a run, allowing for easy field adjustment



Note: Only FC fixtures are field cuttable — Do not attempt to cut non FC fixtures.
Cut only on the marked cut lines. Only cut from non-feed end. Do not attempt to cut while power is on.



Q-CAP KURV™ STATIC WHITE

24VDC Flexible Fixtures

SEAMLESS


Shown with bare wire, connectors vary




Omnidirectional
wireways
S5, S6, P5, P6

8 / 9 CONNECTOR/WIRE – IN/OUT


Connector/Wire In or Out not needed to specify product. Typical selection is S1 for Wire Input/Output, BW for Connector/Wire In, N/A for Connector/Wire Out, and WH for End Caps



10 END CAPS (NO FEED)




END CAPS (WITH FEED)




11 LENGTH - WIRING DETAIL

1.5W, 3.0W, 5.0W | Available in 1" increments 12"-19"




1.5HEW, 3.0HEW, 6.0HEW | Available in 2" increments 12"-19"



12 EXACT/OPTIMAL FIXTURE LENGTH

Exact fixtures are the exact length specified. Optimal fixtures' length is rounded down based on LED cut points to allow the fixture to be illuminated end to end. For runs with multiple fixtures that need to fill a specific length, it's recommended to order all optimal fixtures with an exact fixture at the end of the run.





Q-CAP KURV™ STATIC WHITE

24VDC Flexible Fixtures

SW LENGTHS BY INCH

Available in any length in between 12" and 191", chart below shows example lengths. Exact fixtures are the length specified. Optimal fixtures' length is rounded down with illumination end to end. All fixtures' tolerance is $+0 - 1/8"$. Consult factory for lengths under 12".

EXACT LENGTH

Requested Length	Potential dim spot on either end of fixture
12"	.5"
13"	.5"
14"	.5"
15"	.5"
16"	.5"
17"	.5"
18"	.5"
19"	.5"
20"	.5"
21"	.5"
22"	.5"
23"	.5"
24"	.5"
36"	.5"
48"	.5"
60"	.5"
72"	.5"
84"	.5"
96"	.5"

OPTIMAL LENGTH

Requested Nominal Length	S1 S1	S2 & S3 & S4	P1	P2 & P3 & P4	S5 & S6 & P5 & P6
12"	11.45"	11.79"	11.7"	12.38"	11.2"
13"	12.45"	12.79"	12.7"	13.38"	12.2"
14"	13.45"	13.79"	13.7"	14.38"	13.2"
15"	14.45"	14.79"	14.7"	15.38"	14.2"
16"	15.45"	15.79"	15.7"	16.38"	15.2"
17"	16.45"	16.79"	16.7"	17.38"	16.2"
18"	17.45"	17.79"	17.7"	18.38"	17.2"
19"	18.45"	18.79"	18.7"	19.38"	18.2"
20"	19.45"	19.79"	19.7"	20.38"	19.2"
21"	20.45"	20.79"	20.7"	21.38"	20.2"
22"	21.45"	21.79"	21.7"	22.38"	21.2"
23"	22.45"	22.79"	22.7"	23.38"	22.2"
24"	23.45"	23.79"	23.7"	24.38"	23.2"
36"	35.45"	35.79"	35.7"	36.38"	35.2"
48"	47.45"	47.79"	47.7"	48.38"	47.2"
60"	59.45"	59.79"	59.7"	60.38"	59.2"
72"	71.45"	71.79"	71.7"	72.38"	71.2"
84"	83.45"	83.79"	83.7"	84.38"	83.2"
96"	95.45"	95.79"	95.7"	96.38"	95.2"

SW-HE LENGTHS BY INCH

Available in any length in between 12" and 191", chart below shows example lengths. Exact fixtures are the length specified. Optimal fixtures' length is rounded down with illumination end to end. All fixtures' tolerance is $+0 - 1/8"$. Consult factory for lengths under 12".

EXACT LENGTH

Requested Length	Potential dim spot on either end of fixture
12"	1"
13"	.5"
14"	1"
15"	.5"
16"	1"
17"	.5"
18"	1"
19"	.5"
20"	1"
21"	.5"
22"	1"
23"	.5"
24"	1"
36"	1"
48"	1"
60"	1"
72"	1"
84"	1"
96"	1"

OPTIMAL LENGTH: highlighted rows are closest to requested nominal length

Requested Nominal Length	S1 S1	S2 & S3 & S4	P1	P2 & P3 & P4	S5 & S6 & P5 & P6
12"	10.45"	10.85"	10.7"	11.5"	10.2"
13"	12.45"	12.85"	12.7"	11.5"	12.2"
14"	12.45"	12.85"	12.7"	13.5"	12.2"
15"	14.45"	14.85"	14.7"	13.5"	14.2"
16"	14.45"	14.85"	14.7"	15.5"	14.2"
17"	16.45"	16.85"	16.7"	15.5"	16.2"
18"	16.45"	16.85"	16.7"	17.5"	16.2"
19"	18.45"	18.85"	18.7"	17.5"	18.2"
20"	18.45"	18.85"	18.7"	19.5"	18.2"
21"	20.45"	20.85"	20.7"	19.5"	20.2"
22"	20.45"	20.85"	20.7"	21.5"	20.2"
23"	22.45"	22.85"	22.7"	21.5"	22.2"
24"	22.45"	22.85"	22.7"	23.5"	22.2"
36"	34.45"	34.85"	34.7"	35.5"	34.2"
48"	46.45"	46.85"	46.7"	47.5"	46.2"
60"	58.45"	58.85"	58.7"	59.5"	58.2"
72"	70.45"	70.85"	70.7"	71.5"	70.2"
84"	82.45"	82.85"	82.7"	83.5"	82.2"
96"	94.45"	94.85"	94.7"	95.5"	94.2"



Q-CAP KURV™ STATIC WHITE

24VDC Flexible Fixtures

COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

DIM TO LEVEL	INDOOR		OUTDOOR	
	SW24/1.5-4.0	SW24/5.0, SW-HE, SW-HE+	SW24/1.5-4.0	SW24/5.0, SW-HE, SW-HE+
Dim to Black	Q6M-DC+CAP QTM-DC+CAP iQ-PH iQ-PH+QD1	Q6M-DC+CAP QTM-DC+CAP iQ-PH iQ-PH+QD1	QOM-DC+CAP QOM-PH	QOM-DC+CAP QOM-PH
0.1%	QT-CAB-QZ-PH/0-10V QT-CAB-eLED+0-10V QT-CAB-eLED+0-10V-AWN QT-CAB-eLED+DALI-DT6 QT-CAB-eLED+DALI-DT6-AWN QT-eLED+0-10V QTM-eLED+0-10V-AWN QTM-eLED+DALI-DT6 QTM-eLED+DALI-DT6-AWN QZ-BOWTIE+DIMMER QZ-DMX QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP	QT-CAB-QZ-PH/0-10V QT-CAB-eLED+0-10V QT-CAB-eLED+0-10V-AWN QT-CAB-eLED+DALI-DT6 QT-CAB-eLED+DALI-DT6-AWN QT-eLED+0-10V QTM-eLED+0-10V-AWN QTM-eLED+DALI-DT6 QTM-eLED+DALI-DT6-AWN QZ-BOWTIE+DIMMER QZ-DMX QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP	Q-SET-QZ-DMX Q-SET-QZ-PH/0-10V Q-SET-eLED+0-10V QOM-eLED+0-10V QOM-eLED+DALI-DT6 QOM-eLED+PS-DALI-DT6 QZ-DMX QZ-PH/0-10V	Q-SET-QZ-DMX Q-SET-QZ-PH/0-10V Q-SET-eLED+0-10V QOM-eLED+0-10V QOM-eLED+DALI-DT6 QOM-eLED+PS-DALI-DT6 QZ-DMX QZ-PH/0-10V
1%	QTM-eLED(E) QZ-DALI-DT6	QTM-eLED(E) QZ-DALI-DT6	Q-SET+QZ-DALI-DT6 QZ-DALI-DT6	Q-SET+QZ-DALI-DT6 QZ-DALI-DT6
10%	Non-Dim Power Supply with SW App Dongle	Non-Dim Power Supply with SW App Dongle	Q-HEX-mini-DC Q-SET-mLED	


DIMMING PROTOCOL	INDOOR		OUTDOOR	
	SW24/1.5-4.0	SW24/5.0, SW-HE, SW-HE+	SW24/1.5-4.0	SW24/5.0, SW-HE, SW-HE+
Non-Dim	QT-CAB-eLED-ND QTM-eLED-ND QZ-ND	QT-CAB-eLED-ND QTM-eLED-ND QZ-ND	Q-SET-QZ-ND Q-SET-eLED-ND QOM-eLED-ND QZ-ND iQ-ND-50-65	Q-SET-QZ-ND Q-SET-eLED-ND QOM-eLED-ND QZ-ND iQ-ND-50-65
Phase	Q6M-DC+CAP QT-CAB-QZ-PH/0-10V QTM-DC+CAP QTM-eLED(E) QZ-BOWTIE+DIMMER QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP iQ-PH iQ-PH+QD1	Q6M-DC+CAP QT-CAB-QZ-PH/0-10V QTM-DC+CAP QTM-eLED(E) QZ-BOWTIE+DIMMER QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP iQ-PH iQ-PH+QD1	Q-HEX-mini-DC Q-SET-QZ-PH/0-10V Q-SET-mLED QOM-DC+CAP QOM-PH QZ-PH/0-10V	Q-SET-QZ-PH/0-10V QOM-DC+CAP QOM-PH QZ-PH/0-10V
0-10V	QT-CAB-QZ-PH/0-10V QT-CAB-eLED+0-10V QT-CAB-eLED+0-10V-AWN QTM-eLED+0-10V QTM-eLED+0-10V-AWN QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP	QT-CAB-QZ-PH/0-10V QT-CAB-eLED+0-10V QT-CAB-eLED+0-10V-AWN QTM-eLED+0-10V QTM-eLED+0-10V-AWN QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP	Q-SET-QZ-PH/0-10V Q-SET-eLED+0-10V QOM-eLED+0-10V QZ-PH/0-10V	Q-SET-QZ-PH/0-10V Q-SET-eLED+0-10V QOM-eLED+0-10V QZ-PH/0-10V
Lutron Athena	QT-CAB-eLED+0-10V-AWN QT-CAB-eLED+DALI-DT6-AWN QTM-eLED+0-10V-AWN QTM-eLED+DALI-DT6-AWN	QT-CAB-eLED+0-10V-AWN QT-CAB-eLED+DALI-DT6-AWN QTM-eLED+0-10V-AWN QTM-eLED+DALI-DT6-AWN		
ECO System	QTM-eLED(E)	QTM-eLED(E)		
DMX	QZ-DMX	QZ-DMX	Q-SET-QZ-DMX QZ-DMX	Q-SET-QZ-DMX QZ-DMX
DALI-2: DT6	QT-CAB-eLED+DALI-DT6 QT-CAB-eLED+DALI-DT6-AWN QTM-eLED+DALI-DT6 QTM-eLED+DALI-DT6-AWN QZ-DALI-DT6	QT-CAB-eLED+DALI-DT6 QT-CAB-eLED+DALI-DT6-AWN QTM-eLED+DALI-DT6 QTM-eLED+DALI-DT6-AWN QZ-DALI-DT6	Q-SET+QZ-DALI-DT6 QOM-eLED+DALI-DT6 QZ-DALI-DT6	Q-SET+QZ-DALI-DT6 QOM-eLED+DALI-DT6 QZ-DALI-DT6
SCENE App Dimmed	Non-Dim Power Supply with SW App Dongle	Non-Dim Power Supply with SW App Dongle		




Q-CAP KURV™ STATIC WHITE

24VDC Flexible Fixtures

COMPATIBLE MOUNTING ACCESSORIES



COMPATIBLE WIRING ACCESSORIES



COMPATIBLE CONTROL ACCESSORIES

SCENE APP DONGLE



Wi-Fi or Bluetooth Connectivity

COMPATIBLE APPS

NFC APP



Read and write
DMX addresses and
adjust voltage