




# Q-CAP WURM™ FOR WARM DIM APPLICATIONS

## 24VDC Flexible Fixtures



- Flexible encapsulated fixture
- Both helical bend and up/down bend
- 6" bend radius
- Interior and exterior rated (not including FC)
- Two mounting options available
- When using DALI and DMX power supplies, LED wattage must be doubled
- Do not cut Non-Field Cuttable Q-CAP flexible fixtures

1 PRODUCT	2 MOUNTING	3 RATED	4 CCT	5 WATTAGE	6 LENS	7 WIRE INPUT/OUTPUT	8 CONNECTOR/ WIRE IN	9 CONNECTOR/ WIRE OUT	10 END CAPS	11 LENGTH
					ENC/CL	S1		N/A	WH	48"

Sample Part Number: **WURM-DW-WSCS-DRY-24/30-1.5HE-ENC/TL-P1-BW-BW-N/A-48"-E**

<b>1</b> PRODUCT	<b>2</b> MOUNTING	<b>3</b> RATED	<b>4</b> CCT
<b>WURM-DW</b> <b>WURM-DW-USA</b>  Select USA option for BA, BAA and BABA projects.  LED engine is built with 3 wires requiring 0-10v, DMX or DALI control. Using DALI, DMX, or non QTL power supplies may double watts/ft. See last page for compatible power supplies.	<b>MCS</b> <b>WSCS</b> <b>BN-UD-SST-16'</b> <b>BN-UD-SST-32'</b> <b>BN-UD-WH-16'</b> <b>BN-UD-WH-32'</b>  White snug clip only for indirect cove use, not intended for hanging fixtures upside down.	<b>DRY</b> <b>WET</b>  IP20 IP67	<b>24/30</b> <b>27/40</b>  2400K/3000K 2700K/4000K

<b>5</b> WATTAGE	<b>6</b> LENS	<b>7</b> WIRE INPUT/OUTPUT
<b>1.5HE</b> 1.5WHE-SO <b>2.5HE</b> 2.5WHE-HO  SO: Standard Output HO: High Output	<b>ENC/CL</b> Encapsulated in Clear  For representation of LED visibility, see Diode Visibility section on following pages	<b>S1</b> Single 1 (Input only) - End Feed

<b>8</b> CONNECTOR/WIRE IN	<b>9</b> CONNECTOR/WIRE OUT	<b>10</b> END CAPS	<b>11</b> LENGTH
<b>BW</b> Bare Wire (Standard 24") <b>CON6</b> Connector 6" <b>CON24</b> Connector 24"  BW: Standard length is 24". Max length is 120". Request custom length by writing in part number next to BW (example: BW48)	<b>N/A</b> Closed End (No feed)	<b>WH</b> White	<b>48"</b> Optimal  Minimum length is 12", maximum length is 191" not including end caps. Contact us for lengths under 12". Available in 2" increments.


5 year warranty | Warranty only valid with QTL power supplies | Up/Down & Helical Bend | Data subject to change, all data has +/- 5% tolerance | Ambient or mounting surface must not be lower than -4°F or higher than: 1.5HE - 125°F; 2.5HE - 115°F | Patent # D846,786 S, 10,619,828 B2 | Only FC fixtures are Field-Cuttable per installation instructions | Field Cuttable is not returnable or refundable after it has been cut | Field Cuttable is not returnable or refundable after it has been cut



# Q-CAP WURM™ FOR WARM DIM APPLICATIONS


24VDC Flexible Fixtures

## 1 PRODUCT - DIMENSIONS




Profile  
(Standard)

## BEND RADIUS




## FLEXIBILITY



## 2 MOUNTING

### WSCS




White Snug Clip Small  
Indirect uplight

To order separately use WSCS

Each clip comes with a #6x5/8" flat  
screw

### MCS




Magnetic Clip Small  
Cove use only

To order separately use MCS

each clip comes with a #6x1 1/4"  
screw

### BN-UD



BENDIT Channel  
Vertical Stainless Steel  
Flexible Channel

Continuous mounting solution for  
flexible fixtures, 16' or 32' field  
cuttable lengths

To order separately use either  
STND-QCAP-BN-UD-S-SST-16',  
STND-QCAP-BN-UD-S-SST-32',  
STND-QCAP-BN-UD-S-WH-16', or  
STND-QCAP-BN-UD-S-WH-32'

64 #4-40 1/2" screws provided per  
16'



# Q-CAP WURM™ FOR WARM DIM APPLICATIONS

24VDC Flexible Fixtures

## 4 / 5 DELIVERED LUMENS

[Calculated L70 = 40000 hrs]  
Tested with WURM-DW-WSCS-DRY

CCT	1.5HE W/FT		2.5 HE W/FT	
	ENC/CL	ENC/CL	ENC/CL	ENC/CL
	LM	CRI	LM	CRI
2400K	133	92	198	92
2700K	126	96	201	97
3000K	132	97	206	97
4000K	142	97	225	98

## 6 DIODE VISIBILITY



ENC/CL - Clear encapsulation

## TEMPERATURE RATINGS


	DW 1.5 HE W/FT		DW 3.0 HE W/FT		DW 2.5 HE W/FT		DW 5.0 HE W/FT	
	QTL power supply other than DALI, DMX		DALI, DMX, or non-QTL power supply		QTL power supply other than DALI, DMX		DALI, DMX, or non-QTL power supply	
	Min	Max	Min	Max	Min	Max	Min	Max
Ambient Operating Temp - Surface	-4°F	140°F	-4°F	120°F	-4°F	120°F	-4°F	100°F
Storage Temp	-4°F	140°F	**	**	-4°F	140°F	**	**
Installation Temp	50°F	100°F	**	**	50°F	100°F	**	**

## BUG RATING

WATTAGE	B	U	G
6.0 (ALL CCTs), 3.0HE (ALL CCTs), 5.0HE (ALL CCTs)	B0	U1	G0


## 7 WIRE INPUT/OUTPUT

SINGLE (Input only)



End Feed

PASS THROUGH (Input/Output)




End Feed




# Q-CAP WURM™ FOR WARM DIM APPLICATIONS

24VDC Flexible Fixtures


## CONFIGURATION OPTIONS




Single End Feed




Connection by others  
Non-Continuous End Feed



Connection by others  
Non-Continuous Corner Feed




Continuous End to End Feed



Standard Fixture

Field Cuttable - Continuous End to End Feed

## FIELD CUTTABLE MARKING



Field cuttable fixtures are sold in 4' increments and go at the end of a run, allowing for easy field adjustment



**Note:** Only FC fixtures are field cuttable — Do not attempt to cut non FC fixtures.  
Cut only on the marked cut lines. Only cut from non-feed end. Do not attempt to cut while power is on.




# Q-CAP WURM™ FOR WARM DIM APPLICATIONS


24VDC Flexible Fixtures

## 8 / 9 CONNECTOR/WIRE – IN/OUT

Connector/Wire In or Out not needed to specify product. Typical selection is S1 for Wire Input/Output, BW for Connector/Wire In, N/A for Connector/Wire Out, and WH for End Caps




## 10 END CAPS (NO FEED)



White endcaps  
.11" added at end  
.24" dim spot


## END CAPS (WITH FEED)




White endcaps  
.0" added at end  
.38" dim spot

## 11 LENGTH - WIRING DETAIL

Available in 2" increments 12"-191"



## 12 EXACT/OPTIMAL FIXTURE LENGTH



Exact fixtures are the exact length specified. Optimal fixtures' length is rounded down based on LED cut points to allow the fixture to be illuminated end to end. For runs with multiple fixtures that need to fill a specific length, it's recommended to order all optimal fixtures with an exact fixture at the end of the run.



# Q-CAP WURM™ FOR WARM DIM APPLICATIONS

24VDC Flexible Fixtures

## DW LENGTHS BY INCH

Available in any length in between 12" and 191", chart below shows example lengths. Exact fixtures are the length specified. Optimal fixtures' length is rounded down with illumination end to end. All fixtures' tolerance is +0 – 1/8". Consult factory for lengths under 12".

### EXACT LENGTH

Requested Length	Potential dim spot on either end of fixture
12"	1"
13"	.5"
14"	1"
15"	.5"
16"	1"
17"	.5"
18"	1"
19"	.5"
20"	1"
21"	.5"
22"	1"
23"	.5"
24"	1"
36"	1"
48"	1"
60"	1"
72"	1"
84"	1"
96"	1"

### OPTIMAL LENGTH: highlighted rows are closest to requested nominal length

Requested Nominal Length	S1 IN	P1 OUT
12"	10.63"	10.75"
13"	12.63"	12.75"
14"	12.63"	12.75"
15"	14.63"	14.75"
16"	14.63"	14.75"
17"	16.63"	16.75"
18"	16.63"	16.75"
19"	18.63"	18.75"
20"	18.63"	18.75"
21"	20.63"	20.75"
22"	20.63"	20.75"
23"	22.63"	22.75"
24"	22.63"	22.75"
36"	34.63"	34.75"
48"	46.63"	46.75"
60"	58.63"	58.75"
72"	70.63"	70.75"
84"	82.63"	82.75"
96"	94.63"	94.75"

## COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

DIM TO LEVEL	INDOOR	OUTDOOR
	DW-HE Warm Dim Applications	DW-HE Warm Dim Applications
0.1%	QT-CAB-eLED+DALI-DT6 QT-CAB-eLED+DALI-DT8 QT-CAB-eLED+DALI-DT8-AWN QT-CAB-eLED+WD QT-CAB-eLED+WD-AWN QTM-eLED+DALI-DT6 QTM-eLED+DALI-DT8 QTM-eLED+DALI-DT8-AWN QTM-eLED+WD QTM-eLED+WD-AWN QZ-DW	Q-SET-QZ-DW QOM-eLED+DALI-DT6 QOM-eLED+DALI-DT8 QOM-eLED+PS-DALI-DT6 QOM-eLED+PS-DALI-DT8 QOM-eLED+WD QZ-DW
1%	QZ-DALI-DT8	Q-SET+QZ-DALI-DT8 QZ-DALI-DT8
10%	Non-Dim Power Supply with WD App Dongle	




# Q-CAP WURM™ FOR WARM DIM APPLICATIONS


24VDC Flexible Fixtures

DIMMING PROTOCOL	INDOOR	OUTDOOR
	DW-HE Warm Dim Applications	DW-HE Warm Dim Applications
Phase	QZ-DW	Q-SET-QZ-DW QZ-DW
0-10V	QT-CAB-eLED+WD QT-CAB-eLED+WD-AWN QTM-eLED+WD QTM-eLED+WD-AWN QZ-DW	Q-SET-QZ-DW QOM-eLED+WD QZ-DW
Lutron Athena	QT-CAB-eLED+DALI-DT8-AWN QT-CAB-eLED+WD-AWN QTM-eLED+DALI-DT8-AWN QTM-eLED+WD-AWN	
DALI-2: DT6 LED wattage must be doubled for DW-HE products except for AWN	QT-CAB-eLED+DALI-DT6 QTM-eLED+DALI-DT6	QOM-eLED+DALI-DT6
DALI-2: DT8 LED wattage must be doubled for DW-HE products except for AWN	QT-CAB-eLED+DALI-DT8 QT-CAB-eLED+DALI-DT8-AWN QTM-eLED+DALI-DT8 QTM-eLED+DALI-DT8-AWN QZ-DALI-DT8	Q-SET+QZ-DALI-DT8 QOM-eLED+DALI-DT8 QZ-DALI-DT8
SCENE App Dimmed	Non-Dim Power Supply with WD App Dongle	

## COMPATIBLE MOUNTING ACCESSORIES



## COMPATIBLE WIRING ACCESSORIES



UL Listed, miniature junction box, DRY/DMP (WET rated with silicone)

## COMPATIBLE CONTROL ACCESSORIES



Wi-Fi or Bluetooth Connectivity



## Q-CAP WURM™ FOR WARM DIM APPLICATIONS

24VDC Flexible Fixtures

---

### COMPATIBLE APPS

#### NFC APP



Read and write  
DMX addresses and  
adjust voltage