





# MDIN

## Field Assembled Extrusion - Recessed



- Flush installation LED aluminum extrusion
- Designed to be placed within a drywall application, with its 'wings' then covered with tape and mud for a seamless look
- Once inside the drywall, there's a very small nominal 1/10" reveal showing the light so it is nearly flush

1	2	3	4	5	6
PRODUCT	FINISH	MOUNTING	LENS	WIRE INPUT/OUTPUT	EXTRUSION LENGTH (IN)
MDIN		SST	DF	NI	

Sample Part Number: **MDIN-ST-SST-DF-NI-48"**

<b>1</b>	<b>PRODUCT</b>	<b>2</b>	<b>FINISH</b>	<b>3</b>	<b>MOUNTING</b>
MDIN		<b>ST</b> Satin <b>CU</b> Custom Color  Custom finishes require a longer lead time, consult factory		<b>SST</b> Stainless Steel  Refer to following pages for mounting clip option details and provided quantities.	
<b>4</b>	<b>LENS</b>	<b>5</b>	<b>WIRE INPUT/OUTPUT</b>	<b>6</b>	<b>EXTRUSION LENGTH (IN)</b>
<b>DF</b> Diffused  For representation of LED visibility, see Diode Visibility section on following pages. For beam angles, see Photometric Performance section on following pages.		<b>NI</b> Not Installed		1" increments from 1" - 98.43" Tolerance +0.0"/-0.5"	

## COMPATIBLE LED STRIPS

	STATIC WHITE (SW)	STATIC WHITE STANDARD (SD-SW)	STATIC WHITE HIGH EFFICACY (SW-HE)	STATIC WHITE HIGH EFFICACY PLUS (SW-HE+)	STATIC WHITE EXTREME TEMP (SW-XT)	STATIC WHITE DOUBLE ROW (SW-DR)	STATIC WHITE HIGH EFFICACY DOUBLE ROW (SW-HE-DR)	DYNAMIC WHITE HIGH EFFICACY (DW-HE)	WARM DIM (WD)	STATIC COLOR (SC)	RGB	RGBW	RGBW HIGH EFFICACY (RGBW-HE)
DRY	✓ W/FT: 1.5, 3.0, 4.0, 5.0	✓ W/FT: 1.0, 2.0, 4.0, 6.0	✓ W/FT: 1.5, 3.0, 6.0	✓ W/FT: 3.0, 6.0				✓ W/FT: 1.5, 2.5	✓ W/FT: 6.0	✓ W/FT: 5.0	✓ W/FT: 6.0	✓ W/FT: 6.0	✓ W/FT: 4.0
DMP	✓ W/FT: 1.5, 3.0, 4.0, 5.0		✓ W/FT: 1.5, 3.0, 6.0					✓ W/FT: 1.5, 2.5		✓ W/FT: 5.0	✓ W/FT: 6.0	✓ W/FT: 6.0	✓ W/FT: 4.0
ENC													
WET	✓ W/FT: 1.5, 3.0, 4.0, 5.0	✓ W/FT: 1.0, 2.0, 4.0		✓ W/FT: 3.0, 6.0				✓ W/FT: 1.5, 2.5	✓ W/FT: 6.0	✓ W/FT: 5.0	✓ W/FT: 6.0		✓ W/FT: 4.0


Field modifications must comply with QTL's installation methods otherwise warranty is null & void | Recess mounted with adhesive only | Painted end caps match the extrusion finish and have a white painted interior. Satin end caps utilize a metallic paint.




# MDIN

## Field Assembled Extrusion - Recessed

### 1 PRODUCT - DIMENSIONS



Profile




Profile with stainless steel mounting clip

### END CAPS

One pair of end caps is provided with each length of extrusion ordered.

Flat end caps



Feed

To order separately, use MDIN-S-EC

### 2 FINISH




Satin

Custom finishes require a longer lead time, consult factory

### 3 MOUNTING

SST



Stainless Steel Clip

2 clips provided for 4' or less; 4 clips provided for greater than 4'

To order separately use SST-05

Each clip comes with a #4 x 5/8" Flat Head SS

### 4 DIODE VISIBILITY



DF - Diffused lens

### PHOTOMETRIC PERFORMANCE

Nominal beam spread shown, beam spread varies based on light engine. For more detailed information, see factory built fixture photometric data.

DF



Diffused 117°