





BL-MICRO

MICRO 5 BACKWARDS L BRACKET - ALUMINUM EXTRUSION




- Backwards L bracket with no reveal, creating the least amount of cutoff
- Surface mount from the bottom, ideal for illuminating pre-existing cove applications
- Mounts the MICRO 5 family of fixtures, LED light engines, and SHIELD
- Paintable finish
- Intended for indoor use only
- Mounting clips conveniently preinstalled for hassle-free installation
- Durable anodized aluminum

| 1 | 2 | 3 | 4 |
|----------|--------|----------|-------------|
| PRODUCT | FINISH | MOUNTING | LENGTH (IN) |
| BL-MICRO | | | |


Sample Part Number: BL-MICRO-ST-SST-08-48"

| 1 | 2 | 3 | 4 |
|----------|---------------------------------------|--|--|
| PRODUCT | FINISH | MOUNTING | LENGTH (IN) |
| BL-MICRO | <div>STSatin</div> <div>BKBlack</div> | <div>SST-08Stainless Steel Clip</div> <div>WSC-02White Snug Clip</div> <div>VHBVHB Tape</div> <div>N/ANo Clip (For Light Engine)</div> <div>Mounting clips preinstalled</div> <div>See MOUNTING COMPATIBILITY CHART for more information</div> | <div>1" increments from 2" - 98.43"</div> <div>Tolerance +0.0/-0.5"</div> <div>Light engine ordered separately</div> |


1 PRODUCT - DIMENSIONS WITH RECOMMENDED PROFILES



Profile



profile with: ALTA-01



profile with: ATOM-01



profile with: SHLD-B



profile with: TILT-01

Field modifications must comply with QTL's installation methods otherwise warranty is null & void | Surface mount



BL-MICRO

MICRO 5 BACKWARDS L BRACKET - ALUMINUM EXTRUSION

2


FINISH



3

MOUNTING


SST
(SST-08)



Stainless Steel Clip

To order separately use
SST-08

WSC
(WSC-02)



White Snug Clip

To order separately use
WSC-02










VHB TAPE
(TAPE-VHB-IP67-5)



Sold separately

10MM wide VHB Tape
To order separately use
TAPE-VHB-IP67-5

COMPATIBILITY CHART

| |  ATOM |  TILT |  WALA |  WAVE |  NEXUS |  ALTA |  ANYBEND |  SHIELD-B |  LIGHT ENGINE |
|-----------------------------------|---|---|---|---|--|--|--|---|---|
| Lens Notes | Works with: ATOM-01, ATOM-03 | Works with: TILT-01 | | | | Works with: ALTA-01, ALTA-03 | | | |
| SST-08 Stainless Steel Clip | ✓ | ✓ | | | | ✓ | | | |
| WSC-02 White Snug Clip | | | ✓ | ✓ | ✓ | | ✓ | | |
| VHB | ✓ | ✓ | ✓ | ✓ | ✓ | | ✓ | | |
| N/A | | | | | | | | ✓ | ✓ |



BL-MICRO

MICRO 5 BACKWARDS L BRACKET - ALUMINUM EXTRUSION

LIGHT ENGINE COMPATIBILITY CHART

Order Separately

| LED Strips No extrusion | STATIC WHITE (SW) | STATIC WHITE INDIVIDUALLY ADDRESSABLE (SW-IA) | STATIC WHITE STOCKING DISTRIBUTOR (SD-SW) | STATIC WHITE HIGH EFFICACY (SW-HE) | STATIC WHITE HIGH EFFICACY PLUS (SW-HE+) | STATIC WHITE EXTREME TEMP (SW-XT) | DYNAMIC WHITE HIGH EFFICACY (DW-HE) | WARM DIM (WD) | STATIC COLOR (SC) | RGB | RGBW | RGBW HIGH EFFICACY (RGBW-HE) |
|----------------------------|----------------------------------|--|--|--|---|---|--|------------------|----------------------|----------------|----------------|------------------------------------|
| DRY | ✓ W/FT: 1.5, 3.0, 4.0, 5.0 | ✓ W/FT: 5.0 | ✓ W/FT: 1.0, 2.0, 4.0, 6.0 | ✓ W/FT: 1.5, 3.0, 6.0, 9.0 | ✓ W/FT: 3.0, 6.0 | | ✓ W/FT: 1.5, 2.5, 4.0 | ✓ W/FT: 6.0 | ✓ W/FT: 5.0 | ✓ W/FT: 6.0 | ✓ W/FT: 6.0 | ✓ W/FT: 4.0, 8.0 |
| DMP | ✓ W/FT: 1.5, 3.0, 4.0, 5.0 | | | ✓ W/FT: 1.5, 3.0, 6.0 | | | | | ✓ W/FT: 5.0 | ✓ W/FT: 6.0 | ✓ W/FT: 6.0 | ✓ W/FT: 4.0 |
| WET | ✓ W/FT: 1.5, 3.0, 4.0, 5.0 | | ✓ W/FT: 1.0, 2.0, 4.0, 6.0 | ✓ W/FT: 1.5, 3.0, 6.0 | ✓ W/FT: 3.0, 6.0 | ✓ W/FT: 3.0 | | ✓ W/FT: 6.0 | ✓ W/FT: 5.0 | ✓ W/FT: 6.0 | ✓ W/FT: 6.0 | ✓ W/FT: 4.0 |

ACCESSORY COMPATIBILITY CHART

Order Separately | Only Compatible with DRY

| LED Strips No extrusion | | STATIC WHITE (SW) | STATIC WHITE INDIVIDUALLY ADDRESSABLE (SW-IA) | STATIC WHITE STOCKING DISTRIBUTOR (SD-SW) | STATIC WHITE HIGH EFFICACY (SW-HE) | STATIC WHITE HIGH EFFICACY PLUS (SW-HE+) | STATIC WHITE EXTREME TEMP (SW-XT) | DYNAMIC WHITE HIGH EFFICACY (DW-HE) | WARM DIM (WD) | STATIC COLOR (SC) | RGB | RGBW | RGBW HIGH EFFICACY (RGBW-HE) |
|----------------------------|---|----------------------------------|--|--|--|---|---|--|------------------|----------------------|----------------|----------------|------------------------------------|
| SHIELD-B | S | ✓ W/FT: 1.5, 3.0, 4.0, 5.0 | | ✓ W/FT: 2.0, 4.0, 6.0 | | | | | | ✓ W/FT: 5.0 | | | |
| | M | | ✓ W/FT: 5.0 | | | ✓ W/FT: 3.0, 6.0 | | ✓ W/FT: 1.5, 2.5 | ✓ W/FT: 6.0 | | ✓ W/FT: 6.0 | | ✓ W/FT: 4.0 |
| | L | | | | ✓ W/FT: 1.5, 3.0, 6.0 | | | | | | | ✓ W/FT: 6.0 | |



BL-MICRO

MICRO 5 BACKWARDS L BRACKET - ALUMINUM EXTRUSION

COMPATIBLE SHIELD

Order separately | See SHIELD cut sheet for more information



Profile - S



Profile - M



Profile - L

PHOTOMETRIC PERFORMANCE

Tested with SW24/4.0 at 3000K

