





SD-L-MICRO

MICRO 5 L BRACKET - ALUMINUM EXTRUSION



- L bracket with no reveal, creating the least amount of cutoff
- Surface mounts from the side, best for wall applications
- Mounts the MICRO 5 family of fixtures, LED light engines, and SHIELD
- Paintable finish
- Intended for indoor use only
- Mounting clips conveniently preinstalled for hassle-free installation
- Durable anodized aluminum


1	2	3	4
PRODUCT	FINISH	MOUNTING	LENGTH (IN)
SD-L-MICRO			

Sample Part Number: SD-L-MICRO-ST-SST-08-48"


1	2	3	4
PRODUCT	FINISH	MOUNTING	LENGTH (IN)
SD-L-MICRO	<div>STSatin</div> <div>BKBlack</div>	<div>SST-08Stainless Steel Clip</div> <div>WSC-02White Snug Clip</div> <div>VHBVHB Tape</div> <div>N/ANo Clip (For Light Engine)</div> <div>Mounting clips preinstalled</div> <div>See MOUNTING COMPATIBILITY CHART for more information</div>	<div>1" increments from 2" - 98.43"</div> <div>Tolerance +0.0/-0.5"</div> <div>Light engine ordered separately</div>

1


PRODUCT - DIMENSIONS WITH RECOMMENDED PROFILES




Profile




profile with: ALTA-01



profile with: ATOM-01



profile with: TILT-01



profile with: SHLD-B

Field modifications must comply with QTL's installation methods otherwise warranty is null & void | Surface mount



SD-L-MICRO

MICRO 5 L BRACKET - ALUMINUM EXTRUSION

2


FINISH



3

MOUNTING


SST  
(SST-08)



Stainless Steel Clip

To order separately use  
SST-08

WSC  
(WSC-02)



White Snug Clip

To order separately use  
WSC-02










VHB TAPE  
(TAPE-VHB-IP67-5)



Sold separately

10MM wide VHB Tape  
To order separately use  
TAPE-VHB-IP67-5

COMPATIBILITY CHART

	 ATOM	 TILT	 WALA	 WAVE	 NEXUS	 ALTA	 ANYBEND	 SHIELD-B	 LIGHT ENGINE
Lens Notes	Works with: ATOM-01, ATOM-03	Works with: TILT-01				Works with: ALTA-01, ALTA-03			
SST-08 Stainless Steel Clip	✓	✓				✓			
WSC-02 White Snug Clip			✓	✓	✓		✓		
VHB	✓	✓	✓	✓	✓		✓		
N/A								✓	✓



SD-L-MICRO

MICRO 5 L BRACKET - ALUMINUM EXTRUSION

LIGHT ENGINE COMPATIBILITY CHART

Order Separately

LED Strips No extrusion	STATIC WHITE (SW)	STATIC WHITE INDIVIDUALLY ADDRESSABLE (SW-IA)	STATIC WHITE STOCKING DISTRIBUTOR (SD-SW)	STATIC WHITE HIGH EFFICACY (SW-HE)	STATIC WHITE HIGH EFFICACY PLUS (SW-HE+)	STATIC WHITE EXTREME TEMP (SW-XT)	DYNAMIC WHITE HIGH EFFICACY (DW-HE)	WARM DIM (WD)	STATIC COLOR (SC)	RGB	RGBW	RGBW HIGH EFFICACY (RGBW-HE)
DRY	✓ W/FT: 1.5, 3.0, 4.0, 5.0	✓ W/FT: 5.0	✓ W/FT: 1.0, 2.0, 4.0, 6.0	✓ W/FT: 1.5, 3.0, 6.0, 9.0	✓ W/FT: 3.0, 6.0		✓ W/FT: 1.5, 2.5, 4.0	✓ W/FT: 6.0	✓ W/FT: 5.0	✓ W/FT: 6.0	✓ W/FT: 6.0	✓ W/FT: 4.0, 8.0
DMP	✓ W/FT: 1.5, 3.0, 4.0, 5.0			✓ W/FT: 1.5, 3.0, 6.0					✓ W/FT: 5.0	✓ W/FT: 6.0	✓ W/FT: 6.0	✓ W/FT: 4.0
WET	✓ W/FT: 1.5, 3.0, 4.0, 5.0		✓ W/FT: 1.0, 2.0, 4.0, 6.0	✓ W/FT: 1.5, 3.0, 6.0	✓ W/FT: 3.0, 6.0	✓ W/FT: 3.0		✓ W/FT: 6.0	✓ W/FT: 5.0	✓ W/FT: 6.0	✓ W/FT: 6.0	✓ W/FT: 4.0

ACCESSORY COMPATIBILITY CHART

Order Separately | Only Compatible with DRY

LED Strips No extrusion		STATIC WHITE (SW)	STATIC WHITE INDIVIDUALLY ADDRESSABLE (SW-IA)	STATIC WHITE STOCKING DISTRIBUTOR (SD-SW)	STATIC WHITE HIGH EFFICACY (SW-HE)	STATIC WHITE HIGH EFFICACY PLUS (SW-HE+)	STATIC WHITE EXTREME TEMP (SW-XT)	DYNAMIC WHITE HIGH EFFICACY (DW-HE)	WARM DIM (WD)	STATIC COLOR (SC)	RGB	RGBW	RGBW HIGH EFFICACY (RGBW-HE)
SHIELD-B	S	✓ W/FT: 1.5, 3.0, 4.0, 5.0		✓ W/FT: 2.0, 4.0, 6.0						✓ W/FT: 5.0			
	M		✓ W/FT: 5.0			✓ W/FT: 3.0, 6.0		✓ W/FT: 1.5, 2.5	✓ W/FT: 6.0		✓ W/FT: 6.0		✓ W/FT: 4.0
	L				✓ W/FT: 1.5, 3.0, 6.0							✓ W/FT: 6.0	




# SD-L-MICRO


## MICRO 5 L BRACKET - ALUMINUM EXTRUSION

### COMPATIBLE SHIELD


Order separately | See SHIELD cut sheet for more information



Profile - S



Profile - M



Profile - L

### PHOTOMETRIC PERFORMANCE

Tested with SW24/4.0 at 3000K

