



# SW24/3.0

## LED Strips - Static White



- One bin, one step static white LED strip with 300 lm/ft @ 3000K provides an even, consistent color
- 6 diodes per 1" cut point
- CCTs 2200K and greater meet or exceed Title 24 and JA8
- Ambient operating temp: -4-140°F
- Installation temp: 50-100°F | Storage temp: -4-140°F
- Calculated L70 = 70000 hrs

1	2	3	4	5	6	7	8
V/WATTS	RATED	CCT	CONNECTOR/WIRE IN	CONNECTOR/WIRE OUT	WIRE COLOR	WIRE TYPE	ILLUMINATED LENGTH
SW24/3.0							

Sample Part Number: **SW24/3.0-DMP-24-BW-CLS-WH-CL2-48"**

1

V/WATTS

SW24/3.0

Voltage: 24VDC  
Wattage: 3.0W/ft  
See following pages for compatible power supplies.

2

RATED

DRY IP20  
DMP IP54  
WET IP67

3

CCT

18 1800K  
20 2000K  
22 2200K  
24 2400K  
27 2700K  
30 3000K  
35 3500K  
40 4000K

4

CONNECTOR/WIRE IN

BW Bare Wire (Standard 24")  
BRL Barrel  
CLS Closed End (No feed)  
CON6 Connector 6"  
CON24 Connector 24"

Connector/Wire In not needed to specify product. Typical selection is BW.  
BW: Standard length is 24". Max length is 120". Request custom length by writing in part number next to BW (example: BW48)

5

CONNECTOR/WIRE OUT

BW Bare Wire (Standard 24")  
BRL Barrel  
CLS Closed End (No feed)  
CON6 Connector 6"  
CON24 Connector 24"

Connector/Wire Out not needed to specify product. Typical selection is CLS or BW.  
BW: Standard length is 24". Max length is 120". Request custom length by writing in part number next to BW (example: BW48)

6

WIRE COLOR

WH White  
BK Black  
N/A Specify for Barrel

Barrel is white

7

WIRE TYPE

CL2 Class 2  
CL2P Class 2 Plenum Rated  
N/A Specify for Barrel

CL2P only available with bare wire leads (BW)

8

ILLUMINATED LENGTH

DRY: 1"-384" in 1" increment  
DMP: 1"-180" in 1" increment  
WET: 1"-360" in 1" increment

Dry version also available in reel lengths of 32' (Class 2) and 100'. Each reel will have a 2' soldered lead wire attached. Contact factory for larger reels.

Available in reel lengths of 32' (Class 2) and 100'. Each reel will have a 2' soldered lead wire attached. Contact factory for larger reels.

## COMPATIBLE EXTRUSIONS

	WIDE	ROUND	TORQ	TRES	LALO	TALO	ARKA	TELA	VEVE	FLUR	EMBD	LATO	MDIN	OPTI-FLAT	OPTI-OPTICS	THIN
DRY	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
DMP	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓
WET	✓		✓ EXCLUDES 40° LENS	✓	✓	✓	✓	✓	✓ EXCLUDES 45° LENS	✓	✓ EXCLUDES 30°, 45°, 60° LENS	✓	✓	✓		✓ NO LENS

5 year warranty | Warranty only valid with QTL power supplies | Field modifications must comply with QTL's installation methods otherwise warranty is null & void | All data has +/- 5% tolerance | UL Listed | Title 24 - JA8-2016 Strips: DRY, DMP, and WET rated, 2200K and above



# SW24/3.0

LED Strips - Static White

## 3 CCT – LUMENS/CRI - DELIVERED LUMENS

### DRY

[Calculated L70 = 70000 hrs]  
Tested with SW24/3.0-DRY

CCT	Lumen/ft	Luminous Efficacy	CRI Ra	CRI R9	TM30 Rf	TM30 Rg
2000K	255	82 Lm/W	93	60	89	103
2200K	254	81 Lm/W	96	91	93	100
2400K	245	78 Lm/W	94	98	93	103
2700K	287	92 Lm/W	97	95	94	101
3000K	300	96 Lm/W	98	96	93	101
3500K	317	102 Lm/W	98	97	92	100
4000K	300	96 Lm/W	96	89	90	100

### DMP

[Calculated L70 = 70000 hrs]  
Tested with SW24/3.0-DMP

CCT	Lumen/ft	CRI Ra
2000K	**	**
2200K	**	**
2400K	**	**
2700K	**	**
3000K	**	**
3500K	**	**
4000K	**	**

### WET

[Calculated L70 = 70000 hrs]  
Tested with SW24/3.0-WET

CCT	Lumen/ft	CRI Ra
2000K	253	93
2200K	220	96
2400K	227	95
2700K	230	95
3000K	242	95
3500K	262	96
4000K	275	96


## TEMPERATURE RATINGS

		Min	Max
DRY	Ambient Operating Temp - Surface	-4°F	140°F
	Storage Temp	-4°F	140°F
	Installation Temp	50°F	100°F

## 4 / 5 CONNECTOR/WIRE – IN/OUT

Connector/Wire In or Out not needed to specify product. Standard configuration is BW for Wire In and CLS for Wire out


**BW**



.10"

Bare Wire 24"  
Stranded 22 AWG


**BRL**



1.44"  
.42"  
1.74"  
.35"

Barrel 6" - DRY/DMP |  
22 AWG


**BRL**



1.36"  
.44"  
1.62"  
.66"

Barrel 6" - WET | 22 AWG


**CON6/CON24**



1.63"  
.38"  
1.34"  
.39"

6" or 24" Overall  
Wire Connector | 22 AWG  
IP67 Rated, UL Listed

**CLS**




Not soldered

## 6 WIRE COLOR



## 8 ILLUMINATED LENGTH - DIMENSIONS



Width  
A  
B  
LED separation  
C  
Cut length  
D  
Height

Section (in)	A	B	C	D
DRY (IP20)	0.32"	0.16"	1.00"	0.06"
DMP (IP54)	0.32"	0.16"	1.00"	0.12"
WET (IP67)	0.39"	0.16"	1.00"	0.21"



SW24/3.0

LED Strips - Static White

COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

DIM TO LEVEL	INDOOR	OUTDOOR
	SW24/1.5-4.0	SW24/1.5-4.0
Dim to Black	Q6M-DC+CAP QTM-DC+CAP IQ-PH+QD1	QOM-DC+CAP QOM-PH
0.1%	QT-CAB-QZ-PH/0-10V QT-CAB-eLED+0-10V QT-CAB-eLED+0-10V-AWN QT-CAB-eLED+DALI-DT6 QT-CAB-eLED+DALI-DT6-AWN QTM-eLED+0-10V QTM-eLED+0-10V-AWN QTM-eLED+DALI-DT6 QTM-eLED+DALI-DT6-AWN QZ-BOWTIE+DIMMER QZ-DMX QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP	Q-SET-QZ-DMX Q-SET-QZ-PH/0-10V Q-SET-eLED+0-10V QOM-eLED+0-10V QOM-eLED+DALI-DT6 QOM-eLED+PS-DALI-DT6 QZ-DMX QZ-PH/0-10V
1%	QTM-eLED(E) QZ-DALI-DT6	Q-SET+QZ-DALI-DT6 QZ-DALI-DT6
10%	Non-Dim Power Supply with SW App Dongle	Q-HEX-mini-DC Q-SET-mLED

















# SW24/3.0

LED Strips - Static White

DIMMING PROTOCOL	INDOOR	OUTDOOR
	SW24/1.5-4.0	SW24/1.5-4.0
Non-Dim	QT-CAB-eLED-ND QTM-eLED-ND QZ-ND	Q-SET-QZ-ND Q-SET-eLED-ND QOM-eLED-ND QZ-ND
Phase	Q6M-DC+CAP QT-CAB-QZ-PH/0-10V QTM-DC+CAP QTM-eLED(E) QZ-BOWTIE+DIMMER QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP iQ-PH+QD1	Q-HEX-mini-DC Q-SET-QZ-PH/0-10V Q-SET-mLED QOM-DC+CAP QOM-PH QZ-PH/0-10V
0-10V	QT-CAB-QZ-PH/0-10V QT-CAB-eLED+0-10V QT-CAB-eLED+0-10V-AWN QTM-eLED+0-10V QTM-eLED+0-10V-AWN QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP	Q-SET-QZ-PH/0-10V Q-SET-eLED+0-10V QOM-eLED+0-10V QZ-PH/0-10V
Lutron Athena	QT-CAB-eLED+0-10V-AWN QT-CAB-eLED+DALI-DT6-AWN QTM-eLED+0-10V-AWN QTM-eLED+DALI-DT6-AWN	
ECO System	QTM-eLED(E)	
DMX	QZ-DMX	Q-SET-QZ-DMX QZ-DMX
DALI-2: DT6	QT-CAB-eLED+DALI-DT6 QT-CAB-eLED+DALI-DT6-AWN QTM-eLED+DALI-DT6 QTM-eLED+DALI-DT6-AWN QZ-DALI-DT6	Q-SET+QZ-DALI-DT6 QOM-eLED+DALI-DT6 QZ-DALI-DT6
SCENE App Dimmed	Non-Dim Power Supply with SW App Dongle	

## COMPATIBLE MOUNTING ACCESSORIES

<b>QUOVA-MICRO</b>  QUOVA Knife Edge	<b>SHIELD A - Small</b>  For standalone use	<b>SHIELD B - Small</b>  For use within extrusions	<b>BL-GRAZER</b>  Backwards L Mounting Bracket	<b>BL-MICRO</b>  Backwards L Mounting Bracket	<b>BL-LARGE</b>  Backwards L Mounting Bracket	<b>SD-L-LARGE</b>  L Mounting Bracket	<b>SD-L-MEDIUM</b>  L Mounting Bracket	<b>SD-L-MICRO</b>  L Mounting Bracket	<b>SD-J-LARGE</b>  J Mounting Bracket
<b>iQ-STRAP</b>  Plastic strap, Fits all LED strips	<b>iQ-CLIP-SS12</b>  Metal clip, Fits DMP strip	<b>iQ-CLIP-SS10</b>  Metal clip, Fits WET strip	<b>iQ-CLIP-PL</b>  Plastic clip, Fits WET strip						



# SW24/3.0

LED Strips - Static White

## COMPATIBLE WIRING ACCESSORIES

<b>SNP-LEAD</b> <p>Connects lead wire to LED strip DRY ONLY</p>	<b>SNP-INLINE</b> <p>Connects LED strip to LED strip DRY ONLY</p>	<b>CLP-LEAD</b> <p>Connects lead wire to LED strip DRY ONLY</p>	<b>CLP-INLINE</b> <p>Connects LED strip to LED strip DRY ONLY</p>	<b>Q-NECT-01-LEAD-24</b> <p>Connects LED board to 24" lead wire DRY ONLY</p>	<b>Q-NECT-01-JUMP-3</b> <p>Connects two LED boards together with 3" jumper; DRY ONLY</p>	<b>Q-NECT-01-INLINE</b> <p>Connects two LED boards together DRY ONLY</p>	<b>Q-NECT-SCREW-LEAD-12</b> <p>Connects LED board to 12" lead wire DRY ONLY</p>	<b>Q-NECT-SCREW-JUMP-12</b> <p>Connects two LED boards together with 12" jumper; DRY ONLY</p>	<b>BARREL-EXT</b> <p>8ft barrel cable extender DRY ONLY</p>
<b>BARREL FOUR-FER</b> <p>Splits lead from one to four LED Barrel connector fixtures; DRY/DMP</p>	<b>CON120-EXT</b> <p>10ft Con cable extender DRY/DMP/WET</p>	<b>CON FOUR-FER</b> <p>Splits lead from one to four LED Con connectors DRY/DMP/WET</p>	<b>CON M - BARREL F</b> <p>Male con to barrel cable adaptor DRY/DMP</p>	<b>Q-mini-J</b> <p>UL Listed, miniature junction box; DRY/DMP (WET rated with silicone)</p>	<b>Q-mini-J5</b> <p>UL Listed, miniature junction box; DRY/DMP (WET rated with silicone)</p>	<b>INSTALLATION KITS</b> <p>LEAD or JUMP DRY and WET LED strip wiring kits</p>			

## COMPATIBLE CONTROL ACCESSORIES

**SCENE APP DONGLE**

1.36"  
2.58"

Wi-Fi or Bluetooth Connectivity

## COMPATIBLE APPS

**NFC APP**

Read and write DMX addresses and adjust voltage