

# VERS-CLEAR-SK (03) STATIC WHITE

24VDC Linear Fixtures - Suspended

WHITE OPTICS | c UL us LISTED | NEC 410.2 & 410.16 Closet Rated up to 4.0W/ft | RoHS COMPLIANT | EPD ENVIRONMENTAL PRODUCT DECLARATION | JA8 2016 | 1-BIN 1-STEP | 5 YEAR WARRANTY | BAA BUY AMERICAN ACT COMPLIANT | BABA BUILD AMERICA, BUY AMERICA COMPLIANT






- 80 Suspension Kit configurations allow fixture to be seamlessly incorporated into any interior
- Create long, continuous lines of light with easy-to-use inline bracket and double feed joiner connectors
- The high quality clear lens allows for maximum variations of LED sources and the most delivered lumens of the VERS Family
- Features integrated metal endcaps and durable anodized aluminum housings
- With standard internal White Optics coating, fixtures achieve greater lumen efficacies
- Suitable for installation in the storage area of a clothes closet when specified with LEDs at 4.0 watts or less per foot per NEC regulations
- Consult factory for field assembly options
- Optional external louver accessory available in white or black for added glare control

**INFORMATION REQUIRED FOR LIGHTING SCHEDULE**

| 1 PRODUCT | 2 WATTS/ FT | 3 CCT | 4 RATED | 5 LENS | 6 EXTERNAL LOUVER |
|---|---|---|---|---|---|
| | | | | CL | |

**ADDITIONAL INFORMATION REQUIRED TO ORDER**

| 7 WIRE INPUT/ OUTPUT | 8 CONNECTOR/ WIRE IN | 9 CONNECTOR/ WIRE OUT | 10 WIRE COLOR | 11 WIRE TYPE | 12 MOUNTING | 13 FINISH | 14 LENGTH (IN) | 15 EXACT/ OPTIMAL |
|---|---|---|---|---|---|---|---|---|
| | BW | CLS | SV | AWM | SK | | | |

Sample Part Number: **VERS-03-SW-5.0-30-DRY-CL-L1-BK-P1-CON6-CON6-BK-CL2-MG-BK-48"-E**

## 1 PRODUCT

**VERS-03-SK-SW**
**VERS-03-SK-SW-USA**

Select USA option for BAA and BABA projects. Only DRY ratings apply.

See following pages for compatible power supplies.

## 2 WATTS/FT

| | |
|---|---|
| **1.5** | 1.5W/ft |
| **3.0** | 3.0W/ft |
| **4.0** | 4.0W/ft |
| **5.0** | 5.0W/ft |
| **1.5HE** | 1.5W/ft HE |
| **3.0HE** | 3.0W/ft HE |
| **6.0HE** | 6.0W/ft HE |
| **9.0HE** | 9.0W/ft HE |

| | |
|---|---|
| **1.5** | 1.5W/ft |
| **3.0** | 3.0W/ft |
| **4.0** | 4.0W/ft |
| **5.0** | 5.0W/ft |
| **1.5HE** | 1.5W/ft HE |
| **3.0HE** | 3.0W/ft HE |
| **6.0HE** | 6.0W/ft HE |

## 3 CCT

| | |
|---|---|
| **18** | 1800K |
| **20** | 2000K |
| **22** | 2200K |
| **24** | 2400K |
| **27** | 2700K |
| **30** | 3000K |
| **35** | 3500K |
| **40** | 4000K |

| | |
|---|---|
| **18** | 1800K |
| **20** | 2000K |
| **22** | 2200K |
| **24** | 2400K |
| **27** | 2700K |
| **30** | 3000K |
| **35** | 3500K |
| **40** | 4000K |

## 4 RATED

| | |
|---|---|
| **DRY** | IP20 |

| | |
|---|---|
| **DMP** | IP54 |

## 5 LENS

| | |
|---|---|
| **CL** | Clear |

For representation of LED visibility, see Diode Visibility section on following pages.
For beam angles, see Photometric Performance section on following pages.

## 6 EXTERNAL LOUVER

| | |
|---|---|
| **L1-WH** | White Plastic |
| **L1-BK** | Black Plastic |
| **L2-ST** | Satin Anodized Aluminum |
| **L2-BK** | Black Anodized Aluminum |
| **L2-WH** | White Powder Coated Aluminum |
| **N/A** | No Louver |

L1 Plastic Louvers come in 12" lengths, multiple pieces will be used to match fixture length. L2 Aluminum louvers come in maximum 98" lengths and will be cut to match fixture length. White and custom painted finishes are not compatible with L2 external louvers.

## 7 WIRE INPUT/OUTPUT

**SINGLE (Input Only)**
**S2** Bottom Feed

## 8 CONNECTOR/WIRE IN

**BW** Bare Wire (Standard 36")

BW: Standard length is 36", max length is 120". Request custom length by writing in part number next to BW (example: BW48)

## 9 CONNECTOR/WIRE OUT

**CLS** Closed End (No feed)

BW: Standard length is 36", Max length is 120". Request custom length by writing in part number next to BW (example: BW48)

## 10 WIRE COLOR

**SV** Silver

## 11 WIRE TYPE

**AWM** Appliance Wiring Material

## 12 MOUNTING

**SK** Suspension Bracket

## 13 FINISH

| | |
|---|---|
| **ST** | Satin |
| **BK** | Black |
| **BZ** | Bronze |
| **WH** | White |
| **CU** | Custom |

White and custom finishes are incompatible with external louvers; custom finishes have longer lead times. Non-RAL 9003 whites custom.

## 14 LENGTH (IN)

Minimum length is 12", maximum length is 98" not including end caps. Contact us for lengths under 12".

## 15 EXACT/OPTIMAL

| | |
|---|---|
| **O** | Optimal Illumination |
| **E** | Exact Specified Length |

Exact fixtures are the exact length specified +0 -1/8". Optimal fixtures' length is rounded down with illumination end to end. See Exact/Optimal Fixture Length charts.

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTLlighting | www.QTL.lighting


Specification subject to change. Rev-10-05-26

5 year warranty | Warranty only valid with QTL power supplies | Field modifications void warranty | Data subject to change, all data has +/- 5% tolerance | Suitable for installation in the storage area of a clothes closet when using wattage of 4.0W/ft or less


# VERS-CLEAR-SK (03) STATIC WHITE

24VDC Linear Fixtures - Suspended

## 1 PRODUCT - DIMENSIONS




Profile with lens





Profile with L1 Louver

## 2 DELIVERED LUMENS

[Calculated L70 = 70000 hrs, L70 = 66000 hrs for HE]
Tested with VERS-03-SK-SW-**-30-DRY

| | 1.5 W/FT | | 1.5HE W/FT | | 3.0 W/FT | | 3.0HE W/FT | | 4.0 W/FT | | 5.0 W/FT | | 6.0HE W/FT | | 9.0HE W/FT | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | LM/FT | CRI | LM/FT | CRI | LM/FT | CRI | LM/FT | CRI | LM/FT | CRI | LM/FT | CRI | LM/FT | CRI | LM/FT | CRI |
| CL | 158 | 98 | 200 | 98 | 276 | 98 | 381 | 98 | 356 | 98 | 427 | 98 | 692 | 98 | 1024 | 98 |


## 6 DIODE VISIBILITY




## PHOTOMETRIC PERFORMANCE

Nominal beam spread shown, beam spread varies based on light engine. For more detailed information, see photometric data.

**5W/ft** Clear lens




© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

# VERS-CLEAR-SK (03) STATIC WHITE


24VDC Linear Fixtures - Suspended

## TEMPERATURE RATINGS


| | | 1.5 W/FT | | 1.5 HE W/FT | | 3.0 W/FT | | 3.0 HE W/FT | | 4.0 W/FT | | 5.0 W/FT | | 6.0 HE W/FT | | 9.0 HE W/FT | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Min | Max | Min | Max | Min | Max | Min | Max | Min | Max | Min | Max | Min | Max | Min | Max |
| DRY | Ambient Operating Temp - Surface | -4°F | 140°F | -4°F | 145°F | -4°F | 130°F | -4°F | 135°F | -4°F | 125°F | -4°F | 120°F | -4°F | 120°F | -4°F | 100°F |
| DMP | Ambient Operating Temp - Surface | -4°F | 140°F | -4°F | 145°F | -4°F | 130°F | -4°F | 135°F | -4°F | 125°F | -4°F | 120°F | -4°F | 120°F | — | — |

## 6 EXTERNAL LOUVER

**PLASTIC**




**L1-XX**




Lumen Multiplier

| WH | BK |
|---|---|
| 0.70 | 0.54 |

## 7 WIRE INPUT/ OUTPUT


SINGLE (Input only)





## CONFIGURATION OPTIONS




Single Feed




Continuous Row End Feeds




Continuous Row Center Feeds

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting


# VERS-CLEAR-SK (03) STATIC WHITE

24VDC Linear Fixtures - Suspended

## 8/9 CONNECTOR/WIRE – IN/OUT

Connector/Wire In or Out not needed to specify product.

**BW**





Bare Wire 36" | 22 AWG
Clear outer jacket, metal shield

## 10 WIRE COLOR

Silver

## 12 MOUNTING

**SK**




Suspension Bracket

2 required up to 6' lengths; additional support required between 6' to 8'

## 13 FINISH


Satin
Black
Bronze
White

White and custom finishes are incompatible with external louvers; custom finishes have longer lead times. Non-RAL 9003 whites custom.

## 15 EXACT/OPTIMAL FIXTURE LENGTH

E/O Length Calculator →  E/O Explained →

Exact fixtures are the exact length specified +0 -1/8". Optimal fixtures' length is rounded down based on LED cut points to allow the fixture to be illuminated end to end. For runs with multiple fixtures that need to fill a specific length, it's recommended to order all optimal fixtures with an exact fixture at the end of the run.




© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting


Specification subject to change. Rev-10-05-26

# VERS-CLEAR-SK (03) STATIC WHITE


24VDC Linear Fixtures - Suspended

## SW DRY DMP LENGTHS BY INCH

**EXACT LENGTH**


| Requested Length | Potential dim spot on either end of a S1 fixture   End Feed |
|---|---|
| 12" | 0.5" |
| 13" | 0.5" |
| 14" | 0.5" |
| 15" | 0.5" |
| 16" | 0.5" |
| 17" | 0.5" |
| 18" | 0.5" |
| 19" | 0.5" |
| 20" | 0.5" |
| 21" | 0.5" |
| 22" | 0.5" |
| 23" | 0.5" |
| 24" | 0.5" |
| 36" | 0.5" |
| 48" | 0.5" |
| 60" | 0.5" |
| 72" | 0.5" |
| 84" | 0.5" |
| 96" | 0.5" |

**OPTIMAL LENGTH**


| Requested Nominal Length | S2   Bottom Feed |
|---|---|
| 12" | 11.49" |
| 13" | 12.49" |
| 14" | 13.49" |
| 15" | 14.49" |
| 16" | 15.49" |
| 17" | 16.49" |
| 18" | 17.49" |
| 19" | 18.49" |
| 20" | 19.49" |
| 21" | 20.49" |
| 22" | 21.49" |
| 23" | 22.49" |
| 24" | 23.49" |
| 36" | 35.49" |
| 48" | 47.49" |
| 60" | 59.49" |
| 72" | 71.49" |
| 84" | 83.49" |
| 96" | 95.49" |

## SW-HE DRY DMP LENGTHS BY INCH

**EXACT LENGTH**

| Requested Length | Potential dim spot on either end of a S1 fixture   End Feed |
|---|---|
| 12" | 1" |
| 13" | 0.5" |
| 14" | 1" |
| 15" | 0.5" |
| 16" | 1" |
| 17" | 0.5" |
| 18" | 1" |
| 19" | 0.5" |
| 20" | 1" |
| 21" | 0.5" |
| 22" | 1" |
| 23" | 0.5" |
| 24" | 1" |
| 36" | 1" |
| 48" | 1" |
| 60" | 1" |
| 72" | 1" |
| 84" | 1" |
| 96" | 1" |

**OPTIMAL LENGTH**

| Requested Nominal Length | S2   Bottom Feed |
|---|---|
| 12" | 10.49" |
| 13" | 12.49" |
| 14" | 12.49" |
| 15" | 14.49" |
| 16" | 14.49" |
| 17" | 16.49" |
| 18" | 16.49" |
| 19" | 18.49" |
| 20" | 18.49" |
| 21" | 20.49" |
| 22" | 20.49" |
| 23" | 22.49" |
| 24" | 22.49" |
| 36" | 34.49" |
| 48" | 46.49" |
| 60" | 58.49" |
| 72" | 70.49" |
| 84" | 82.49" |
| 96" | 94.49" |

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

# VERS-CLEAR-SK (03) STATIC WHITE

24VDC Linear Fixtures - Suspended

## COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

| DIM TO LEVEL | INDOOR | |
|---|---|---|
| | SW24/1.5-4.0 | SW24/5.0, SW-HE, SW-HE+ |
| Dim to Black | Q6M-DC+CAP<br>QTM-DC+CAP<br>iQ-PH+QD1 | Q6M-DC+CAP<br>QTM-DC+CAP<br>iQ-PH+QD1 |
| 0.1% | QT-CAB-QZ-PH/0-10V<br>QT-CAB-eLED+0-10V<br>QT-CAB-eLED+0-10V-AWN<br>QT-CAB-eLED+DALI-DT6<br>QT-CAB-eLED+DALI-DT6-AWN<br>QTM-eLED+0-10V<br>QTM-eLED+0-10V-AWN<br>QTM-eLED+DALI-DT6<br>QTM-eLED+DALI-DT6-AWN<br>QZ-BOWTIE+DIMMER<br>QZ-DMX<br>QZ-PRO-PH/0-10V<br>QZ-STICK-PH/0-10V<br>QZLP | QT-CAB-QZ-PH/0-10V<br>QT-CAB-eLED+0-10V<br>QT-CAB-eLED+0-10V-AWN<br>QT-CAB-eLED+DALI-DT6<br>QT-CAB-eLED+DALI-DT6-AWN<br>QTM-eLED+0-10V<br>QTM-eLED+0-10V-AWN<br>QTM-eLED+DALI-DT6<br>QTM-eLED+DALI-DT6-AWN<br>QZ-BOWTIE+DIMMER<br>QZ-DMX<br>QZ-PRO-PH/0-10V<br>QZ-STICK-PH/0-10V<br>QZLP |
| 1% | Q-DIM<br>QTM-eLED(E)<br>QZ-DALI-DT6 | Q-DIM<br>QTM-eLED(E)<br>QZ-DALI-DT6 |
| 10% | Non-Dim Power Supply with SW App Dongle | Non-Dim Power Supply with SW App Dongle |

| DIMMING PROTOCOL | INDOOR | |
|---|---|---|
| | SW24/1.5-4.0 | SW24/5.0, SW-HE, SW-HE+ |
| Non-Dim | QT-CAB-eLED-ND<br>QTM-eLED-ND<br>QZ-ND | QT-CAB-eLED-ND<br>QTM-eLED-ND<br>QZ-ND |
| Phase | Q6M-DC+CAP<br>QT-CAB-QZ-PH/0-10V<br>QTM-DC+CAP<br>QTM-eLED(E)<br>QZ-BOWTIE+DIMMER<br>QZ-PRO-PH/0-10V<br>QZ-STICK-PH/0-10V<br>QZLP<br>iQ-PH+QD1 | Q6M-DC+CAP<br>QT-CAB-QZ-PH/0-10V<br>QTM-DC+CAP<br>QTM-eLED(E)<br>QZ-BOWTIE+DIMMER<br>QZ-PRO-PH/0-10V<br>QZ-STICK-PH/0-10V<br>QZLP<br>iQ-PH+QD1 |
| 0-10V | QT-CAB-QZ-PH/0-10V<br>QT-CAB-eLED+0-10V<br>QT-CAB-eLED+0-10V-AWN<br>QTM-eLED+0-10V<br>QTM-eLED+0-10V-AWN<br>QZ-PRO-PH/0-10V<br>QZ-STICK-PH/0-10V<br>QZLP | QT-CAB-QZ-PH/0-10V<br>QT-CAB-eLED+0-10V<br>QT-CAB-eLED+0-10V-AWN<br>QTM-eLED+0-10V<br>QTM-eLED+0-10V-AWN<br>QZ-PRO-PH/0-10V<br>QZ-STICK-PH/0-10V<br>QZLP |
| Lutron Athena | QT-CAB-eLED+0-10V-AWN<br>QT-CAB-eLED+DALI-DT6-AWN<br>QTM-eLED+0-10V-AWN<br>QTM-eLED+DALI-DT6-AWN | QT-CAB-eLED+0-10V-AWN<br>QT-CAB-eLED+DALI-DT6-AWN<br>QTM-eLED+0-10V-AWN<br>QTM-eLED+DALI-DT6-AWN |
| ECO System | QTM-eLED(E) | QTM-eLED(E) |
| DMX | QZ-DMX | QZ-DMX |
| DALI-2: DT6 | QT-CAB-eLED+DALI-DT6<br>QT-CAB-eLED+DALI-DT6-AWN<br>QTM-eLED+DALI-DT6<br>QTM-eLED+DALI-DT6-AWN<br>QZ-DALI-DT6 | QT-CAB-eLED+DALI-DT6<br>QT-CAB-eLED+DALI-DT6-AWN<br>QTM-eLED+DALI-DT6<br>QTM-eLED+DALI-DT6-AWN<br>QZ-DALI-DT6 |
| SCENE App Dimmed | Non-Dim Power Supply with SW App Dongle | Non-Dim Power Supply with SW App Dongle |

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

# VERS-CLEAR-SK (03) STATIC WHITE

24VDC Linear Fixtures - Suspended


## COMPATIBLE WIRING ACCESSORIES

**Q-mini-J**




UL Listed, miniature junction box, DRY/DMP (WET rated with silicone)

**Q-mini-J5**




UL Listed, miniature junction box, DRY/DMP (WET rated with silicone)

## COMPATIBLE APPS

**NFC APP**




Read and write DMX addresses and adjust voltage

# VERS-SK

Linear Fixtures - Suspended



- Shop drawings required for run lengths over 8ft
- If no suspension length provided, 36" is standard
- Suspension cable maximum length: 120"
- Suspension cable is field cuttable
- Suspended fixtures over 6ft require additional suspension points. 8ft lengths will bow 0.25" in middle without additional support.
- Any run length over 8' requires inline brackets
- Consult factory for power over aircraft
- Consult factory for custom color of canopy
- Lag Screw is for mounting into drywall, wood, or other types of finished ceilings for non-feed mounting only

## POWER FEED SUSPENSION KIT

| 1 PRODUCT | 2 FEED | 3 CANOPY SHAPE | 4 CANOPY SIZE | 5 CANOPY FINISH | 6 APPLICATION | 7 SUSPENSION CABLE LENGTH (IN) |
|---|---|---|---|---|---|---|
| SK | | | 5" | | | |

Sample Part Number: **SK-SF-RD-5"-WH-JB-36"**

**1 PRODUCT**

| | |
|---|---|
| **SK** | |

**2 FEED**

| | |
|---|---|
| **SF** | Single |
| **DF** | Double |

**3 CANOPY SHAPE**

| | |
|---|---|
| **RD** | Round |
| **SQ** | Square |

**4 CANOPY SIZE**

| |
|---|
| **5"** |

**5 CANOPY FINISH**

| | |
|---|---|
| **WH** | White |
| **BK** | Black |

**6 APPLICATION**

| | |
|---|---|
| **JB** | Junction Box |
| **TB** | T-Bar Mount |

JB - mounting bracket only, junction box not included
TB - mounting bracket and junction box

**7 SUSPENSION CABLE LENGTH (IN)**

| |
|---|
| **36"** |
| **120"** |

## NON-FEED SUSPENSION KIT

| 1 PRODUCT | 2 FEED | 3 CANOPY SHAPE | 4 CANOPY SIZE | 5 CANOPY FINISH | 6 APPLICATION | 7 SUSPENSION CABLE LENGTH (IN) |
|---|---|---|---|---|---|---|
| SK | NF | | | | | |

Sample Part Number: **SK-SF-RD-5"-WH-JB-36"**

**1 PRODUCT**

| | |
|---|---|
| **SK** | |

**2 FEED**

| | |
|---|---|
| **NF** | No Feed |

**3 CANOPY SHAPE**

| | |
|---|---|
| **RD** | Round |
| **SQ** | Square |

**4 CANOPY SIZE**

| |
|---|
| **2"** |
| **5"** |
| **5"** |

**5 CANOPY FINISH**

| | |
|---|---|
| **WH** | White |
| **BK** | Black |
| **WH** | White |
| **BK** | Black |

**6 APPLICATION**

| | |
|---|---|
| **TB** | T-Bar Mount |
| **LS** | Lag Screw |

TB - T-Bar clip only, junction box not included

| | |
|---|---|
| **JB** | Junction Box |

Mounting bracket only, junction box not included

**7 SUSPENSION CABLE LENGTH (IN)**

| |
|---|
| **36"** |
| **120"** |

## KIT CONTENTS

- 1/16" Steel suspension cable – 36" standard
- Selected canopy
- Cable Gripper
- Cable Coupler

**JBOX**
- Bracket to mount to junction box (junction box not included)
- Wire strain relief
- Ties for securing electrical cable to suspension cable

**T-BAR – feed**
- Includes junction box specifically designed for T-BAR applications
- Bracket to mount to junction box
- Wire strain relief
- Ties for securing electrical wire to suspension cable

**T-BAR – non-feed**
- Bracket to mount to T-BAR (no junction box)

**LAG SCREW – non-feed only**
- Double ended screw, with a wood thread side and machine thread side
- One piece cable coupler


© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

# VERS-SK

Linear Fixtures - Suspended


## 3 CANOPY OPTIONS

**RD - 2" - NF**





Round
2"
No Feed

**SQ - 2" - NF**





Square
2"
No Feed

**RD - 5" - NF**





Round
5"
No Feed

**SQ - 5 - NF**





Square
5"
No Feed

**RD - 5" - SF**





Round
5"
Single Feed

**SQ - 5" - SF**





Square
5"
Single Feed

**RD - 5" - DF**





Round
5"
Double Feed

**SQ - 5" - DF**




Square
5"
Double Feed


## 5 CANOPY FINISH




White

Black

## JOINTS/CONNECTORS





Inline Bracket




Double Feed Joiner


## 6 APPLICATION

**TB**
Power Feed Kit




T-Bar Junction Box

**TB**
Non-Feed Kit




T-Bar Clip

**LS**



Lag Screw

## KIT HARDWARE



Cable Gripper



Cable Coupler


© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting

# VERS-SK


Linear Fixtures - Suspended

## MOUNTING


- Maximum single fixture length: 98”
- Suspended fixtures over 6ft require additional suspension points. 8ft lengths will bow 0.25” in middle without additional support.
- Shop drawings required for run lengths over 8ft
- Any double fed fixture will come with double feed joiner and inline bracket




**Power Feed Suspension**




**Non-Feed Suspension**





© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting


# VERS-SK

Linear Fixtures - Suspended

## MOUNTING

- Maximum single fixture length: 98"
- Suspended fixtures over 6ft require additional suspension points. 8ft lengths will bow 0.25" in middle without additional support.
- Shop drawings required for run lengths over 8ft
- Any double fed fixture will come with double feed joiner and inline bracket










**Part number example for a suspended VERS-01 dry rated static white fixture with a diffused lens in 1.5W/ft, 3000K, in a satin finish:**

**A** VERS-01-SK-SW-1.5-30-DRY-DF-N/A-S2-BW-CLS-SV-AWM-SK-ST-144" (1X)
SK-SF-RD-5"-WH-JB-36" (2X)
SK-NF-RD-5"-WH-JB-36" (1X)

**B** VERS-01-SK-SW-1.5-30-DRY-DF-N/A-S2-BW-CLS-SV-AWM-SK-ST-144" (1X)
SK-DF-RD-5"-WH-JB-36" (1X)
SK-NF-RD-5"-WH-JB-36" (2X)





© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting


# VERS-SK

Linear Fixtures - Suspended


## SUSPENSION T-BAR POWER FEED ASSEMBLY

SK-SF-RD-5-**-TB-36



15 T-Bar mounted Junction Box




### VERS SUSPENSION COMPONENTS

| | | | | | | |
|---|---|---|---|---|---|---|
| 1 VERS | 2 Suspension Bracket | 3 8-32 Screw | 4 Endcap | 5 Cable Gripper | 6 1/16” Cable | 7 Tie |
| 8 Lead Wire | 9 Cable Coupler | 10 Strain Relief | 11 Canopy | 12 Crossbar | 13 1/4”-20 | 14 Ground Screw |

© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting


# VERS-SK

Linear Fixtures - Suspended

## SUSPENSION POWER FEED ASSEMBLY - TO MOUNT TO JUNCTION BOX*

*JUNCTION BOX NOT INCLUDED

SK-SF-RD-5-**-JB-36




### VERS SUSPENSION COMPONENTS

| | | | | | | |
|---|---|---|---|---|---|---|
| 1 VERS | 2 Suspension Bracket | 3 8-32 Screw | 4 Endcap | 5 Cable Gripper | 6 1/16” Cable | 7 Tie |
| 8 Lead Wire | 9 Cable Coupler | 10 Strain Relief | 11 Canopy | 12 Crossbar | 13 1/4”-20 | 14 Ground Screw |


© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting


# VERS-SK

Linear Fixtures - Suspended

## SUSPENSION T-BAR NON-FEED ASSEMBLY

SK-NF-RD-2-NF-*-TB-36




NON-POWERED FEED KIT

| | | | | |
|---|---|---|---|---|
| 1 VERS | 2 Suspension Bracket | 3 8-32 Screw | 4 Endcap | 5 Cable Gripper |
| 6 1/16” Cable | 7 Cable Coupler | 8 Canopy | 9 T-Bar Clip | |


© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting


# VERS-SK

Linear Fixtures - Suspended

## LAG SCREW NON-FEED ASSEMBLY

SK-NF-RD-2-NF-*-LS-36




NON-POWERED FEED KIT

| | | | | |
|---|---|---|---|---|
| 1 VERS | 2 Suspension Bracket | 3 8-32 Screw | 4 Endcap | 5 Cable Gripper |
| 6 1/16” Cable | 7 Cable Coupler | 8 Canopy | 9 Lag Screw | |

© 2024 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | QTL.lighting