





MICRO 5 POP MUD-IN-FLAT (01) FOR WARM DIM APPLICATIONS

24VDC Linear Fixtures - Recessed



- MICRO 5 Series linear LED fixture designed to provide superior light performance and uniformity with discreet integration into drywall
- Two-piece mud-in fixture
- Asymmetric fixture with an 80° focused beam 20° off-nadir
- Once installed, its wings are covered with tape and compound to create a seamless look
- Used in applications to provide warmer CCTs as the light is dimmed
- When using DALI and DMX power supplies, LED wattage must be doubled

ORDERING PROCESS

A Specify LED Fixture

B Specify MUD-IN Housing

A. LED FIXTURE

INFORMATION REQUIRED FOR LIGHTING SCHEDULE

| A1 | A2 | A3 | A4 | A5 |
|---------|-----------|-----|-------|------|
| PRODUCT | WATTS/ FT | CCT | RATED | LENS |
| | 2.0 | | DRY | |

ADDITIONAL INFORMATION REQUIRED TO ORDER

| A6 | A7 | A8 | A9 | A10 | A11 | A12 | A13 | A14 |
|--------------------|--------------------|---------------------|------------|-----------|----------|--------|-------------|----------------|
| WIRE INPUT/ OUTPUT | CONNECTOR/ WIRE IN | CONNECTOR/ WIRE OUT | WIRE COLOR | WIRE TYPE | MOUNTING | FINISH | LENGTH (IN) | EXACT/ OPTIMAL |
| | | | | | | | | |

Sample Part Number: **POP-MD-01-DW-2.0-2.0/30-DRY-DF-S1A-BW-CLS-WH-CL2-SP-ST-48"-E**

| A1 | A2 | A3 | A4 | A5 |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|--------------------------------------------------------------------------------------------------------------|-----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PRODUCT | WATTS/FT | CCT | RATED | LENS |
| POP-MD-01-DW POP-MD-01-DW-USA Select USA option for BAA and BABA projects. LED engine is built with 3 wires requiring 0-10V, DMX or DALI control. Using DALI, DMX, or non QTL power supplies may double watts/ft. See following pages for compatible power supplies. | 2.0 2.0W/ft | 20/27 2000K/2700K 20/30 2000K/3000K 27/40 2700K/4000K 27/55 2700K/5500K | DRY IP20 | DF Diffused PR Polar For representation of LED visibility, see Diode Visibility section on following pages. For beam angles, see Photometric Performance section on following pages. |

| A6 | A7 | A8 |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WIRE INPUT/OUTPUT | CONNECTOR/WIRE IN | CONNECTOR/WIRE OUT |
| SINGLE (Input Only) S1A End Feed S1B End Feed S2A Bottom Feed S2B Bottom Feed For continuous mounting, consider bottom feed. | BW Bare Wire (Standard 24") BW: Standard length is 24"; Max length is 120". Request custom length by writing in part number next to BW (example: BW48) | CLS Closed End (No feed) |
| PASS THROUGH (Input/output) P1A End Feed P1B End Feed P2A Bottom Feed P2B Bottom Feed For continuous mounting, consider bottom feed. | BW Bare Wire (Standard 24") BW: Standard length is 24"; Max length is 120". Request custom length by writing in part number next to BW (example: BW48) | BW Bare Wire (Standard 24") BW: Standard length is 24"; Max length is 120". Request custom length by writing in part number next to BW (example: BW48) |

| A9 | A10 | A11 | A12 | A13 | A14 |
|------------------------------------|-----------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WIRE COLOR | WIRE TYPE | MOUNTING | FINISH | LENGTH (IN) | EXACT/OPTIMAL |
| WH White BK Black | CL2 Class 2 CL2P Plenum Rated CL2P only available with bare wire leads (BW) | SC Screw SP Spring Clip For either mounting option POP-MD-MNT-KIT is required for mounting POP into the Mud-In Channel | ST Satin BK Black BZ Bronze WH White CU Custom Custom finishes have longer lead times. Non-RAL 9003 whites custom. | Minimum length is 12", maximum length is 98.43" not including end caps. Contact us for lengths under 12". | E Exact specified length O Optimal illumination Exact fixtures match the exact length you specify, but they may have dim spots at the ends. Optimal fixtures are slightly shorter than the length specified, but provide full illumination from end to end. |

5 year warranty | Warranty only valid with QTL power supplies | Field modifications void warranty | Data subject to change, all data has +/- 5% tolerance



MICRO 5 POP MUD-IN-FLAT (01) FOR WARM DIM APPLICATIONS

24VDC Linear Fixtures - Recessed

B. MUD-IN HOUSING

| | |
|----------------------------------|---------------------------------|
| <div>B1</div> <div>PRODUCT</div> | <div>B2</div> <div>LENGTH</div> |
| POP-MD | |

Sample Part Number: POP-MD-FCN


| | |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <div>B1</div> <div>PRODUCT</div> | <div>B2</div> <div>LENGTH</div> |
| POP-MD | <div>FCN</div> Field Cuttable <div>CTL</div> Cut to Length <div>Full length 98.43" housings will be sent for field cuttable specifications. Quantity will be determined by dividing the POP fixture measurements by 98.43 and rounding up. Cut to length housing specifications will be the length of the POP fixture specified, plus .125" for endcaps.</div> |




MICRO 5 POP MUD-IN-FLAT (01) FOR WARM DIM APPLICATIONS

24VDC Linear Fixtures - Recessed


A1 PRODUCT - DIMENSIONS




Profile



Profile with mud-in accessory




Profile with mud-in accessory and spring clip



Profile with mud-in accessory and screw mount


END CAPS

Flat end caps



Feed

To order separately, use
POP-EC-MDIN-A-ST



Feed

To order separately, use
POP-EC-MDIN-B-ST

A2 DELIVERED LUMENS

[Calculated L70 = 70000 hrs]
Tested with POP-01-DW-2.0-**-DRY

| | 2000K | | 2700K | | 3000K | | 4000K | | 5500K | |
|----|-------|-----|-------|-----|-------|-----|-------|-----|-------|-----|
| | LM/FT | CRI | LM/FT | CRI | LM/FT | CRI | LM/FT | CRI | LM/FT | CRI |
| PR | 77 | 93 | 89 | 98 | 93 | 98 | 95 | 97 | 100 | 97 |
| DF | 69 | 93 | 81 | 98 | 83 | 98 | 86 | 97 | 93 | 97 |

A5 DIODE VISIBILITY




DF - Diffused lens

PR - Polar lens

PHOTOMETRIC PERFORMANCE

Nominal beam spread shown, beam spread varies based on light engine. For more detailed information, see photometric data.



DF lens at 3000K



MICRO 5 POP MUD-IN-FLAT (01) FOR WARM DIM APPLICATIONS


24VDC Linear Fixtures - Recessed

TEMPERATURE RATINGS


| | | DW 2.0 W/FT | | DW 4.0 W/FT | |
|-----|-----------------------------------|---------------------------------------|-------|-----------------------------------|-------|
| | | QTL power supply other than DALI, DMX | | DALI, DMX or non-QTL power supply | |
| | | Min | Max | Min | Max |
| DRY | Ambient Operating Temp - Recessed | -4°F | 130°F | -4°F | 110°F |

A6 WIRE INPUT/OUTPUT


ASYMMETRIC ONLY SINGLE (Input only)



ASYMMETRIC ONLY PASS THROUGH (Input/Output)



CONFIGURATION OPTIONS






MICRO 5 POP MUD-IN-FLAT (01) FOR WARM DIM APPLICATIONS

24VDC Linear Fixtures - Recessed

A7 / A8 CONNECTOR/WIRE – IN/OUT

Connector/Wire In or Out not needed to specify product. Typical selection is S1 for Wire Input/Output, BW for Connector/Wire In, N/A for Connector/Wire Out

BW




Bare Wire 24"
22 AWG

A9 WIRE COLOR



A11 MOUNTING

POP-MD-MNT-KIT




Plastic Clip Kit

2 clips provided for 4' or less;
4 clips provided for greater
than 4'

To order separately use POP-
MD-MNT-KIT

Each clip comes with a #4 x
3/16 Flat Head SS" and two
#6 x 1/8" long set screws

SP



Spring Clip

Only to be used with mud-in
accessory

4 clips provided for each full
length of MUD-IN

To order separately use
SP-02


832



832 Silicone

Sold separately


SC



Screw

6 #6x1.75" flat head screws
are provided for each full
length of MUD-IN

A12 FINISH



Custom finishes require a longer lead time, consult factory




MICRO 5 POP MUD-IN-FLAT (01) FOR WARM DIM APPLICATIONS

24VDC Linear Fixtures - Recessed

15 EXACT/OPTIMAL FIXTURE LENGTH

Exact fixtures are the exact length specified. Optimal fixtures' length is rounded down based on LED cut points to allow the fixture to be illuminated end to end. For runs with multiple fixtures that need to fill a specific length, it's recommended to order all optimal fixtures with an exact fixture at the end of the run.



DW DRY LENGTHS BY INCH

EXACT LENGTH


| Requested Length | Potential dim spot on either end of a S1 fixture |
|------------------|--------------------------------------------------|
| | S1 |
| 12" | 1" |
| 13" | 0.5" |
| 14" | 1" |
| 15" | 0.5" |
| 16" | 1" |
| 17" | 0.5" |
| 18" | 1" |
| 19" | 0.5" |
| 20" | 1" |
| 21" | 0.5" |
| 22" | 1" |
| 23" | 0.5" |
| 24" | 1" |
| 36" | 1" |
| 48" | 1" |
| 60" | 1" |
| 72" | 1" |
| 84" | 1" |
| 96" | 1" |

OPTIMAL LENGTH

| Requested Nominal Length | S1A/B & S2A/B | | P1A/B & P2A/B | |
|--------------------------|---------------|--------|---------------|--------|
| | S1 | S2 | P1 | P2 |
| 12" | 10.50" | 10.75" | 10.75" | 10.75" |
| 13" | 12.50" | 12.75" | 12.75" | 12.75" |
| 14" | 12.50" | 12.75" | 12.75" | 12.75" |
| 15" | 14.50" | 14.75" | 14.75" | 14.75" |
| 16" | 14.50" | 14.75" | 14.75" | 14.75" |
| 17" | 16.50" | 16.75" | 16.75" | 16.75" |
| 18" | 16.50" | 16.75" | 16.75" | 16.75" |
| 19" | 18.50" | 18.75" | 18.75" | 18.75" |
| 20" | 18.50" | 18.75" | 18.75" | 18.75" |
| 21" | 20.50" | 20.75" | 20.75" | 20.75" |
| 22" | 20.50" | 20.75" | 20.75" | 20.75" |
| 23" | 22.50" | 22.75" | 22.75" | 22.75" |
| 24" | 22.50" | 22.75" | 22.75" | 22.75" |
| 36" | 34.50" | 34.75" | 34.75" | 34.75" |
| 48" | 46.50" | 46.75" | 46.75" | 46.75" |
| 60" | 58.50" | 58.75" | 58.75" | 58.75" |
| 72" | 70.50" | 70.75" | 70.75" | 70.75" |
| 84" | 82.50" | 82.75" | 82.75" | 82.75" |
| 96" | 94.50" | 94.75" | 94.75" | 94.75" |

A14 EXACT/OPTIMAL FIXTURE LENGTH

Exact fixtures are the exact length specified. Optimal fixtures' length is rounded down based on LED cut points to allow the fixture to be illuminated end to end. For runs with multiple fixtures that need to fill a specific length, it's recommended to order all optimal fixtures with an exact fixture at the end of the run.





MICRO 5 POP MUD-IN-FLAT (01) FOR WARM DIM APPLICATIONS

24VDC Linear Fixtures - Recessed





DW DRY LENGTHS BY INCH

Available in any length in between 12" and 98.43" not including end caps, chart below shows example lengths. Exact fixtures are the length specified. Optimal fixtures' length is rounded down with illumination end to end. All fixtures' tolerance is +0 - 1/8". Consult factory for lengths under 12".

EXACT LENGTH

| Requested Length | Potential dim spot on either end of fixture |
|------------------|---------------------------------------------|
| 12" | 1" |
| 13" | .5" |
| 14" | 1" |
| 15" | .5" |
| 16" | 1" |
| 17" | .5" |
| 18" | 1" |
| 19" | .5" |
| 20" | 1" |
| 21" | .5" |
| 22" | 1" |
| 23" | .5" |
| 24" | 1" |
| 36" | 1" |
| 48" | 1" |
| 60" | 1" |
| 72" | 1" |
| 84" | 1" |
| 96" | 1" |

OPTIMAL LENGTH: highlighted rows are closest to requested nominal length

| Requested Nominal Length | S1A/B & S2A/B | | P1A/B & P2A/B | |
|--------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| |  |  |  |  |
| 12" | | 10.5" | | 10.75" |
| 13" | | 12.5" | | 12.75" |
| 14" | | 12.5" | | 12.75" |
| 15" | | 14.5" | | 14.75" |
| 16" | | 14.5" | | 14.75" |
| 17" | | 16.5" | | 16.75" |
| 18" | | 16.5" | | 16.75" |
| 19" | | 18.5" | | 18.75" |
| 20" | | 18.5" | | 18.75" |
| 21" | | 20.5" | | 20.75" |
| 22" | | 20.5" | | 20.75" |
| 23" | | 22.5" | | 22.75" |
| 24" | | 22.5" | | 22.75" |
| 36" | | 34.5" | | 34.75" |
| 48" | | 46.5" | | 46.75" |
| 60" | | 58.5" | | 58.75" |
| 72" | | 70.5" | | 70.75" |
| 84" | | 82.5" | | 82.75" |
| 96" | | 94.5" | | 94.75" |

COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

| DIM TO LEVEL | INDOOR |
|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | MICRO 5-DW Warm Dim Applications |
| 0.1% | QT-CAB-eLED+DALI-DT6 QT-CAB-eLED+DALI-DT8 QT-CAB-eLED+DALI-DT8-AWN QT-CAB-eLED+WD QT-CAB-eLED+WD-AWN QTM-eLED+DALI-DT6 QTM-eLED+DALI-DT8 QTM-eLED+DALI-DT8-AWN QTM-eLED+WD QTM-eLED+WD-AWN QZ-DMX QZ-DW |
| 1% | QZ-DALI-DT8 |
| 10% | Non-Dim Power Supply with WD App Dongle |




MICRO 5 POP MUD-IN-FLAT (01) FOR WARM DIM APPLICATIONS

24VDC Linear Fixtures - Recessed

| DIMMING PROTOCOL | INDOOR |
|------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|
| | MICRO 5-DW Warm Dim Applications |
| Phase | QZ-DW |
| 0-10V | QT-CAB-eLED+WD QT-CAB-eLED+WD-AWN QTM-eLED+WD QTM-eLED+WD-AWN QZ-DW |
| Lutron Athena | QT-CAB-eLED+DALI-DT8-AWN QT-CAB-eLED+WD-AWN QTM-eLED+DALI-DT8-AWN QTM-eLED+WD-AWN |
| DMX LED wattage must be doubled for DW-HE products | QZ-DMX |
| DALI-2: DT6 LED wattage must be doubled for DW-HE products except for AWN | QT-CAB-eLED+DALI-DT6 QTM-eLED+DALI-DT6 |
| DALI-2: DT8 LED wattage must be doubled for DW-HE products except for AWN | QT-CAB-eLED+DALI-DT8 QT-CAB-eLED+DALI-DT8-AWN QTM-eLED+DALI-DT8 QTM-eLED+DALI-DT8-AWN QZ-DALI-DT8 |
| SCENE App Dimmed | Non-Dim Power Supply with WD App Dongle |

COMPATIBLE WIRING ACCESSORIES



UL Listed, miniature junction box, DRY/DMP (WET rated with silicone)

COMPATIBLE CONTROL ACCESSORIES

SCENE APP DONGLE



Wi-Fi or Bluetooth Connectivity

COMPATIBLE APPS

NFC APP



Read and write DMX addresses and adjust voltage