





OPTI-FLAT (01) STATIC WHITE DOUBLE ROW

24VDC Linear Fixtures - Surface & Recessed



- Choose from diffused, polar or frosted lens options for varying diode visibility and beam cutoff
- Delivers smooth and consistent light to highlight architectural features and surfaces
- Ideal for surface-mounted installations
- Integrated metal end caps combined with an extruded aluminum housing give this fixture a polished modern look
- Suitable for installation in the storage area of a clothes closet when specified at 4.0 watts or less per foot per NEC regulations



410.2 & 410.16
Closet Rated
up to 4.0W/ft



BUY AMERICAN
ACT COMPLIANT



BUILD AMERICA
BUY AMERICA
COMPLIANT



Declare.

INFORMATION REQUIRED FOR LIGHTING SCHEDULE

| 1 | 2 | 3 | 4 | 5 |
|---------|-----------|-----|-------|------|
| PRODUCT | WATTS/ FT | CCT | RATED | LENS |
| | | | DRY | |

ADDITIONAL INFORMATION REQUIRED TO ORDER

| 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 |
|-----------------------|-----------------------|------------------------|------------|-----------|----------|--------|-------------|-------------------|
| WIRE INPUT/ OUTPUT | CONNECTOR/ WIRE IN | CONNECTOR/ WIRE OUT | WIRE COLOR | WIRE TYPE | MOUNTING | FINISH | LENGTH (IN) | EXACT/ OPTIMAL |
| | | | | | | | | |

Sample Part Number: **OP1SWDR-5.0-30-DRY-DF-S1-BW-CLS-BK-CL2-CC-BK-48"-E**

| | | | | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 PRODUCT OP1SWDR OP1SWDR-USA Select USA option for BAA and BABA projects. See following pages for compatible power supplies. | 2 WATTS/FT 1.5 1.5W/ft 3.0 3.0W/ft 4.0 4.0W/ft 5.0 5.0W/ft 1.5HE 1.5W/ft HE 3.0HE 3.0W/ft HE 6.0HE 6.0W/ft HE 9.0HE 9.0W/ft HE | 3 CCT 18 1800K 20 2000K 22 2200K 24 2400K 27 2700K 30 3000K 35 3500K 40 4000K | 4 RATED DRY IP20 | | |
| 5 LENS DF Diffused PR Polar FR Frosted | 6 WIRE INPUT/OUTPUT SINGLE (Input only) S1 End Feed S2 Bottom Feed PASS THROUGH (Input/Output) P1 End Feed P2 Bottom Feed | 7 CONNECTOR/WIRE IN BW Bare Wire (Standard 36") CON6 Connector 6" CON24 Connector 24" BW Bare Wire (Standard 36") CON6 Connector 6" CON24 Connector 24" | 8 CONNECTOR/WIRE OUT CLS Closed End (No feed) BW Bare Wire (Standard 36") CON6 Connector 6" CON24 Connector 24" | | |
| 9 WIRE COLOR WH White BK Black | 10 WIRE TYPE CL2 Class 2 CL2P Plenum Rated CL2P only available with bare wire leads (BW) | 11 MOUNTING CC Concealed Clip MG Magnet | 12 FINISH ST Satin BK Black WH White CU Custom Custom finishes have longer lead times. Non-RAL 9003 whites custom. | 13 LENGTH (IN) Minimum length is 12", maximum length is 98.43" not including end caps. Contact us for lengths under 12". | 14 EXACT/OPTIMAL O Optimal Illumination E Exact Specified Length Exact fixtures match the exact length you specify, but they may have dim spots at the ends. Optimal fixtures are slightly shorter than the length specified, but provide full illumination from end to end. |

For continuous mounting, consider bottom feed.

BW: Standard length is 36". Max length is 120". Request custom length by writing in part number next to BW (example: BW48)



BW: Standard length is 36". Max length is 120". Request custom length by writing in part number next to BW (example: BW48)




OPTI-FLAT (01) STATIC WHITE DOUBLE ROW

24VDC Linear Fixtures - Surface & Recessed


1 PRODUCT - DIMENSIONS



Profile with
concealed clip



Profile with magnet clip



Profile with magnet mount
clip and magnet mount
accessory

2 DELIVERED LUMENS

[Calculated L70 = 70000 hrs, L70 = 66000 for HE]
Tested with OP1SWDR-**-30-DRY-STD

| | 1.5 W/FT | | 1.5HE W/FT | | 3.0 W/FT | | 3.0HE W/FT | | 4.0 W/FT | | 5.0 W/FT | | 6.0HE W/FT | | 9.0HE W/FT | |
|----|----------|-----|------------|-----|----------|-----|------------|-----|----------|-----|----------|-----|------------|-----|------------|-----|
| | LM/FT | CRI | LM/FT | CRI | LM/FT | CRI | LM/FT | CRI | LM/FT | CRI | LM/FT | CRI | LM/FT | CRI | LM/FT | CRI |
| FR | 145 | 97 | 161 | 98 | 287 | 98 | 318 | 98 | 398 | 98 | 484 | 98 | 634 | 98 | 928 | 98 |
| PR | 136 | 97 | 151 | 98 | 271 | 98 | 302 | 98 | 377 | 98 | 453 | 98 | 600 | 98 | 876 | 98 |
| DF | 121 | 97 | 136 | 98 | 240 | 97 | 272 | 98 | 333 | 98 | 399 | 98 | 536 | 98 | 784 | 98 |

TEMPERATURE RATINGS

| DRY | Ambient Operating Temp - Surface | 1.5 W/FT | | 1.5 W/FT HE | | 3.0 W/FT | | 3.0 W/FT HE | | 4.0 W/FT | | 5.0 W/FT | | 6.0 W/FT HE | | 9.0 HE | |
|-----|-------------------------------------|----------|-------|-------------|-------|----------|-------|-------------|-------|----------|-------|----------|-------|-------------|-------|--------|-------|
| | | Min | Max | Min | Max | Min | Max | Min | Max | Min | Max | Min | Max | Min | Max | Min | Max |
| | | -4°F | 140°F | -4°F | 145°F | -4°F | 135°F | -4°F | 135°F | -4°F | 130°F | -4°F | 125°F | -4°F | 125°F | -4°F | 105°F |




OPTI-FLAT (01) STATIC WHITE DOUBLE ROW

24VDC Linear Fixtures - Surface & Recessed


PHOTOMETRIC PERFORMANCE

Nominal beam spread shown, beam spread varies based on light engine. For more detailed information, see photometric data.




6 WIRE INPUT/OUTPUT


SINGLE (Input only)



PASS THROUGH (Input/Output)



CONFIGURATION OPTIONS






OPTI-FLAT (01) STATIC WHITE DOUBLE ROW


24VDC Linear Fixtures - Surface & Recessed

7 / 8 CONNECTOR/WIRE - IN/OUT

Connector/Wire In or Out not needed to specify product. Standard configuration is BW for Wire In and CLS for Wire out



Bare Wire 36"
22 AWG




6" or 24" Overall
Wire Connector | 22 AWG
IP67 Rated, UL Listed

9 WIRE COLOR



11 MOUNTING

CC
(CC-01)



Concealed Clip

2 pieces of hardware provided for 4' or less; 4 pieces of hardware provided for greater than 4'

To order separately use CC-01 (sold in pairs)

Each clips comes with a #4 x 5/8" Flat Head screw.

MG




Magnet Clip

One MG provided per foot

To order separately use MG-02

MMA-02



Magnet Mount
Accessory for MG-02

Sold separately, to order use MMA-02

Each bracket comes with 2 #6 x 5/8" Flat Head SS

Required when mounting to a non-magnetic surface


12 FINISH



Custom finishes require a longer lead time, consult factory

14 EXACT/OPTIMAL FIXTURE LENGTH

Exact fixtures are the exact length specified. Optimal fixtures' length is rounded down based on LED cut points to allow the fixture to be illuminated end to end. For runs with multiple fixtures that need to fill a specific length, it's recommended to order all optimal fixtures with an exact fixture at the end of the run.






OPTI-FLAT (01) STATIC WHITE DOUBLE ROW

24VDC Linear Fixtures - Surface & Recessed





SWDR DRY LENGTHS BY INCH

Available in any length in between 12" and 98.43" not including end caps, chart below shows example lengths. Exact fixtures are the length specified. Optimal fixtures' length is rounded down with illumination end to end. All fixtures' tolerance is +0 - 1/8". Consult factory for lengths under 12".

EXACT LENGTH

| Requested Length | Potential dim spot on either end of a S1 fixture |
|------------------|-----------------------------------------------------------------------------------|
| |  |
| 12" | 0.25" |
| 13" | 0.25" |
| 14" | 0.25" |
| 15" | 0.25" |
| 16" | 0.25" |
| 17" | 0.25" |
| 18" | 0.25" |
| 19" | 0.25" |
| 20" | 0.25" |
| 21" | 0.25" |
| 22" | 0.25" |
| 23" | 0.25" |
| 24" | 0.25" |
| 36" | 0.25" |
| 48" | 0.25" |
| 60" | 0.25" |
| 72" | 0.25" |
| 84" | 0.25" |
| 96" | 0.25" |


OPTIMAL LENGTH

| Requested Nominal Length | S1 & S2 | | P1 & P2 | |
|--------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
| |  |  |  |  |
| 12" | 11.91" | | 11.66" | |
| 13" | 12.91" | | 12.66" | |
| 14" | 13.91" | | 13.66" | |
| 15" | 14.91" | | 14.66" | |
| 16" | 15.91" | | 15.66" | |
| 17" | 16.91" | | 16.66" | |
| 18" | 17.91" | | 17.66" | |
| 19" | 18.91" | | 18.66" | |
| 20" | 19.91" | | 19.66" | |
| 21" | 20.91" | | 20.66" | |
| 22" | 21.91" | | 21.66" | |
| 23" | 22.91" | | 22.66" | |
| 24" | 23.91" | | 23.66" | |
| 36" | 35.91" | | 35.66" | |
| 48" | 47.91" | | 47.66" | |
| 60" | 59.91" | | 59.66" | |
| 72" | 71.91" | | 71.66" | |
| 84" | 83.91" | | 83.66" | |
| 96" | 95.91" | | 95.66" | |





SWDR-HE DRY LENGTHS BY INCH

Available in any length in between 12" and 98.43" not including end caps, chart below shows example lengths. Exact fixtures are the length specified. Optimal fixtures' length is rounded down with illumination end to end. All fixtures' tolerance is +0 - 1/8". Consult factory for lengths under 12".

EXACT LENGTH

| Requested Length | Potential dim spot on either end of a S1 fixture |
|------------------|-------------------------------------------------------------------------------------|
| |  |
| 12" | 0.5" |
| 13" | 0.5" |
| 14" | 0.5" |
| 15" | 0.5" |
| 16" | 0.5" |
| 17" | 0.5" |
| 18" | 0.5" |
| 19" | 0.5" |
| 20" | 0.5" |
| 21" | 0.5" |
| 22" | 0.5" |
| 23" | 0.5" |
| 24" | 0.5" |
| 36" | 0.5" |
| 48" | 0.5" |
| 60" | 0.5" |
| 72" | 0.5" |
| 84" | 0.5" |
| 96" | 0.5" |

OPTIMAL LENGTH

| Requested Nominal Length | S1 & S2 | | P1 & P2 | |
|--------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| |  |  |  |  |
| 12" | 11.41" | | 11.66" | |
| 13" | 12.41" | | 12.66" | |
| 14" | 13.41" | | 13.66" | |
| 15" | 14.41" | | 14.66" | |
| 16" | 15.41" | | 15.66" | |
| 17" | 16.41" | | 16.66" | |
| 18" | 17.41" | | 17.66" | |
| 19" | 18.41" | | 18.66" | |
| 20" | 19.41" | | 19.66" | |
| 21" | 20.41" | | 20.66" | |
| 22" | 21.41" | | 21.66" | |
| 23" | 22.41" | | 22.66" | |
| 24" | 23.41" | | 23.66" | |
| 36" | 35.41" | | 35.66" | |
| 48" | 47.41" | | 47.66" | |
| 60" | 59.41" | | 59.66" | |
| 72" | 71.41" | | 71.66" | |
| 84" | 83.41" | | 83.66" | |
| 96" | 95.41" | | 95.66" | |



OPTI-FLAT (01) STATIC WHITE DOUBLE ROW

24VDC Linear Fixtures - Surface & Recessed

COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

| DIM TO LEVEL | INDOOR |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | SW24/1.5-4.0 |
| Dim to Black | Q6M-DC+CAP QTM-DC+CAP IQ-PH+QD1 |
| 0.1% | QT-CAB-QZ-PH/0-10V QT-CAB-eLED+0-10V QT-CAB-eLED+0-10V-AWN QT-CAB-eLED+DALI-DT6 QT-CAB-eLED+DALI-DT6-AWN QTM-eLED+0-10V QTM-eLED+0-10V-AWN QTM-eLED+DALI-DT6 QTM-eLED+DALI-DT6-AWN QZ-BOWTIE+DIMMER QZ-DMX QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP |
| 1% | QTM-eLED(E) QZ-DALI-DT6 |
| 10% | Non-Dim Power Supply with SW App Dongle |















| DIMMING PROTOCOL | INDOOR |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| | SW24/1.5-4.0 |
| Non-Dim | QT-CAB-eLED-ND QTM-eLED-ND QZ-ND |
| Phase | Q6M-DC+CAP QT-CAB-QZ-PH/0-10V QTM-DC+CAP QTM-eLED(E) QZ-BOWTIE+DIMMER QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP IQ-PH+QD1 |
| 0-10V | QT-CAB-QZ-PH/0-10V QT-CAB-eLED+0-10V QT-CAB-eLED+0-10V-AWN QTM-eLED+0-10V QTM-eLED+0-10V-AWN QZ-PH/0-10V QZ-STICK-PH/0-10V QZLP |
| Lutron Athena | QT-CAB-eLED+0-10V-AWN QT-CAB-eLED+DALI-DT6-AWN QTM-eLED+0-10V-AWN QTM-eLED+DALI-DT6-AWN |
| ECO System | QTM-eLED(E) |
| DMX | QZ-DMX |
| DALI-2: DT6 | QT-CAB-eLED+DALI-DT6 QT-CAB-eLED+DALI-DT6-AWN QTM-eLED+DALI-DT6 QTM-eLED+DALI-DT6-AWN QZ-DALI-DT6 |
| SCENE App Dimmed | Non-Dim Power Supply with SW App Dongle |








OPTI-FLAT (01) STATIC WHITE DOUBLE ROW

24VDC Linear Fixtures - Surface & Recessed

COMPATIBLE MOUNTING ACCESSORIES

| | | | | | | | | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| HINGE - HMB-M  1.41" .71" Adjustable mounting bracket - Medium | HINGE - HMB-L  1.46" 1.29" Adjustable mounting bracket - Large | HINGE - HMB-XL  4" 1.46" Adjustable mounting bracket - XLarge | Q-PIVOT  .75" 1.03" Small mounting accessory | Q-ANGLE  2.23" 1.38" Adjustable mounting accessory | QUOVA-STANDARD  QUOVA Knife Edge | NJ-LARGE  J Mounting Bracket | NU-LARGE  U Mounting Bracket | SD-J-LARGE  J Mounting Bracket | BL-LARGE  Backwards L Mounting Bracket |
| BL-LARGE  Backwards L Mounting Bracket | NL-LARGE  L Mounting Bracket | SD-L-LARGE  L Mounting Bracket | MMA-02  .58" Magnet Mount Accessory of MG-02 | | | | | | |

COMPATIBLE WIRING ACCESSORIES

| | | | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Q-mini-J  2" 1.25" UL Listed miniature junction box, DRY/DMP (WET rated with silicone) | Q-mini-J5  2.80" 2.27" UL Listed miniature junction box, DRY/DMP (WET rated with silicone) | CON120-EXT  10ft Con cable extender, DRY/DMP/WET | CON FOUR-FER  Splits lead from one to four LED Con connectors, DRY/DMP/WET | CON M - BARREL F  Male con to barrel cable adaptor, DRY/DMP |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|

COMPATIBLE CONTROL ACCESSORIES

SCENE APP DONGLE



COMPATIBLE APPS

