




ST-2

12V MR16 20W Halogen/8W LED Core Drill  
Step Light



- 6061 Marine Grade Aluminum, available in eight standard TGIC Free powder coat finishes.
- Stainless steel hardware.
- Tempered crystalline spread lens.
- 6 feet of 16/2 low voltage cable supplied.
- Core drill design for masonry (2 1/2" hole required).
- High-temperature silicone O-ring seal used to seal the cap against the body.
- Molded silicone wire pass-thru attached to socket wire prevents wicking and water leaking into the lamp compartment.
- Maximum Wattage: 20W Halogen/8W LED
- Input Voltage: 12V (remote transformer required)
- Socket: GU5.3 Bi Pin Porcelain
- Wet Listed
- Specification-grade, wet-location landscape luminaire for wall mounted fixed downlighting and uplighting applications.

ST-2 Shown in Bronze Texture Powder Coat Finish (BZT)

Dimensions: 5" x 3" faceplate; 4 1/2" length

1	2	3
PRODUCT	MATERIAL	FINISH
ST-2	A	

Sample Part Number: ST-2-A-BK



1	2	3
PRODUCT	MATERIAL	FINISH
ST-2	A Aluminum	BG Beige BB Black Bronze BK Black BKT Black Texture BZ Bronze BZT Bronze Texture SL Silver WH White




# ST-2

12V MR16 20W Halogen/8W LED Core Drill Step Light

## 1 PRODUCT - DIMENSIONS



## 2 MATERIAL



## 3 FINISH

Eight Standard TGIC Free powder coat finishes available



## LAMPS

MR16 Halogen or LED; GU5.3 Bi-Pin Porcelain  
Maximum wattage: 20W Halogen/8W LED





**ST-2**

12V MR16 20W Halogen/8W LED Core Drill Step Light

COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

DIMMING PROTOCOL	OUTDOOR
	LANDSCAPE LIGHTING
Phase	Q-HEX Q-SET-1 Q-SET-2 Q-SET-3 QOMD QOMS