




ST-8
12V MR16 20W Halogen/8W LED Box Mount
Step Light



- 6061 Marine Grade Aluminum, available in eight standard TGIC Free powder coat finishes.
- Stainless steel hardware.
- Tempered crystalline spread lens.
- Single gang junction box design.
- High-temperature silicone O-ring seal used to seal the cap against the body.
- Molded silicone wire pass-thru attached to socket wire prevents wicking and water leaking into the lamp compartment.
- Maximum Wattage: 20W Halogen/8W LED
- Input Voltage: 12V (remote transformer required)
- Lens: Tempered Crystalline Spread
- Socket: GU5.3 Bi Pin Porcelain
- Wet Listed
- Specification-grade, wet-location landscape luminaire for wall mounted fixed downlighting and uplighting applications.

ST-8 Shown in Bronze Texture Powder Coat Finish (BZT)

Dimensions: 5" x 3 " faceplate; 3 1/4" length

1	2	3
PRODUCT	MATERIAL	FINISH
ST-8	A	

Sample Part Number: ST-8-A-BK

1	2	3
PRODUCT	MATERIAL	FINISH
ST-8	A Aluminum	<div><div>BG</div><div>BB</div><div>BK</div><div>BKT</div><div>BZ</div><div>BZT</div><div>SL</div><div>WH</div><div>Beige</div><div>Black Bronze</div><div>Black</div><div>Black Texture</div><div>Bronze</div><div>Bronze Texture</div><div>Silver</div><div>White</div></div>

5 year warranty | Warranty only valid with QTL power supplies | Field modifications void warranty | Data subject to change, all data has +/- 5% tolerance




ST-8

12V MR16 20W Halogen/8W LED Box Mount Step Light

1

PRODUCT - DIMENSIONS



2


MATERIAL



3


FINISH

Eight Standard TGIC Free powder coat finishes available



LAMPS

MR16 Halogen or LED; GU5.3 Bi-Pin Porcelain
Maximum wattage: 20W Halogen/8W LED





ST-8

12V MR16 20W Halogen/8W LED Box Mount Step Light

COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

DIMMING PROTOCOL	OUTDOOR
	LANDSCAPE LIGHTING
Phase	Q-HEX Q-SET-1 Q-SET-2 Q-SET-3 QOMD QOMS