




IN-10
12V MR16 35W Halogen/8W LED In Ground
Well Light



- 6061 Marine Grade Aluminum. Eight standard TGIC Free powder coat finishes
- 15 degrees of aiming adjustment.
- Machined aluminum lamp holder.
- Tempered glass lens.
- 6' of 16/2 low voltage cable supplied.
- Maximum Wattage: 35W Halogen/8W LED
- Input Voltage: 12V (remote transformer required)
- Socket: GU5.3 Bi Pin Porcelain
- Wet Listed
- Specification-grade, wet-location direct burial landscape luminaire for uplighting applications.

IN-10 Shown in Bronze Texture Powder Coat Finish (BZT)

Dimensions: 6 5/8" dia. x 11 1/4" tall

1	2	3	4
PRODUCT	MATERIAL	FIXTURE REGRESS	FINISH
IN-10	A		

Sample Part Number: IN-10-A-1-NT

1	2	3	4
PRODUCT	MATERIAL	FIXTURE REGRESS	FINISH
IN-10	A Aluminum	1 13/4" Regress 2 3" Regress (standard)	BG Beige BB Black Bronze BK Black BKT Black Texture BZ Bronze BZT Bronze Texture SL Silver WH White


5 year warranty | Warranty only valid with QTL power supplies | Field modifications void warranty | Data subject to change, all data has +/- 5% tolerance



IN-10

12V MR16 35W Halogen/8W LED In Ground Well Light

1 PRODUCT - DIMENSIONS



2 MATERIAL



Aluminum

4 FINISH

Eight Standard TGIC Free powder coat finishes



Beige

Black

Black Texture

Bronze



Bronze Texture

Black Bronze

Silver

White

ACCESSORIES - COLOR FILTERS

Holds up to three accessories Wire Filter Holder is included for each color filter in place.

BL



Blue Glass Filter

To order separately
use AY-2-MR16-BL

LB



Light Blue
Glass Filter

To order separately
use AY-2-MR16-LB

PK



Pink Glass Filter

To order separately
use AY-2-MR16-PK


AM



Amber Glass Filter

To order separately
use AY-2-MR16-AM


MV



Mercury Vapor
Glass Filter

To order separately
use AY-2-MR16-MV

RD



Red Glass Filter

To order separately
use AY-2-MR16-RD

GR



Green Glass Filter

To order separately
use AY-2-MR16-GR

DA



Dichroic Amber
Glass Filter

To order separately
use AY-2-MR16-DA



IN-10

12V MR16 35W Halogen/8W LED In Ground Well Light

ACCESSORIES - LENS

Holds up to three accessories

SP



Spread Lens

To order separately
use AY-1-MR16-1

LI



Linear Lens

To order separately
use AY-1-MR16-2

SO



Softening Lens

To order separately
use AY-1-MR16-3

LV



Louver Lens

To order separately
use AY-1-MR16-4

WI



Wire Holder

To order separately
use AY-1-MR16-5

FR




Frosted Lens

To order separately
use AY-1-MR16-6

LAMPS

MR16 Halogen or LED; GU5.3 Bi Pin Porcelain
Maximum wattage: 35W Halogen/8W LED


MR16



EMERY ALLEN

1.0W, 3.0W, 5.0W,
7.0W

MR16



EMERY ALLEN

3W AMBER

COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

DIMMING PROTOCOL	OUTDOOR
	LANDSCAPE LIGHTING
Phase	Q-HEX Q-SET-1 Q-SET-2 Q-SET-3 QOMD QOMS