





## ARKA

### Field Assembled Extrusion - Corner & Surface

SEE THIS EXTRUSION AS A FACTORY BUILT FIXTURE ►



- ARKA is a 45° angled LED extrusion with a curved lens
- Produces a wide 130° beam angle for cove lighting applications
- Combine ARKA with White Optics to increase light output between 2-20%

1	2	3	4	5	6
PRODUCT	FINISH	MOUNTING	LENS	WIRE INPUT/OUTPUT	EXTRUSION LENGTH (IN)
				NI	

Sample Part Number: **ARKA-WO-ST-PL-DF-NI-48"**

<b>1</b>	<b>PRODUCT</b>  <b>ARKA</b> <b>ARKA-WO</b>  WO - WhiteOptics (Internal coating, greater lumen output)	<b>2</b>	<b>FINISH</b>  <b>ST</b> Satin <b>BK</b> Black <b>BZ</b> Bronze <b>CU</b> Custom Color  Custom finishes require a longer lead time, consult factory	<b>3</b>	<b>MOUNTING</b>  <b>SST</b> Stainless Steel <b>PL</b> Plastic Clip  Refer to following pages for mounting clip option details and provided quantities.
<b>4</b>	<b>LENS</b>  <b>DF</b> Diffused <b>PR</b> Polar <b>FR</b> Frosted <b>CL</b> Clear  For representation of LED visibility, see Diode Visibility section on following pages. For beam angles, see Photometric Performance section on following pages.	<b>5</b>	<b>WIRE INPUT/OUTPUT</b>  <b>NI</b> Not Installed	<b>6</b>	<b>EXTRUSION LENGTH (IN)</b>  1" increments from 1" - 98.43" Tolerance +0.0"/-0.5"

## COMPATIBLE LED STRIPS

	STATIC WHITE (SW)	STATIC WHITE STANDARD (SD-SW)	STATIC WHITE HIGH EFFICACY (SW-HE)	STATIC WHITE HIGH EFFICACY PLUS (SW-HE+)	STATIC WHITE EXTREME TEMP (SW-XT)	STATIC WHITE DOUBLE ROW (SW-DR)	STATIC WHITE HIGH EFFICACY DOUBLE ROW (SW-HE-DR)	DYNAMIC WHITE HIGH EFFICACY (DW-HE)	WARM DIM (WD)	STATIC COLOR (SC)	RGB	RGBW	RGBW HIGH EFFICACY (RGBW-HE)
<b>DRY</b>	✓ W/FT: 15, 30, 40, 50	✓ W/FT: 10, 20, 40, 60	✓ W/FT: 15, 30, 60	✓ W/FT: 30, 60				✓ W/FT: 15, 25	✓ W/FT: 60	✓ W/FT: 50	✓ W/FT: 60	✓ W/FT: 60	✓ W/FT: 40 NO CLEAR LENS
<b>DMP</b>	✓ W/FT: 15, 30, 40, 50		✓ W/FT: 15, 30, 60					✓ W/FT: 15, 25		✓ W/FT: 50	✓ W/FT: 60	✓ W/FT: 60	✓ W/FT: 40 NO CLEAR LENS
<b>ENC</b>													
<b>WET</b>	✓ W/FT: 15, 30, 40, 50	✓ W/FT: 10, 20, 40		✓ W/FT: 30, 60				✓ W/FT: 15, 25	✓ W/FT: 60	✓ W/FT: 50	✓ W/FT: 60		✓ W/FT: 40 NO CLEAR LENS

Field modifications must comply with QTL's installation methods otherwise warranty is null & void | Corner/surface mount | Painted end caps match the extrusion finish and have a white painted interior. Satin end caps utilize a metallic paint.




# ARKA


## Field Assembled Extrusion - Corner & Surface

SEE THIS EXTRUSION AS A FACTORY BUILT FIXTURE ▶


### 1 PRODUCT - DIMENSIONS



Profile



Profile with stainless steel mounting clip




Profile with plastic mounting clip

### END CAPS

One pair of end caps is provided with each length of extrusion ordered.

Flat end caps



No feed


To order separately, use  
ARKA-EC

### WHITEOPTICS® PHOTOMETRICS

[Calculated L70(6k) - 70000 hours] Tested with SW24/5.0-DRY-30

	ARKA LM/FT		ARKA-WO LM/FT		ARKA-WO Lumen Increase	
	Satin	Black/Bronze	Satin	Black/Bronze	Satin	Black/Bronze
Clear	432	410	439	438	2%	7%
Frosted	426	404	431	425	1%	5%
Polar	391	371	413	408	6%	10%
Diffused	361	320	390	385	8%	20%


### 2 FINISH



Custom finishes require  
a longer lead time,  
consult factory

### 3 MOUNTING

SST




Stainless Steel Clip

2 clips provided for 4' or less; 4 clips provided  
for greater than 4'

To order separately use SST-03

Each clip comes with a #4 x 5/8" Flat Head SS

PL



Plastic Clip

2 clips provided for 4' or less; 4 clips provided  
for greater than 4'.

To order separately use PLC-02

Each clip comes with a #4 x 5/8" Flat Head SS




ARKA

Field Assembled Extrusion - Corner & Surface


SEE THIS EXTRUSION AS A FACTORY BUILT FIXTURE ▶

4 DIODE VISIBILITY



PHOTOMETRIC PERFORMANCE

Nominal beam spread shown, beam spread varies based on light engine. For more detailed information, see factory built fixture photometric data.



Clear 130°

COMPATIBLE ACCESSORIES

HINGE - HMB-M	HINGE - HMB-L	HINGE - HMB-XL	Q-PIVOT	Q-ANGLE	QUOVA-STANDARD	VHB	SHIELD B - Small	SHIELD B - Medium	SD-J-LARGE
Adjustable mounting bracket - Medium	Adjustable mounting bracket - Large	Adjustable mounting bracket - XLarge	Small mounting accessory	Adjustable mounting accessory	QUOVA Knife Edge	Double sided mounting tape	For use within extrusions	For use within extrusions	J Mounting Bracket