





BL-GRAZER
BACKWARDS L BRACKET - ALUMINUM
EXTRUSION




- Backwards L bracket with no reveal, creating the least amount of cutoff
- Surface mount from the bottom, ideal for illuminating pre-existing cove applications
- Mounts grazer fixtures, LED light engines, and SHIELD
- Paintable finish
- Intended for indoor use only
- Mounting clips conveniently preinstalled for hassle-free installation
- Durable anodized aluminum

1	2	3	4
PRODUCT	FINISH	MOUNTING	LENGTH (IN)
BL-GRAZER			


Sample Part Number: BL-GRAZER-ST-SST-01-48"

1	2	3	4
PRODUCT	FINISH	MOUNTING	LENGTH (IN)
BL-GRAZER	ST Satin BK Black	SST-08 Stainless Steel Clip CC-01 Concealed Clip VHB VHB Tape N/A No Clip (For Light Engine) Mounting clips preinstalled See MOUNTING COMPATIBILITY CHART for more information	1" increments from 2" - 98.43" Tolerance +0.0/-0.5" Light engine ordered separately


1 PRODUCT - DIMENSIONS WITH RECOMMENDED PROFILES




Profile



profile with: ALTA-02



profile with: TORQ-02



profile with: VERS-04

Field modifications must comply with QTL's installation methods otherwise warranty is null & void | Surface mount



BL-GRAZER

BACKWARDS L BRACKET - ALUMINUM EXTRUSION

2


FINISH



3

MOUNTING


SST
(SST-08)



Stainless Steel Clip

To order separately use
SST-08

CC
(CC-01)



Concealed Clip

To order separately use
CC-01 (sold in pairs)








VHB TAPE
(TAPE-VHB-IP67-5)



Sold separately

10MM wide VHB Tape
To order separately use
TAPE-VHB-IP67-5

COMPATIBILITY CHART

	 SHIELD-B	 ATOM-02	 ALTA-02	 LALO-02	 VERS-04	 TORQ-02	 LIGHT ENGINE
Lens Notes		Works with: ATOM-02	Works with: ALTA-02	Works with: LALO-02	Works with: VERS-04	Works with: TORQ-02	
SST-08 Stainless Steel Clip		✓	✓				
CC-01 Concealed Clip					✓		
VHB		✓		✓		✓	
N/A	✓						✓



BL-GRAZER

BACKWARDS L BRACKET - ALUMINUM EXTRUSION

LIGHT ENGINE COMPATIBILITY CHART

Order Separately

LED Strips No extrusion	STATIC WHITE (SW)	STATIC WHITE INDIVIDUALLY ADDRESSABLE (SW-IA)	STATIC WHITE STOCKING DISTRIBUTOR (SD-SW)	STATIC WHITE HIGH EFFICACY (SW-HE)	STATIC WHITE HIGH EFFICACY PLUS (SW-HE+)	STATIC WHITE EXTREME TEMP (SW-XT)	DYNAMIC WHITE HIGH EFFICACY (DW- HE)	WARM DIM (WD)	STATIC COLOR (SC)	RGB	RGBW	RGBW HIGH EFFICACY (RGBW-HE)
DRY	✓ W/FT: 1.5, 3.0, 4.0, 5.0	✓ W/FT: 5.0	✓ W/FT: 1.0, 2.0, 4.0, 6.0	✓ W/FT: 1.5, 3.0, 6.0, 9.0	✓ W/FT: 3.0, 6.0		✓ W/FT: 1.5, 2.5, 4.0	✓ W/FT: 6.0	✓ W/FT: 5.0	✓ W/FT: 6.0	✓ W/FT: 6.0	✓ W/FT: 4.0, 8.0
DMP	✓ W/FT: 1.5, 3.0, 4.0, 5.0			✓ W/FT: 1.5, 3.0, 6.0			✓ W/FT: 1.5, 2.5		✓ W/FT: 5.0	✓ W/FT: 6.0	✓ W/FT: 6.0	✓ W/FT: 4.0
WET	✓ W/FT: 1.5, 3.0, 4.0, 5.0		✓ W/FT: 1.0, 2.0, 4.0, 6.0	✓ W/FT: 1.5, 3.0, 6.0	✓ W/FT: 3.0, 6.0	✓ W/FT: 3.0	✓ W/FT: 1.5, 2.5	✓ W/FT: 6.0	✓ W/FT: 5.0	✓ W/FT: 6.0	✓ W/FT: 6.0	✓ W/FT: 4.0

ACCESSORY COMPATIBILITY CHART

Order Separately | Only Compatible with DRY

LED Strips No extrusion		STATIC WHITE (SW)	STATIC WHITE INDIVIDUALLY ADDRESSABLE (SW-IA)	STATIC WHITE STOCKING DISTRIBUTOR (SD-SW)	STATIC WHITE HIGH EFFICACY (SW-HE)	STATIC WHITE HIGH EFFICACY PLUS (SW-HE+)	STATIC WHITE EXTREME TEMP (SW-XT)	DYNAMIC WHITE HIGH EFFICACY (DW- HE)	WARM DIM (WD)	STATIC COLOR (SC)	RGB	RGBW	RGBW HIGH EFFICACY (RGBW-HE)
SHIELD-B	S	✓ W/FT: 1.5, 3.0, 4.0, 5.0		✓ W/FT: 2.0, 4.0, 6.0						✓ W/FT: 5.0			
	M		✓ W/FT: 5.0			✓ W/FT: 3.0, 6.0		✓ W/FT: 1.5, 2.5	✓ W/FT: 6.0		✓ W/FT: 6.0		✓ W/FT: 4.0
	L				✓ W/FT: 1.5, 3.0, 6.0							✓ W/FT: 6.0	




BL-GRAZER


BACKWARDS L BRACKET - ALUMINUM EXTRUSION

COMPATIBLE SHIELD


Order separately | See SHIELD cut sheet for more information



Profile - S



Profile - M



Profile - L

PHOTOMETRIC PERFORMANCE

Tested with SW24/5.0 at 3000K & MICRO-SW24/4.0 at 3000K

