

# VERS-FLUSH-SK (02) STATIC COLOR

24VDC Linear Fixtures - Suspended

Certified with Red & Amber






- 80 Suspension Kit configurations allow fixture to be seamlessly incorporated into any interior
- Create long, continuous lines of light with easy-to-use inline bracket and double feed joiner connectors
- This VERSatile fixture features a co-extruded lens with an internal reflector, maximizing efficiency for improved lumen output
- The lens sits flush and is available in polar or diffused
- Features integrated metal endcaps and durable anodized aluminum housings
- With standard internal White Optics coating, fixtures achieve greater lumen efficacies
- Consult factory for field assembly options
- Optional external louver accessory available in white or black for added glare control

| 1 PRODUCT | 2 WATTS/ FT | 3 CCT | 4 RATED | 5 LENS | 6 EXTERNAL LOUVER | 7 WIRE INPUT/ OUTPUT | 8 CONNECTOR/ WIRE IN | 9 CONNECTOR/ WIRE OUT | 10 WIRE COLOR | 11 WIRE TYPE | 12 MOUNTING | 13 FINISH | 14 LENGTH (IN) | 15 EXACT/ OPTIMAL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| VERS-02-SK-SC | 5.0 | | | | | S2 | BW | CLS | SV | AWM | SK | | | |

Sample Part Number: **VERS-02-SC-5.0-GR-DRY-DF-L1-BK-P1-CON6-CON6-BK-CL2-MG-BK-48"-E**

### 1 PRODUCT

**VERS-02-SK-SC**

See following pages for compatible power supplies.

### 2 WATTS/FT

**5.0** 5.0W/ft

### 3 CCT

**A** Amber
**B** Blue
**G** Green
**R** Red

### 4 RATED

**DRY** IP20
**DMP** IP54

### 5 LENS

**DF** Diffused
**PR** Polar

For representation of LED visibility, see Diode Visibility section on following pages.
For beam angles, see Photometric Performance section on following pages.

### 6 EXTERNAL LOUVER

**L2-ST** Satin Anodized Aluminum
**L2-BK** Black Anodized Aluminum
**L2-WH** White Powder Coated Aluminum
**N/A** No Louver

### 7 WIRE INPUT/OUTPUT

**S2** Single 2 (Input only) - Bottom Feed

### 8 CONNECTOR/WIRE IN

**BW** Bare Wire (Standard 36")

BW: Standard length is 36", max length is 120". Request custom length by writing in part number next to BW (example: BW48)

### 9 CONNECTOR/WIRE OUT

**CLS** Closed End (No feed)

BW: Standard length is 36", Max length is 120". Request custom length by writing in part number next to BW (example: BW48)

### 10 WIRE COLOR

**SV** Silver

### 11 WIRE TYPE

**AWM** Appliance Wiring Material

### 12 MOUNTING

**SK** Suspension Bracket

### 13 FINISH

**ST** Satin
**BK** Black
**BZ** Bronze
**WH** White
**CU** Custom

White and custom finishes are incompatible with external louvers; custom finishes have longer lead times. Non-RAL 9003 whites custom.

### 14 LENGTH (IN)

Minimum length is 12", maximum length is 98" not including end caps. Contact us for lengths under 12".

### 15 EXACT/OPTIMAL

**O** Optimal Illumination
**E** Exact Specified Length

Exact fixtures are the exact length specified +0 -1/8". Optimal fixtures' length is rounded down with illumination end to end. See Exact/Optimal Fixture Length charts.

PRELIMINARY SUBJECT TO CHANGE


© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTLlighting | www.QTLlighting

Specification subject to change. Rev-09-25-26


# VERS-FLUSH-SK (02) STATIC COLOR

24VDC Linear Fixtures - Suspended

## 1 PRODUCT - DIMENSIONS




Profile with lens




Profile with L1 Louver

## 2 DELIVERED LUMENS

[Calculated L70 = 50000 hrs]
Tested with VERS-02-SK-SC-5.0-**-DRY

| | Red | | Green | | Blue | | Amber | |
|---|---|---|---|---|---|---|---|---|
| | LM/FT | Wavelength | LM/FT | Wavelength | LM/FT | Wavelength | LM/FT | Wavelength |
| PR | 120 | 634 | 561 | 519 | 127 | 467 | 88 | 595 |
| DF | 114 | 634 | 530 | 519 | 119 | 467 | 83 | 595 |

## 5 DIODE VISIBILITY




DF - Diffused lens

PR - Polar lens

## PHOTOMETRIC PERFORMANCE

Nominal beam spread shown, beam spread varies based on light engine. For more detailed information, see photometric data.

**5W/ft | Green** Polar lens




## TEMPERATURE RATINGS

| | | 5.0 W/FT | |
|---|---|---|---|
| | | Min | Max |
| DRY | Ambient Operating Temp - Surface | -4°F | 125°F |
| DMP | Ambient Operating Temp - Surface | -4°F | 125°F |

PRELIMINARY SUBJECT TO CHANGE


© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTLlighting | www.QTLlighting

# VERS-FLUSH-SK (02) STATIC COLOR

24VDC Linear Fixtures - Suspended

## 7 WIRE INPUT/ OUTPUT


SINGLE (Input only)





## CONFIGURATION OPTIONS




Single Feed




Continuous Row End Feeds





Continuous Row Center Feeds

## 8 / 9 CONNECTOR/WIRE – IN/OUT

Connector/Wire In or Out not needed to specify product.

BW





Bare Wire 36" | 22 AWG
Clear outer jacket, metal shield

## 10 WIRE COLOR

Silver

## 12 MOUNTING

SK




Suspension Bracket

2 required up to 6' lengths; additional support required between 6' to 8'

## 13 FINISH

Satin
Black
Bronze
White

White and custom finishes are incompatible with external louvers; custom finishes have longer lead times. Non-RAL 9003 whites custom.

PRELIMINARY
SUBJECT TO CHANGE

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTLlighting | www.QTLlighting


# VERS-FLUSH-SK (02) STATIC COLOR

24VDC Linear Fixtures - Suspended

## 15 EXACT/OPTIMAL FIXTURE LENGTH

E/O Length Calculator → E/O Explained →

Exact fixtures are the exact length specified +0 -1/8". Optimal fixtures' length is rounded down based on LED cut points to allow the fixture to be illuminated end to end. For runs with multiple fixtures that need to fill a specific length, it's recommended to order all optimal fixtures with an exact fixture at the end of the run.




## SC DRY DMP LENGTHS BY INCH

### EXACT LENGTH

| Requested Length | Potential dim spot on either end of a S1 fixture |
|---|---|
| 12" | 1" |
| 13" | 0.5" |
| 14" | 1" |
| 15" | 0.5" |
| 16" | 1" |
| 17" | 0.5" |
| 18" | 1" |
| 19" | 0.5" |
| 20" | 1" |
| 21" | 0.5" |
| 22" | 1" |
| 23" | 0.5" |
| 24" | 1" |
| 36" | 1" |
| 48" | 1" |
| 60" | 1" |
| 72" | 1" |
| 84" | 1" |
| 96" | 1" |

### OPTIMAL LENGTH

| Requested Nominal Length | S2 |
|---|---|
| 12" | 10.49" |
| 13" | 12.49" |
| 14" | 12.49" |
| 15" | 14.49" |
| 16" | 14.49" |
| 17" | 16.49" |
| 18" | 16.49" |
| 19" | 18.49" |
| 20" | 18.49" |
| 21" | 20.49" |
| 22" | 20.49" |
| 23" | 22.49" |
| 24" | 22.49" |
| 36" | 34.49" |
| 48" | 46.49" |
| 60" | 58.49" |
| 72" | 70.49" |
| 84" | 82.49" |
| 96" | 94.49" |

PRELIMINARY
SUBJECT TO CHANGE

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTLlighting | www.QTLlighting

# VERS-FLUSH-SK (02) STATIC COLOR

24VDC Linear Fixtures - Suspended

## COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

| DIM TO LEVEL | INDOOR |
|---|---|
| | SC |
| Dim to Black | Q6M-DC+CAP<br>QTM-DC+CAP<br>iQ-PH+QD1 |
| 0.1% | QT-CAB-QZ-PH/0-10V<br>QT-CAB-eLED+0-10V<br>QT-CAB-eLED+0-10V-AWN<br>QT-CAB-eLED+DALI-DT6<br>QT-CAB-eLED+DALI-DT6-AWN<br>QTM-eLED+0-10V<br>QTM-eLED+0-10V-AWN<br>QTM-eLED+DALI-DT6<br>QTM-eLED+DALI-DT6-AWN<br>QZ-BOWTIE+DIMMER<br>QZ-DMX<br>QZ-PRO-PH/0-10V<br>QZ-STICK-PH/0-10V<br>QZLP |
| 1% | Q-DIM<br>QTM-eLED(E)<br>QZ-DALI-DT6 |
| 10% | Non-Dim Power Supply with SW App Dongle |

| DIMMING PROTOCOL | INDOOR |
|---|---|
| | SC |
| Non-Dim | QT-CAB-eLED-ND<br>QTM-eLED-ND<br>QZ-ND |
| Phase | Q6M-DC+CAP<br>QT-CAB-QZ-PH/0-10V<br>QTM-DC+CAP<br>QTM-eLED(E)<br>QZ-BOWTIE+DIMMER<br>QZ-PRO-PH/0-10V<br>QZ-STICK-PH/0-10V<br>QZLP<br>iQ-PH+QD1 |
| 0-10V | QT-CAB-QZ-PH/0-10V<br>QT-CAB-eLED+0-10V<br>QT-CAB-eLED+0-10V-AWN<br>QTM-eLED+0-10V<br>QTM-eLED+0-10V-AWN<br>QZ-PRO-PH/0-10V<br>QZ-STICK-PH/0-10V<br>QZLP |
| Lutron Athena | QT-CAB-eLED+0-10V-AWN<br>QT-CAB-eLED+DALI-DT6-AWN<br>QTM-eLED+0-10V-AWN<br>QTM-eLED+DALI-DT6-AWN |
| ECO System | QTM-eLED(E) |
| DMX | QZ-DMX |
| DALI-2: DT6 | QT-CAB-eLED+DALI-DT6<br>QT-CAB-eLED+DALI-DT6-AWN<br>QTM-eLED+DALI-DT6<br>QTM-eLED+DALI-DT6-AWN<br>QZ-DALI-DT6 |
| SCENE App Dimmed | Non-Dim Power Supply with SW App Dongle |

PRELIMINARY
SUBJECT TO CHANGE

# VERS-FLUSH-SK (02) STATIC COLOR

24VDC Linear Fixtures - Suspended

PRELIMINARY
SUBJECT TO CHANGE

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting