







# VERS-NANO-LOUVER (11) FOR TUNABLE APPLICATIONS

24VDC Linear Fixtures - Surface & Recessed


## 1 PRODUCT - DIMENSIONS




Profile with lens




Profile with concealed clip




Profile with magnetic clip




Profile with magnet mount clip & magnetic mount accessory



Profile with TBC-03



Profile with TBC-04



Profile with TBC-05

## 2 DELIVERED LUMENS

[Calculated L70 = 70000 hrs]  
Tested with VERS-11-DW-\*\*-\*\*-DRY

|      | 1.5HE W/FT |     |        | 2.5HE W/FT |     |        | 4.0HE W/FT |     |        |
|------|------------|-----|--------|------------|-----|--------|------------|-----|--------|
|      | LM/FT      | CRI | UGR    | LM/FT      | CRI | UGR    | LM/FT      | CRI | UGR    |
| DF-C | 36         | 98  | ≤ 11.0 | 60         | 98  | ≤ 12.8 | 80         | 99  | ≤ 13.8 |
| DF-L | 43         | 98  | ≤ 14.3 | 71         | 98  | ≤ 15.9 | 99         | 98  | ≤ 17.4 |


## 5 DIODE VISIBILITY



DF - Diffused lens

## PHOTOMETRIC PERFORMANCE

Nominal beam spread shown, beam spread varies based on light engine. For more detailed information, see photometric data.





# VERS-NANO-LOUVER (11) FOR TUNABLE APPLICATIONS


24VDC Linear Fixtures - Surface & Recessed

## TEMPERATURE RATINGS


|     |                                  | DW 1.5 HE W/FT                        |       | DW 3.0 HE W/FT                     |       | DW 2.5 HE W/FT                        |       | DW 5.0 HE W/FT                     |       | DW 4.0 HE W/FT                        |       | DW 8.0 HE W/FT                     |       |
|-----|----------------------------------|---------------------------------------|-------|------------------------------------|-------|---------------------------------------|-------|------------------------------------|-------|---------------------------------------|-------|------------------------------------|-------|
|     |                                  | QTL power supply other than DALI, DMX |       | DALI, DMX, or non-QTL power supply |       | QTL power supply other than DALI, DMX |       | DALI, DMX, or non-QTL power supply |       | QTL power supply other than DALI, DMX |       | DALI, DMX, or non-QTL power supply |       |
|     |                                  | Min                                   | Max   | Min                                | Max   | Min                                   | Max   | Min                                | Max   | Min                                   | Max   | Min                                | Max   |
| DRY | Ambient Operating Temp - Surface | -4°F                                  | 145°F | -4°F                               | 135°F | -4°F                                  | 135°F | -4°F                               | 120°F | -4°F                                  | 125°F | -4°F                               | 110°F |
| DMP | Ambient Operating Temp - Surface | -4°F                                  | 140°F | -4°F                               | 130°F | -4°F                                  | 130°F | -4°F                               | 115°F | —                                     | —     | —                                  | —     |

## 6 INTERNAL LOUVER

INTERNAL LOUVER - LENGTHWISE







INTERNAL LOUVER - CROSSWISE



## 7 WIRE INPUT/OUTPUT





LENGTHWISE - SINGLE (Input only)

Reduced Side View Glare - Louver slats are angled towards one side of the fixture. Refer to diagrams to identify the side of the fixture with the most visual cutoff.



LENGTHWISE - PASS THROUGH (Input /Output)

Reduced Side View Glare - Louver slats are angled towards one side of the fixture. Refer to diagrams to identify the side of the fixture with the most visual cutoff.









# VERS-NANO-LOUVER (11) FOR TUNABLE APPLICATIONS

24VDC Linear Fixtures - Surface & Recessed





## CROSSWISE - SINGLE (Input only)

Reduced End View Glare - Louver slats are angled towards one end of the fixture. Refer to diagrams to identify the side of the fixture with the most visual cutoff.



## CROSSWISE - PASS THROUGH (Input /Output)









Reduced End View Glare - Louver slats are angled towards one end of the fixture. Refer to diagrams to identify the side of the fixture with the most visual cutoff.



## CONFIGURATION OPTIONS

### LENGTHWISE

Reduced Side View Glare - Louver slats are angled towards one side of the fixture. Refer to diagrams to identify the side of the fixture with the most visual cutoff.






# VERS-NANO-LOUVER (11) FOR TUNABLE APPLICATIONS

24VDC Linear Fixtures - Surface & Recessed


## CROSSWISE

Reduced End View Glare - Louver slats are angled towards one end of the fixture. Refer to diagrams to identify the side of the fixture with the most visual cutoff.




## 8 / 9 CONNECTOR/WIRE - IN/OUT


Connector/Wire In or Out not needed to specify product.



## 10 WIRE COLOR



## 12 MOUNTING






# VERS-NANO-LOUVER (11) FOR TUNABLE APPLICATIONS

24VDC Linear Fixtures - Surface & Recessed

## MOUNTING CONTINUED

TBC-05



Plastic T-Bar Clip


Use on 9/16" Tegular Drop Ceiling

2 clips provided for first 12"; 1 clip provided for each additional 12" or less length. 1 T-Bar Mounting Jig included with each fixture.

To order separately use TBC-05

Each pair of clips comes with M2.5 x 4mm set screw and Allen key


## 13 FINISH



Custom finishes require a longer lead time, consult factory. Finish is only applicable to the aluminum extrusion and endcaps. The Cover Lens and Internal Louver is always black.

## 15 EXACT/OPTIMAL FIXTURE LENGTH

Exact fixtures are the exact length specified. Optimal fixtures' length is rounded down based on LED cut points to allow the fixture to be illuminated end to end. For runs with multiple fixtures that need to fill a specific length, it's recommended to order all optimal fixtures with an exact fixture at the end of the run.






# VERS-NANO-LOUVER (11) FOR TUNABLE APPLICATIONS





24VDC Linear Fixtures - Surface & Recessed

## DW-HE DRY DMP LENGTHS BY INCH

### EXACT LENGTH

| Requested Length | Potential dim spot on either end of a S1 fixture  |
|------------------|---|
|                  | S1<br><br>End Feed |
| 12"              | 1"  |
| 13"              | 0.5"  |
| 14"              | 1"  |
| 15"              | 0.5"  |
| 16"              | 1"  |
| 17"              | 0.5"  |
| 18"              | 1"  |
| 19"              | 0.5"  |
| 20"              | 1"  |
| 21"              | 0.5"  |
| 22"              | 1"  |
| 23"              | 0.5"  |
| 24"              | 1"  |
| 36"              | 1"  |
| 48"              | 1"  |
| 60"              | 1"  |
| 72"              | 1"  |
| 84"              | 1"  |
| 96"              | 1"  |

### OPTIMAL LENGTH

| Requested Nominal Length | S1A/B & S2A/B   |  | P1A/B & P2A/B   |   |
|--------------------------|---|--|---|---|
|                          | S1<br><br>End Feed | S2<br><br>Bottom Feed | P1<br><br>End Feed | P2<br><br>Bottom Feed |
| 12"                      |   | 10.59"   |   | 10.94"  |
| 13"                      |   | 12.59"   |   | 12.94"  |
| 14"                      |   | 12.59"   |   | 12.94"  |
| 15"                      |   | 14.59"   |   | 14.94"  |
| 16"                      |   | 14.59"   |   | 14.94"  |
| 17"                      |   | 16.59"   |   | 16.94"  |
| 18"                      |   | 16.59"   |   | 16.94"  |
| 19"                      |   | 18.59"   |   | 18.94"  |
| 20"                      |   | 18.59"   |   | 18.94"  |
| 21"                      |   | 20.59"   |   | 20.94"  |
| 22"                      |   | 20.59"   |   | 20.94"  |
| 23"                      |   | 22.59"   |   | 22.94"  |
| 24"                      |   | 22.59"   |   | 22.94"  |
| 36"                      |   | 34.59"   |   | 34.94"  |
| 48"                      |   | 46.59"   |   | 46.94"  |
| 60"                      |   | 58.59"   |   | 58.94"  |
| 72"                      |   | 70.59"   |   | 70.94"  |
| 84"                      |   | 82.59"   |   | 82.94"  |
| 96"                      |   | 94.59"   |   | 94.94"  |

## COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

| DIM TO LEVEL | INDOOR  |
|--------------|---|
|              | DW-HE Tunable Applications  |
| 0.1%         | QT-CAB-eLED+DALI-DT6<br>QT-CAB-eLED+DALI-DT8<br>QT-CAB-eLED+DALI-DT8-AWN<br>QT-CAB-eLED+TW<br>QT-CAB-eLED+TW-AWN<br>QTM-eLED+DALI-DT6<br>QTM-eLED+DALI-DT8<br>QTM-eLED+DALI-DT8-AWN<br>QTM-eLED+TW<br>QTM-eLED+TW-AWN<br>QZ-DMX |
| 1%           | QZ-DALI-DT8   |
| 10%          | Non-Dim Power Supply with TW App Dongle   |



# VERS-NANO-LOUVER (11) FOR TUNABLE APPLICATIONS

24VDC Linear Fixtures - Surface & Recessed

| DIMMING PROTOCOL   | INDOOR  |
|--|---|
|  | DW-HE Tunable Applications  |
| 0-10V  | QT-CAB-eLED+TW<br>QT-CAB-eLED+TW-AWN<br>QTM-eLED+TW<br>QTM-eLED+TW-AWN  |
| Lutron Athena  | QT-CAB-eLED+DALI-DT8-AWN<br>QT-CAB-eLED+TW-AWN<br>QTM-eLED+DALI-DT8-AWN<br>QTM-eLED+TW-AWN                    |
| DMX<br>LED wattage must be doubled for DW-HE products                        | QZ-DMX  |
| DALI-2: DT6<br>LED wattage must be doubled for DW-HE products except for AWN | QT-CAB-eLED+DALI-DT6<br>QTM-eLED+DALI-DT6   |
| DALI-2: DT8<br>LED wattage must be doubled for DW-HE products except for AWN | QT-CAB-eLED+DALI-DT8<br>QT-CAB-eLED+DALI-DT8-AWN<br>QTM-eLED+DALI-DT8<br>QTM-eLED+DALI-DT8-AWN<br>QZ-DALI-DT8 |
| SCENE App Dimmed   | Non-Dim Power Supply with TW App Dongle   |

## COMPATIBLE MOUNTING ACCESSORIES

HINGE - HMB-M

Adjustable mounting bracket - Medium

HINGE - HMB-L

Adjustable mounting bracket - Large

HINGE - HMB-XL

Adjustable mounting bracket - XLarge

Q-PIVOT

Small mounting accessory

Q-ANGLE

Adjustable mounting accessory

NJ-LARGE

J Mounting Bracket

NU-LARGE

U Mounting Bracket

SD-J-LARGE

J Mounting Bracket

BL-LARGE

Backwards L Mounting Bracket

NL-LARGE

L Mounting Bracket

SD-L-LARGE

L Mounting Bracket

MMA-02

Magnet Mount Accessory for MG-02

## COMPATIBLE WIRING ACCESSORIES

Q-mini-J5

UL Listed, miniature junction box, DRY/DMP (WET rated with silicone)





# VERS-NANO-LOUVER (11) FOR TUNABLE APPLICATIONS

24VDC Linear Fixtures - Surface & Recessed

---

## COMPATIBLE CONTROL ACCESSORIES

### SCENE APP DONGLE



Wi-Fi or Bluetooth  
Connectivity

## COMPATIBLE APPS

### NFC APP



Read and write  
DMX addresses and  
adjust voltage