

# ESSENTIALS TELA-FLAT (01) STATIC COLOR

24VDC Linear Fixtures - Corner & Surface






- Corner and surface mount linear fixture
- Choose from diffused or frosted lens options
- Two-sided 90° lens
- Mounting options include stainless steel or plastic clips
- Features painted end caps to match extrusion finish
- Can be suitable for exterior use when specified as wet, contact factory for more information
- Red, Green, Blue or Amber LEDs available
- Q-Tran Red & Amber LED products are Florida Fish and Wildlife Conservation Commission certified, making them safe for turtles and other wildlife

| 1 PRODUCT | 2 WATTS/ FT | 3 CCT | 4 RATED | 5 EFFICIENCY | 6 LENS | 7 WIRE INPUT/ OUTPUT | 8 CONNECTOR/ WIRE IN | 9 CONNECTOR/ WIRE OUT | 10 WIRE COLOR | 11 WIRE TYPE | 12 MOUNTING | 13 FINISH | 14 LENGTH (IN) | 15 EXACT/ OPTIMAL |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| TL1SC | 5.0 | | | | | | | | | | | | | |

Sample Part Number: **TL1SC-5.0-GR-DRY-STD-DF-P1-BW-BW-BK-CL2-SST-BK-48"-E**

### 1 PRODUCT

**TL1SC**

See following pages for compatible power supplies.

### 2 WATTS/FT

| | |
|---|---|
| **5.0** | 5.0W/ft |

### 3 CCT

| | |
|---|---|
| **A** | Amber |
| **B** | Blue |
| **G** | Green |
| **R** | Red |

### 4 RATED

| | |
|---|---|
| **DRY** | IP20 |
| **DMP** | IP54 |
| **WET** | IP67 |

Can be suitable for exterior use, contact factory for more information

### 5 EFFICIENCY

| | |
|---|---|
| **STD** | Standard |
| **WO** | White Optics |

WhiteOptics - Internal coating, greater lumen output

### 6 LENS

| | |
|---|---|
| **DF** | Diffused |
| **FR** | Frosted |

For representation of LED visibility, see Diode Visibility section on following pages. For beam angles, see Photometric Performance section on following pages

### 7 WIRE INPUT/OUTPUT

| | |
|---|---|
| **S1** | Single 1 (Input only) - End Feed |
| **P1** | Pass Through 1 (Input/output) - End Feed |

### 8 CONNECTOR/WIRE IN

| | |
|---|---|
| **BW** | Bare Wire (Standard 24") |
| **BRL** | Barrel |
| **CON6** | Connector 6" |
| **CON24** | Connector 24" |

BW: Standard length is 24", Max length is 120". Request custom length by writing in part number next to BW (example: BW48)

### 9 CONNECTOR/WIRE OUT

| | |
|---|---|
| **CLS** | Closed End (No feed) |

| | |
|---|---|
| **BW** | Bare Wire (Standard 24") |
| **BRL** | Barrel |
| **CON6** | Connector 6" |
| **CON24** | Connector 24" |

BW: Standard length is 24", Max length is 120". Request custom length by writing in part number next to BW (example: BW48)

### 10 WIRE COLOR

| | |
|---|---|
| **WH** | White |
| **BK** | Black |
| **N/A** | For Barrel |

wet barrel only available in black

### 11 WIRE TYPE

| | |
|---|---|
| **CL2** | Class 2 |
| **CL2P** | Plenum Rated |
| **N/A** | For Barrel |

CL2P only available with bare wire leads (BW)

### 12 MOUNTING

| | |
|---|---|
| **SST** | Stainless Steel |
| **PL** | Plastic Clip |

### 13 FINISH

| | |
|---|---|
| **ST** | Satin |
| **BK** | Black |
| **BZ** | Bronze |
| **CU** | Custom |

Custom finishes require a longer lead time, consult factory

### 14 LENGTH (IN)

Minimum length is 12", maximum length is 98" not including end caps. Contact us for lengths under 12".

### 15 EXACT/OPTIMAL

| | |
|---|---|
| **O** | Optimal Illumination |
| **E** | Exact Specified Length |

Exact fixtures are the exact length specified +0 -1/8". Optimal fixtures' length is rounded down with illumination end to end. See Exact/Optimal Fixture Length charts.

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTLlighting | www.QTLlighting


Specification subject to change. Rev-11-11-26

5 year warranty | Warranty only valid with QTL power supplies | Field modifications void warranty | Data subject to change, all data has +/- 5% tolerance | FWC rated Strips: DRY and WET rated, Red and Amber


# ESSENTIALS TELA-FLAT (01) STATIC COLOR

24VDC Linear Fixtures - Corner & Surface


## 1 PRODUCT - DIMENSIONS




Profile




Profile with stainless steel mounting clip




Profile with plastic mounting clip

## 2 DELIVERED LUMENS


[Calculated L70 = 30000 hrs]
Tested with TL1SC-5.0-**-DRY-STD

| | Red | | Green | | Blue | | Amber | |
|---|---|---|---|---|---|---|---|---|
| | LM/FT | WAVELENGTH | LM/FT | WAVELENGTH | LM/FT | WAVELENGTH | LM/FT | WAVELENGTH |
| FR | 106 | 633 | 415 | 517 | 103 | 466 | 64 | 597 |
| DF | 102 | 633 | 398 | 517 | 99 | 466 | 61 | 597 |

[Calculated L70 = 30000 hrs]
Tested with TL1SC-5.0-**-DRY-WO


| | Red | | Green | | Blue | | Amber | |
|---|---|---|---|---|---|---|---|---|
| | LM/FT | WAVELENGTH | LM/FT | WAVELENGTH | LM/FT | WAVELENGTH | LM/FT | WAVELENGTH |
| FR | 116 | 633 | 455 | 517 | 113 | 466 | 70 | 597 |
| DF | 107 | 633 | 422 | 517 | 105 | 466 | 65 | 597 |

## 6 DIODE VISIBILITY




## PHOTOMETRIC PERFORMANCE

Nominal beam spread shown, beam spread varies based on light engine. For more detailed information, see photometric data.




130°

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

Specification subject to change. Rev-11-11-26

# ESSENTIALS TELA-FLAT (01) STATIC COLOR


24VDC Linear Fixtures - Corner & Surface

## TEMPERATURE RATINGS

| | | 6.0 W/FT | |
|---|---|---|---|
| | | Min | Max |
| DRY | Ambient Operating Temp - Surface | -13°F | 105°F |
| DMP | Ambient Operating Temp - Surface | -13°F | 105°F |
| WET | Ambient Operating Temp - Surface | -13°F | 100°F |


## 7 WIRE INPUT/OUTPUT

SINGLE (Input only)





End Feed

PASS THROUGH (Input/Output)





End Feed

## CONFIGURATION OPTIONS





Single End Feed





Connection by others

Non-Continuous End Feed




Connection by others


Non-Continuous Corner Feed





Continuous End to End Feed

## 8 / 9 CONNECTOR/WIRE – IN/OUT


Connector/Wire In or Out not needed to specify product. Standard configuration is BW for Wire In and CLS for Wire out





Bare Wire 24"
22 AWG




Barrel 6" - DRY/DMP | 22 AWG





Barrel 6"- WET | 22 AWG




6" or 24" Overall
Wire Connector | 22 AWG
IP67 Rated, UL Listed

## 10 WIRE COLOR



White

Black

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting


Specification subject to change. Rev-11-11-26

# ESSENTIALS TELA-FLAT (01) STATIC COLOR

24VDC Linear Fixtures - Corner & Surface

## 12 MOUNTING

**SST**





Stainless Steel Clip

2 clips provided for 4' or less; 4 clips provided for greater than 4'

To order separately use SST-03

Each clip comes with a #4 x 5/8" Flat Head SS

**PL**




Plastic Clip

2 clips provided for 4' or less; 4 clips provided for greater than 4'

To order separately use PLC-02

Each clip comes with a #4 x 5/8" Flat Head SS

## 13 FINISH



Satin

Black

Bronze


Custom finishes require a longer lead time, consult factory

## 14 EXACT/OPTIMAL FIXTURE LENGTH

E/O Length Calculator →


E/O Explained →

Exact fixtures are the exact length specified +0 -1/8". Optimal fixtures' length is rounded down based on LED cut points to allow the fixture to be illuminated end to end. For runs with multiple fixtures that need to fill a specific length, it's recommended to order all optimal fixtures with an exact fixture at the end of the run.






## SC DRY DMP LENGTHS BY INCH

**EXACT LENGTH**

| Requested Length | Potential dim spot on either end of a S1 fixture   End Feed |
|---|---|
| 12" | 1" |
| 13" | 0.5" |
| 14" | 1" |
| 15" | 0.5" |
| 16" | 1" |
| 17" | 0.5" |
| 18" | 1" |
| 19" | 0.5" |
| 20" | 1" |
| 21" | 0.5" |
| 22" | 1" |
| 23" | 0.5" |
| 24" | 1" |
| 36" | 1" |
| 48" | 1" |
| 60" | 1" |
| 72" | 1" |
| 84" | 1" |
| 96" | 1" |

**OPTIMAL LENGTH**

| Requested Nominal Length | S1   End Feed | P1   End Feed |
|---|---|---|
| 12" | 10.41" | 10.66" |
| 13" | 12.41" | 12.66" |
| 14" | 12.41" | 12.66" |
| 15" | 14.41" | 14.66" |
| 16" | 14.41" | 14.66" |
| 17" | 16.41" | 16.66" |
| 18" | 16.41" | 16.66" |
| 19" | 18.41" | 18.66" |
| 20" | 18.41" | 18.66" |
| 21" | 20.41" | 20.66" |
| 22" | 20.41" | 20.66" |
| 23" | 22.41" | 22.66" |
| 24" | 22.41" | 22.66" |
| 36" | 34.41" | 34.66" |
| 48" | 46.41" | 46.66" |
| 60" | 58.41" | 58.66" |
| 72" | 70.41" | 70.66" |
| 84" | 82.41" | 82.66" |
| 96" | 94.41" | 94.66" |


© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTLlighting | www.QTLlighting

# ESSENTIALS TELA-FLAT (01) STATIC COLOR



24VDC Linear Fixtures - Corner & Surface

## SC WET LENGTHS BY INCH

### EXACT LENGTH

| Requested Length | Potential dim spot on either end of a S1 fixture   End Feed |
|---|---|
| 12" | 1" |
| 13" | 0.5" |
| 14" | 1" |
| 15" | 0.5" |
| 16" | 1" |
| 17" | 0.5" |
| 18" | 1" |
| 19" | 0.5" |
| 20" | 1" |
| 21" | 0.5" |
| 22" | 1" |
| 23" | 0.5" |
| 24" | 1" |
| 36" | 1" |
| 48" | 1" |
| 60" | 1" |
| 72" | 1" |
| 84" | 1" |
| 96" | 1" |

### OPTIMAL LENGTH

| Requested Nominal Length | S1   End Feed | P1   End Feed |
|---|---|---|
| 12" | 10.61" | 10.76" |
| 13" | 12.61" | 12.76" |
| 14" | 12.61" | 12.76" |
| 15" | 14.61" | 14.76" |
| 16" | 14.61" | 14.76" |
| 17" | 16.61" | 16.76" |
| 18" | 16.61" | 16.76" |
| 19" | 18.61" | 18.76" |
| 20" | 18.61" | 18.76" |
| 21" | 20.61" | 20.76" |
| 22" | 20.61" | 20.76" |
| 23" | 22.61" | 22.76" |
| 24" | 22.61" | 22.76" |
| 36" | 34.61" | 34.76" |
| 48" | 46.61" | 46.76" |
| 60" | 58.61" | 58.76" |
| 72" | 70.61" | 70.76" |
| 84" | 82.61" | 82.76" |
| 96" | 94.61" | 94.76" |

## COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

| DIM TO LEVEL | INDOOR | OUTDOOR |
|---|---|---|
| | SC | SC |
| Dim to Black | Q6M-DC+CAP<br>QTM-DC+CAP<br>iQ-PH+QD1 | QOM-DC+CAP<br>QOM-PH |
| 0.1% | QT-CAB-QZ-PH/0-10V<br>QT-CAB-eLED+0-10V<br>QT-CAB-eLED+0-10V-AWN<br>QT-CAB-eLED+DALI-DT6<br>QT-CAB-eLED+DALI-DT6-AWN<br>QTM-eLED+0-10V<br>QTM-eLED+0-10V-AWN<br>QTM-eLED+DALI-DT6<br>QTM-eLED+DALI-DT6-AWN<br>QZ-BOWTIE+DIMMER<br>QZ-DMX<br>QZ-PRO-PH/0-10V<br>QZ-STICK-PH/0-10V<br>QZLP | Q-SET-QZ-DMX<br>Q-SET-QZ-PH/0-10V<br>Q-SET-eLED+0-10V<br>QOM-eLED+0-10V<br>QOM-eLED+DALI-DT6<br>QOM-eLED+DALI-DT6-PS<br>QZ-DMX<br>QZ-PRO-PH/0-10V |
| 1% | Q-DIM<br>QTM-eLED(E)<br>QZ-DALI-DT6 | Q-SET+QZ-DALI-DT6<br>QZ-DALI-DT6 |
| 10% | Non-Dim Power Supply with SW App Dongle | |

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting


# ESSENTIALS TELA-FLAT (01) STATIC COLOR

24VDC Linear Fixtures - Corner & Surface

| DIMMING PROTOCOL | INDOOR | OUTDOOR |
|---|---|---|
| | SC | SC |
| Non-Dim | QT-CAB-eLED-ND<br>QTM-eLED-ND<br>QZ-ND | Q-SET-QZ-ND<br>Q-SET-eLED-ND<br>QOM-eLED-ND<br>QZ-ND |
| Phase | Q6M-DC+CAP<br>QT-CAB-QZ-PH/0-10V<br>QTM-DC+CAP<br>QTM-eLED(E)<br>QZ-BOWTIE+DIMMER<br>QZ-PRO-PH/0-10V<br>QZ-STICK-PH/0-10V<br>QZLP<br>iQ-PH+QD1 | Q-SET-QZ-PH/0-10V<br>QOM-DC+CAP<br>QOM-PH<br>QZ-PRO-PH/0-10V |
| 0-10V | QT-CAB-QZ-PH/0-10V<br>QT-CAB-eLED+0-10V<br>QT-CAB-eLED+0-10V-AWN<br>QTM-eLED+0-10V<br>QTM-eLED+0-10V-AWN<br>QZ-PRO-PH/0-10V<br>QZ-STICK-PH/0-10V<br>QZLP | Q-SET-QZ-PH/0-10V<br>Q-SET-eLED+0-10V<br>QOM-eLED+0-10V<br>QZ-PRO-PH/0-10V |
| Lutron Athena | QT-CAB-eLED+0-10V-AWN<br>QT-CAB-eLED+DALI-DT6-AWN<br>QTM-eLED+0-10V-AWN<br>QTM-eLED+DALI-DT6-AWN | |
| ECO System | QTM-eLED(E) | |
| DMX | QZ-DMX | Q-SET-QZ-DMX<br>QZ-DMX |
| DALI-2: DT6 | QT-CAB-eLED+DALI-DT6<br>QT-CAB-eLED+DALI-DT6-AWN<br>QTM-eLED+DALI-DT6<br>QTM-eLED+DALI-DT6-AWN<br>QZ-DALI-DT6 | Q-SET+QZ-DALI-DT6<br>QOM-eLED+DALI-DT6<br>QZ-DALI-DT6 |
| SCENE App Dimmed | Non-Dim Power Supply with SW App Dongle | |


## COMPATIBLE MOUNTING ACCESSORIES

**HINGE - HMB-M**




Adjustable mounting bracket - Medium

**HINGE - HMB-L**




Adjustable mounting bracket - Large

**HINGE - HMB-XL**




Adjustable mounting bracket - XLarge

**Q-PIVOT**





Small mounting accessory

**Q-ANGLE**




Adjustable mounting accessory

**QUOVA-STANDARD**



QUOVA Knife Edge

**SD-J-LARGE**



J Mounting Bracket

**NL-LARGE**



L Mounting Bracket

**NJ-MEDIUM**



J Mounting Bracket

**SD-L-MEDIUM**



L Mounting Bracket


## COMPATIBLE WIRING ACCESSORIES

**Q-mini-J**




UL Listed, miniature junction box, DRY/DMP (WET rated with silicone)

**Q-mini-J5**




UL Listed, miniature junction box, DRY/DMP (WET rated with silicone)

**BARREL-EXT**



8ft barrel cable extender
DRY ONLY

**BARREL FOUR-FER**



Splits lead from one to four LED Barrel connector fixtures, DRY/DMP

**CON120-EXT**



10ft Con cable extender
DRY/DMP/WET

**CON FOUR-FER**



Splits lead from one to four LED Con connectors
DRY/DMP/WET

**CON M - BARREL F**



Male con to barrel cable adaptor
DRY/DMP

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting

Specification subject to change. Rev-11-11-26

# ESSENTIALS TELA-FLAT (01) STATIC COLOR

24VDC Linear Fixtures - Corner & Surface

## COMPATIBLE APPS

**NFC APP**

Q-NFC

Read and write DMX addresses and adjust voltage

© 2026 QTL. All rights reserved | 155 Hill St. Milford, CT 06460 | 203-367-8777 | sales@QTL.lighting | www.QTL.lighting