



QZLC

24V DC Power Supply - 96W



- Versatile Class 2 LED driver controlled with phase (forward or reverse) or 0-10V dimming down to 1%
- Pulse Width Modulation (PWM) output provides smooth flicker-free dimming
- 24VDC constant voltage output
- Housing is listed for indoor or outdoor use

1	2	3	4	5	6
PRODUCT	WATTAGE	PRIMARY VOLTAGE	SECONDARY VOLTAGE	CONTROL	COLOR
QZLC	96W	UNV	24V	PH/010	BK

Sample Part Number: QZLC-96W-UNV-24V-PH/010-BK

1	2	3	4
PRODUCT	WATTAGE	PRIMARY VOLTAGE	SECONDARY VOLTAGE
QZLC	96W	UNV Universal (120-277V)	24V
5	6		
CONTROL	COLOR		
PH/010 Phase or 0-10V dimming	BK Black Powder Coat Finish		

COMPATIBLE LEDS

STATIC WHITE

SW24/1.5-4.0 SW-DR24/1.5-4.0 SHLD-SW24/1.5-4.0	✓
SW24/5.0, SW-HE, SW-HE+ SW-DR24/5.0, SW-HE-DR SHLD-SW24/5.0, SHLD-SW-HE	✓
SD-SW24/1.0-4.0	✓
SD-SW24/6.0	✓
SW-1A	
SW-XT	✓

OTHER

DW-HE Tunable Applications	
DW-HE Warm Dim Applications	
WD	✓
SC	✓
RGB	
RGBW, RGBW-HE	

SHEETS

Q-SHEETS SW	✓
Q-SHEETS DW Tunable Applications	
Q-SHEETS DW Warm Dim Applications	
Q-SHEETS RGB	
Q-SHEETS RGBW	

MICRO 5

MICRO 5-SW	✓
MICRO 5-DW Tunable Applications	
MICRO 5-DW Warm Dim Applications	
MICRO 5-RGB	

PRODUCT INFORMATION

- Vertical or horizontal surface mount
- Constant voltage output
- PH/010 Dimming:
 - Phase dimming: works with forward phase / leading edge, MLV and Reverse phase / trailing edge, ELV, TRIAC dimmers
 - Dimming range: 1% - 100%
 - 0-10V dimming
 - 1-10V dimming
 - Flicker-free dimming
 - PWM (high frequency) output reduces visible flicker
- WET listed
- Follows recommended practices of IEEE standard P1789 to mitigate flicker-induced health risks
- Suitable for dry, damp and wet locations
- Suitable for indoor & outdoor use
- Primary voltage - universal (110-277V)
- Wide operating temperature range: -40°F to +140°F
- UL, cUL listed
- Type HL rated
- Compliant to FCC Part 15B
- 5 year warranty



QZLC

24V DC Power Supply - 96W

VOLTAGE DROP CHART

Wiring from power supply to light fixture must be two conductor cable

VDC	Load (W)	Distance from PS for 5% Voltage Drop								
		10 AWG	12 AWG	14 AWG	16 AWG	18 AWG	20 AWG	22 AWG	24 AWG	26 AWG
24	15	961	605	380	239	150	95	60	37	24
	30	481	302	190	120	75	47	30	19	12
	60	240	151	95	60	38	24	15	9	6
	80	180	113	71	45	28	18	11	7	4
	96	150	95	59	37	24	15	9	6	4

VDC	Load (W)	Distance from PS for 3% Voltage Drop								
		10 AWG	12 AWG	14 AWG	16 AWG	18 AWG	20 AWG	22 AWG	24 AWG	26 AWG
24	15	577	363	228	143	90	57	36	22	14
	30	288	181	114	72	45	28	18	11	7
	60	144	91	57	36	23	14	9	6	4
	80	108	68	43	27	17	11	7	4	3
	96	90	57	36	22	14	9	6	4	2


VDC	Load (W)	Distance from PS for 1% Voltage Drop								
		10 AWG	12 AWG	14 AWG	16 AWG	18 AWG	20 AWG	22 AWG	24 AWG	26 AWG
24	15	192	121	76	48	30	19	12	8	5
	30	96	61	38	24	15	10	6	4	2
	60	48	30	19	12	8	5	3	2	1
	80	36	23	14	9	6	4	2	1	1
	96	30	19	12	8	5	3	2	1	1

1 PRODUCT - DIMENSIONS

Size	Length (in)	Width (in)	Height (in)
96W	8.68	3.75	1.58

2 TECHNICAL INFORMATION

Wattage	Primary Voltage	Secondary Voltage	Secondary Current
96W	110-277V	24VDC	1x4 A





QZLC
24V DC Power Supply - 96W

SPECIFICATIONS

Input	
Input Voltage (Vrms)	110-277V
Input Current, max (Arms)	1.3A @ 110V
Inrush Current, max* (Apk)	43A@277V
Input Frequency (Hz)	50/60Hz
Input Power (W)	112W

Output	
Output Voltage, nom (V)	24V
Output Current (A)	4A
Output Power (Wmax)	96W

Environmental	Min	Nom	Max
THD (%)	-	-	20
PF (%)	0.98	-	-
Working Temp (°F)	-	-	140

*-200us event

NOTE: All measurement done at 120V AC unless specified.

PROTECTIONS

- Short Circuit Protection (SCP)Over Loading Protection (OLP)Over Temperature Protection (OTP)I/P-O/P: 1.8KVACI/P-O/P: 100MΩ / 500VDC / 77°F / 70%RH


6 COLOR



Black Powder
Coat Finish

COMPLIANCE

- EMI/RFI
 - FCC 47 CFR Part 15 Subpart B
- Certified
 - UL8750







QZLC

24V DC Power Supply - 96W

PHASE DIMMING



0-10V DIMMING



Wiring from power supply to light fixture must be two conductor cable

COMPATIBLE WIRING ACCESSORIES

