





# Q-CAP KURV™ RGB

## 24VDC Flexible Fixtures



- Flexible encapsulated fixture
- Side bend
- 6" bend radius
- Interior and exterior rated (not including FC)
- Seven different mounting options
- Available in a seamless configuration for a continuous line of light
- Utilize clear endcaps for continuous runs
- Do not cut Non-Field Cuttable Q-CAP flexible fixtures
- IK10 impact rated

### ORDERING PROCESS

- A** Specify Non-Field Cuttable Q-CAP      **B** (Optional) Specify field cuttable 4' piece - used to adjust total run length in the field (dry applications only)

### A. NON-FIELD CUTTABLE Q-CAP

A1	A2	A3	A4	A5	A6	A7	A8	A9	A10	A11	A12
PRODUCT	MOUNTING	RATED	CCT	WATTAGE	LENS	WIRE INPUT/OUTPUT	CONNECTOR/WIRE IN	CONNECTOR/WIRE OUT	END CAPS	LENGTH (IN)	EXACT/OPTIMAL
KURV-RGB			RGB	6.0							

Sample Part Number: **KURV-RGB-PPS-2-DRY-RGB-6.0-ENC/TL-P1-BW-BW-N/A-48"-E**

<b>A1</b> <b>PRODUCT</b>  <b>KURV-RGB</b>  See last page for compatible power supplies.	<b>A2</b> <b>MOUNTING</b>  <b>RLC</b> Rigid Lock Channel <b>MC</b> Magnetic Clip <b>SGC</b> Side Graze Channel <b>PPS-2</b> PVC Clip <b>PPS-96</b> PVC Channel <b>PPS-LP-2</b> PVC Low Profile Clip <b>PPS-LP-96</b> PVC Low Profile Channel <b>WSC</b> White Snug Clip <b>BN-SB-SST-16'</b> 16" BENDIT Side Stainless Steel Channel <b>BN-SB-SST-32'</b> 32" BENDIT Side Stainless Steel Channel <b>BN-SB-WH-16'</b> 16" BENDIT Side White Stainless Channel <b>BN-SB-WH-32'</b> 32" BENDIT Side White Stainless Channel  White snug clip only for indirect cove use, not intended for hanging fixtures upside down. PPS mounting clip recommended for seamless applications	<b>A3</b> <b>RATED</b>  <b>DRY</b> IP20 <b>WET</b> IP67	<b>A4</b> <b>CCT</b>  <b>RGB</b>	<b>A5</b> <b>WATTAGE</b>  <b>6.0</b> 6.0W-SO SO: Standard Output	<b>A6</b> <b>LENS</b>  <b>ENC/CL</b> Encapsulated in Clear <b>ENC/TL</b> Encapsulated in Translucent  For representation of LED visibility, see Diode Visibility section on following pages	<b>A7</b> <b>WIRE INPUT/OUTPUT</b>  <b>S1</b> Single 1 (Input only) - End Feed <b>S2</b> Single 2 (Input only) - Bottom Feed <b>S3</b> Single 3 (Input only) - Left Side Feed <b>S4</b> Single 4 (Input only) - Right Side Feed  <b>P1</b> Pass Through 1 (Input/Output) - End Feed <b>P2</b> Pass Through 2 (Input/Output) - Bottom Feed <b>P3</b> Pass Through 3 (Input/Output) - Left Side Feed <b>P4</b> Pass Through 4 (Input/Output) - Right Side Feed	<b>A8</b> <b>CONNECTOR/WIRE IN</b>  <b>BW</b> Bare Wire (Standard 24") <b>CON6</b> Connector 6" <b>CON24</b> Connector 24"  BW: Standard length is 24". Max length is 120". Request custom length by writing in part number next to BW (example: BW48)  <b>BW</b> Bare Wire (Standard 24") <b>CON6</b> Connector 6" <b>CON24</b> Connector 24"  BW: Standard length is 24". Max length is 120". Request custom length by writing in part number next to BW (example: BW48)	<b>A9</b> <b>CONNECTOR/WIRE OUT</b>  <b>N/A</b> Closed End (No feed)  <b>BW</b> Bare Wire (Standard 24") <b>CON6</b> Connector 6" <b>CON24</b> Connector 24"  BW: Standard length is 24". Max length is 120". Request custom length by writing in part number next to BW (example: BW48)	<b>A10</b> <b>END CAPS</b>  <b>CL</b> Clear <b>WH</b> White  <b>N/A</b> Not Applicable	<b>A11</b> <b>LENGTH (IN)</b>  Minimum length is 12", maximum length is 191" not including end caps. Contact us for lengths under 12". Available in 2" increments.	<b>A12</b> <b>EXACT/OPTIMAL</b>  <b>O</b> Optimal Illumination <b>E</b> Exact Specified Length  Exact fixtures are the exact length specified +0 - 1/8". Optimal fixtures' length is rounded down with illumination end to end. See Exact/Optimal Fixture Length charts.
--	--	---	---	--	---	---	---	---	--	---	--

5 year warranty | Side Bend | Data subject to change, all data has +/- 5% tolerance | Ambient or mounting surface must not be lower than -4°F or higher than 125°F | Patent # D863646 S, 10,619,828 B2 | Only FC fixtures are Field-Cuttable per installation instructions | Field Cuttable is not returnable or refundable after it has been cut



Q-CAP KURV™ RGB  
24VDC Flexible Fixtures

B. FIELD CUTTABLE Q-CAP

B1	B2	B3	B4	B5	B6	B7	B8	B9	B10	B11	B12
PRODUCT	MOUNTING	RATED	CCT	WATTAGE	LENS	WIRE INPUT/ OUTPUT	CONNECTOR/ WIRE IN	CONNECTOR/ WIRE OUT	END CAPS	LENGTH (IN)	EXACT/ OPTIMAL
KURV-FC-RGB		DRY	RGB	6.0				N/A	CL	48"	N/A

Sample Part Number: KURV-RGB-PPS-2-DRY-RGB-6.0-ENC-TL-P1-BW-BW-N/A-48"-E

B1

PRODUCT

KURV-FC-RGB

See last page for compatible power supplies.

B2

MOUNTING

RLC

MC

SGC

PPS-2

PPS-96

PPS-LP-2

PPS-LP-96

WSC

BN-SB-SST-16'

BN-SB-SST-32'

BN-SB-WH-16'

BN-SB-WH-32'

Rigid Lock Channel

Magnetic Clip

Side Graze Channel

PVC Clip

PVC Channel

PVC Low Profile Clip

PVC Low Profile Channel

White Snug Clip

16" BENDIT Side Stainless Steel Channel

32" BENDIT Side Stainless Steel Channel

16" BENDIT Side White Stainless Channel

32" BENDIT Side White Stainless Channel

White snug clip only for indirect cove use, not intended for hanging fixtures upside down.

PPS mounting clip recommended for seamless applications

B3

RATED

DRY IP20

B4

CCT

RGB

B5

WATTAGE

6.0 6.0W-SO

SO: Standard Output

B6

LENS

ENC/CL Encapsulated in Clear

ENC/TL Encapsulated in Translucent

For representation of LED visibility, see Diode Visibility section on following pages

B7

WIRE INPUT/OUTPUT

S1

S2

S3

S4

Single 1 (Input only) - End Feed

Single 2 (Input only) - Bottom Feed

Single 3 (Input only) - Left Side Feed

Single 4 (Input only) - Right Side Feed

B8

CONNECTOR/WIRE IN

BW

CON6

CON24

Bare Wire (Standard 24")

Connector 6"

Connector 24"

BW: Standard length is 24". Max length is 120". Request custom length by writing in part number next to BW (example: BW48)

B9

CONNECTOR/WIRE OUT

N/A Closed End (No feed)

B10

END CAPS

CL Clear

Due to cutting, white endcaps are not available.

B11

LENGTH (IN)

48" Nominal

Starting Run length is 48.55" for S1 and 48.75" for S2, S3, S4

Each cut point subtracts from the Starting Run Length

6.0 has a 2" cut point

S2, S3, & S4 can be cut down to as little as 2.75"

S1 can be cut down to as little as 2.55"

B12

EXACT/OPTIMAL

N/A


Single ▶




# Q-CAP KURV™ RGB

24VDC Flexible Fixtures


## 1 PRODUCT - DIMENSIONS



Profile  
(Standard)




Profile  
(Seamless bare wire)



Profile  
(Seamless CON6-24)


## BEND RADIUS

### Side Bend




6" bending radius

## FLEXIBILITY



## 2 MOUNTING

### WSC




White Snug Clip  
Indirect uplight

To order separately use WSC

Each clip comes with a #6x5/8" flat screw

### RLC




Rigid Lock Channel

To order separately use RLC

Each clip comes with a #6x5/8" flat screw

### MC




Magnetic Clip  
Cove use only

To order separately use MC

Each clip comes with a #6x5/8" flat screw

### SGC




Side Graze Clip

To order separately use SGC

Each clip comes with a #6x5/8" flat screw

### PPS-2



PVC Mounting Clip

To order separately use KURV-PPS2



# Q-CAP KURV™ RGB

## 24VDC Flexible Fixtures

### MOUNTING CONTINUED

**PPS-96**

96" straight linear run

To order separately use KURV-PPS-96

Each clip comes with a #8" flat screw

**PPS-LP-2**

Low profile PVC Mounting Clip

To order separately use KURV-PPS-LP-2

**PPS-LP-96**

Low profile PVC channel 96" straight linear run

To order separately use KURV-PPS-LP-96

Each clip comes with a #8" flat screw

**BN-SB**

BENDIT Channel  
Horizontal Stainless Steel Flexible Channel

Continuous mounting solution for flexible fixtures, 16' or 32' field cuttable lengths

To order separately use either STND-QCAP-BN-SB-SST-16', STND-QCAP-BN-SB-SST-32', STND-QCAP-BN-SB-WH-16', or STND-QCAP-BN-SB-WH-32'

64 #4-40 1/2" screws provided per 16'

### 4 / 5 DELIVERED LUMENS

[Calculated L70 = 40000 hrs]  
Tested with KURV-RGB-WSC-DRY

CCT	6.0W/FT Total Load				
	ENC/CL		ENC/TL		Circuit Wattage
	LM	Wavelength	LM	Wavelength	
Red	78	630	71	631	2.4
Green	152	521	135	523	1.9
Blue	46	468	41	469	1.7
All	255	-	229	-	6.0

### 6 DIODE VISIBILITY

ENC/CL - Clear encapsulation

ENC/TL - Translucent encapsulation

### BUG RATING

WATTAGE	B	U	G
6.0 (ALL CCTs)	B0	U1	G0

### TEMPERATURE RATINGS

	6.0 W/FT	
	Min	Max
Ambient Operating Temp - Surface	-13°F	176°F
Storage Temp	-4°F	140°F
Installation Temp	50°F	100°F

### 7 WIRE INPUT/OUTPUT

SINGLE (Input only)

**S1**

End Feed

**S2**

Bottom Feed

**S3**

Side Feed - Left

**S4**

Side Feed - Right

PASS THROUGH (Input/Output) - Only applicable for Non-Field Cuttable Q-CAP

**P1**

End Feed

**P2**

Bottom Feed

**P3**

Side Feed - Left

**P4**


Side Feed - Right




# Q-CAP KURV™ RGB

## 24VDC Flexible Fixtures


### CONFIGURATION OPTIONS



### FIELD CUTTABLE MARKING




Field cuttable fixtures are sold in 4' increments and go at the end of a run, allowing for easy field adjustment




**Note:** Only FC fixtures are field cuttable — Do not attempt to cut non FC fixtures.  
Cut only on the marked cut lines. Only cut from non-feed end. Do not attempt to cut while power is on.

### 8 / 9 CONNECTOR/WIRE - IN/OUT


Connector/Wire In or Out not needed to specify product. Typical selection is S1 for Wire Input/Output, BW for Connector/Wire In, N/A for Connector/Wire Out, and WH for End Caps



### 10 END CAPS (NO FEED)




### END CAPS (WITH FEED)



### 11 LENGTH - WIRING DETAIL

Available in 2" increments 12"-191"






# Q-CAP KURV™ RGB

## 24VDC Flexible Fixtures

### 12 EXACT/OPTIMAL FIXTURE LENGTH

[E/O Length Calculator →](#)[E/O Explained →](#)

Exact fixtures are the exact length specified. Optimal fixtures' length is rounded down based on LED cut points to allow the fixture to be illuminated end to end. For runs with multiple fixtures that need to fill a specific length, it's recommended to order all optimal fixtures with an exact fixture at the end of the run.



## RGB LENGTHS BY INCH

Available in any length in between 12" and 191", chart below shows example lengths. Exact fixtures are the length specified. Optimal fixtures' length is rounded down with illumination end to end. All fixtures' tolerance is +0 - 1/8". Consult factory for lengths under 12".

### EXACT LENGTH

Requested Length	Potential dim spot on either end of fixture with S1 wireway
12"	1"
13"	.5"
14"	1"
15"	.5"
16"	1"
17"	.5"
18"	1"
19"	.5"
20"	1"
21"	.5"
22"	1"
23"	.5"
24"	1"
36"	1"
48"	1"
60"	1"
72"	1"
84"	1"
96"	1"

### OPTIMAL LENGTH: highlighted rows are closest to requested nominal length

Requested Nominal Length	S1	S2	S3	S4	P1	P2	P3	P4
	End Feed	Bottom Feed	Side Feed - Left	Side Feed - Right	End Feed	Bottom Feed	Side Feed - Left	Side Feed - Right
12"	10.58"		10.91"		10.95"		11.63"	
13"	12.58"		12.91"		12.95"		11.63"	
14"	12.58"		12.91"		12.95"		13.63"	
15"	14.58"		14.91"		14.95"		13.63"	
16"	14.58"		14.91"		14.95"		15.63"	
17"	16.58"		16.91"		16.95"		15.63"	
18"	16.58"		16.91"		16.95"		17.63"	
19"	18.58"		18.91"		18.95"		17.63"	
20"	18.58"		18.91"		18.95"		19.63"	
21"	20.58"		20.91"		20.95"		19.63"	
22"	20.58"		20.91"		20.95"		21.63"	
23"	22.58"		22.91"		22.95"		21.63"	
24"	22.58"		22.91"		22.95"		23.63"	
36"	34.58"		34.91"		34.95"		35.63"	
48"	46.58"		46.91"		46.95"		47.63"	
60"	58.58"		58.91"		58.95"		59.63"	
72"	70.58"		70.91"		70.95"		71.63"	
84"	82.58"		82.91"		82.95"		83.63"	
96"	94.58"		94.91"		94.95"		95.63"	

## COMPATIBLE POWER SUPPLIES

See power supplies cut sheets for more information. Data subject to change, all data has +/- 5% tolerance.

DIM TO LEVEL	INDOOR	OUTDOOR
	RGB	RGB
0.1%	QT-CAB-eLED+DALI-DT8 QT-CAB-eLED+DMX QTM-eLED+DALI-DT8 QTM-eLED+DMX QZ-DMX	Q-SET-QZ-DMX QOM-eLED+DALI-DT8 QOM-eLED+DMX QOM-eLED+PS-DALI-DT8 QZ-DMX
1%	QZ-DALI-DT8	Q-SET+QZ-DALI-DT8 QZ-DALI-DT8
10%	Non-Dim Power Supply with RGB App Dongle	



# Q-CAP KURV™ RGB

24VDC Flexible Fixtures

DIMMING PROTOCOL	INDOOR	OUTDOOR
	RGB	RGB
DMX	QTM-eLED+DMX QZ-DMX	Q-SET-QZ-DMX QOM-eLED+DMX QZ-DMX
DALI-2: DT8	QT-CAB-eLED+DALI-DT8 QTM-eLED+DALI-DT8 QZ-DALI-DT8	Q-SET+QZ-DALI-DT8 QOM-eLED+DALI-DT8 QZ-DALI-DT8

## COMPATIBLE MOUNTING ACCESSORIES

**Q-ANGLE**

Adjustable mounting accessory

**NJ-LARGE**

J Mounting Bracket

**NU-LARGE**

U Mounting Bracket

**SD-J-LARGE**

J Mounting Bracket

**BL-LARGE**

Backwards L Mounting Bracket

**NL-LARGE**

L Mounting Bracket

**SD-L-LARGE**

L Mounting Bracket

**IQ-QCAP-UNV-CUTTER**

QTL recommended FC Cutter

## COMPATIBLE WIRING ACCESSORIES

**Q-mini-J5**

UL Listed, miniature junction box, DRY/DMP (WET rated with silicone)

## COMPATIBLE CONTROL ACCESSORIES

**SCENE APP DONGLE**

Wi-Fi or Bluetooth Connectivity

## COMPATIBLE APPS

**NFC APP**

Read and write DMX addresses and adjust voltage